



Luxwood Technical Specifications

Description: Luxury Engineered Plank, Floating Floor with Attached EVA Pad

Warranty: Limited Lifetime Residential Wear Warranty
Limited Lifetime Waterproof Warranty
Limited Lifetime Structural Warranty
15 Year Limited Lt. Commercial Warranty

Installation: Unilin Click - Float, Glue Down

Construction: Stone Core Composite (70% Limestone with virgin PVC)
Luxwood – 20 mil wear layer with 1.5mm EVA Pad

Size/Packing: Luxwood – 7.25” x 48” x 6.5mm Planks
24.14 sf/box, 10 planks/box, 53.20 lbs/box, 45 boxes/pallet

Wear Finish: 2 layered Ceramic Bead, Aluminum Oxide Finish with Antimicrobial surface

TEST DATA

ASTM – E90-09 Airborne Sound Conduction:	STC 63 db
ASTM – E492-09 Impact Sound Conduction:	IIC 65 db / ΔIIC 21
ANSI A137.1 Dynamic Coefficient of Friction Test:	0.52 DCOF
ASTM F970-00 Static Load	1500 PSI (0.008 of an inch)
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Δ E Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Δ E Requirement

Additional results visit: www.iwtttesoro.com

