

NICE TOONA 6 THE FASTER CHOICE IN SWING GATE AUTOMATION

THE NEW MOTOR FOR LEAVES UP TO 6 M:
FASTER AND STURDY, DESIGNED FOR INDUSTRIAL
OPERATION WITH INTENSIVE USE.

The image shows a white van driving past a grey swing gate in an industrial setting. The gate is partially open, and a motor unit is visible on the concrete wall. The background includes a building with large windows and trees under a clear sky.

Nice

TOONA 6

SOLEMYO OPERA BLUEBUS 24V

For swing gates with leaves up to 6 m.

Electromechanical gear motor, surface mounted, powered at 24 Vdc, with magnetic encoder. Ideal for industrial installations, designed for intensive use.

Reliable: durability thanks to the housing, made up of two tough aluminium shells with polyester paint finish; more resistant to atmospheric agents.

Internal moving parts completely in steel, light alloys and technopolymers.

Silent: patented layout of internal parts and lead nut in bronze.

Generously sized and practical connection compartment: rapid and easy access from above to internal parts located in the upper section of the motor.


Moonclever MC824H/V1 control unit:

- simple programming, by means of a single key;
- self-learning of opening and closing limit positions;
- automatic fault diagnostics;
- programming of pause time;
- pedestrian pass door;
- deceleration on opening and closing;
- obstacle detection with dual technology;
- operation in event of power failure by means of optional rechargeable batteries (PS324);
- provision for connection of latest generation resistive sensitive edges.

CODE	DESCRIPTION	CERTIFICATION
T06024	IRREVERSIBLE, 24 Vdc, WITH MAGNETIC ENCODER, MECHANICAL STOP ON OPENING AND CLOSING	

TECHNICAL SPECIFICATIONS

CODE	T06024
ELECTRICAL DATA	
POWER SUPPLY (Vac 50 Hz)	-
POWER SUPPLY (Vdc)	24
ABSORPTION (A)	5
POWER (W)	120
PERFORMANCE DATA	
SPEED (m/s)	0,016
FORCE (N)	2200
WORK CYCLE (CYCLES/HOUR)	41
DIMENSIONAL AND GENERAL DATA	
PROTECTION LEVEL (IP)	44
WORKING TEMP. (°C MIN/MAX)	-20 ÷ +50
DIMENSIONS (mm)	1200x128x150 h
WEIGHT (kg)	15



ACCESSORIES



PLA10
VERTICAL 12 V ELECTRIC
LOCK (REQUIRED FOR GATES
LONGER THAN 3 m).




PLA11
HORIZONTAL 12 V ELECTRIC LOCK
(REQUIRED FOR GATES
LONGER THAN 3 m).




PS324
24 V BATTERY
WITH INTEGRATED
BATTERY CHARGER.

UTILISATION LIMITS




The shape, the height of the gate and the weather conditions can considerably reduce the values shown in the graph to the side.

DIMENSIONS



INSTALLATION DIAGRAM



1. MOTOR
2. TRANSMITTER
3. PHOTOCELLS MOUNTED ON POSTS
4. PHOTOCELLS
5. FLASHING LIGHT
6. CONTROL UNIT
7. DIGITAL OR KEY SWITCHES
8. SYP SOLAR PANEL
9. PSY24 BATTERY BOX
10. 0-VIEW MULTIFUNCTION DISPLAY

● Solemyo SOLAR POWER ACCESSORIES

NICE TOTAL CONTROL

INTEGRATED SOLUTIONS FOR THE HOME.
EASE OF USE, AESTHETIC QUALITY, SAFETY.

NICE KEEPS THE HOME UNDER CONTROL
WITH JUST A FEW, SIMPLE GESTURES.

THANKS TO THE NEW ERA TOUCH CONTROL UNIT,
AUTOMATIONS FOR GATES, GARAGE DOORS
AND ROLLING DOORS, AWNINGS AND SHUTTERS
CAN ALL BE MANAGED THROUGH A SINGLE
SUPPORT, AS LIGHTING SYSTEMS.

NICE IS INNOVATIVE SOLUTIONS
THAT SIMPLIFY LIFE.



Nice

Nice SpA
Oderzo TV Italy
Ph. +39.0422.85.38.38
info@niceforyou.com

Find out more about Nice
products and services on the website:
www.niceforyou.com



NiceLoveEarth

Nice cares for the environment.
Using natural paper it avoids excessive
use of raw materials and forest
exploitation. Waste is reduced, energy
is saved and climate quality is improved.