

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Advanced Atlas

TECHNICAL CHARACTERISTICS

Available Formats:	7x45		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	12
Thickness in mm:	9.5mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	3	Surface Type:	Satin, Textured
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	.45
Scratch Hardness (MOHS)	5	Breaking Strength:	UNE-EN-ISO 10545-4 pass
Frost Resistant:	Yes	Thermal Shock Resistance:	UNE-EN-ISO 10545-9 pass
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	UNE-EN-ISO 10545-11		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.44	Pieces per Carton:	5
SqFt per Pallet:	657.72	Pounds per Carton:	47.71
Boxes per Pallet:	63	SqFt per Container:	12496.68
Pallets per Container:	19		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".