

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME **Terranova**

TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 3x24 Bullnose Matte & Glossy		
Style Description:		Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Glossy Marble	Number of Faces/Screens:	
Thickness in mm:	11 mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte & Glossy
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.01%	Static COF:	Wet: 0.37 Dry: 0.89
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.19
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Type 5		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	4
SqFt per Pallet:	620.00	Pounds per Carton:	74.09
Boxes per Pallet:	40	SqFt per Container:	14260.00
Pallets per Container:	23		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".