

LAKE MICHIGAN SALES

Relationships Matter • People Make the Difference


Manufacturer's Representative

1900 Estes Avenue
Elk Grove Village, Illinois 60007
o: 847-378-8045 f: 847-307-8975
www.lakemichigansales.com
sales@lakemichigansales.com

NOW STOCKING EIKO® LED!!

Please contact sales@lakemichigansales.com for pricing & more information.

(Full list of stocked LED SKUs on back)



SLM Slim Panels

LED Edge-lit Slim Panels to replace 2X2 and 2X4 Troffers



VOL Volumetric Troffers

LED Volumetric Troffers to replace 2X2 and 2X4 Troffers



LLH Highbay

LED Linear Highbay to replace 4 Lamp T8s to 6 Lamp T5s



HID Replacements

LED replacements for 50W-600W HID lamps

CFL Replacements

LED PL CFL Replacements to replace 26/32W compact fluorescent



LLW Surface Wrap

LED Linear Surface Wrap Fixture to replace T8



Surface Canopy Round

LED Shallow Round Surface Canopy Fixture



T5 LED Lamps

Direct Replacement LED T5 Lamps (Uses existing ballast)

***On BILD List**



T8 LED Lamps

Line Voltage (120-277V) and Direct Replacement LED T8 Lamps (uses existing ballast)

***Direct Replacement on BILD List**



Incandescent Replacements

LED A19s, A21s, G25s, BR20s, BR30s, and MR16s to replace various incandescent wattages

*** Select SKUs on BILD List**

Full spec sheets can be found at www.eiko.com.

NOW STOCKING EIKO LED!!

Please contact sales@lakemichigansales.com for pricing & more information.

Elk Grove Warehouse: 1900 Estes Ave, Elk Grove Village, Illinois 60007

office: 847-378-8045 fax: 847-307-8975

Item	Description
LED100WPT40KMOG-G6	LED Litespan HID Replacement 100W 12000lm 4K 80CRI EX39 univ burn 120-277V
LED100WPT50KMOG-G6	LED Litespan HID Replacement 100W 12000lm 5K 80CRI EX39 univ burn 120-277V
LED11WA19/300/827K-DIM-G5	LED LiteSpan A19 Omni-Directional 300 Degree Beam, 11W - 1100lm, Dimmable, 2700K, E26
LED11WA19/300/840K-DIM-G5	LED LiteSpan A19 Omni-Directional 300 Degree Beam, 11W - 1100lm, Dimmable, 4000K E26
LED11WA19/OMN/830K-DIM-G7 2PK	LED Litespan A19 Omni-directional 11W-1100lm Dim 80CRI 3000K E26 120VAC 2 Pack
LED11WBR30/827K-DIM-G5	LED LiteSpan BR30 Reflector Flood, 11W - 850lm, Dimmable, 2700K, 80+CRI, 120VAC
LED11WBR30/830K-DIM-G5	LED LiteSpan BR30 Reflector Flood, 11W - 850lm, Dimmable, 3000K, 80+CRI, 120VAC
LED11WBR30/840K-DIM-G5	LED LiteSpan BR30 Reflector Flood, 11W - 850lm, Dimmable, 4000K, 80+CRI, 120VAC
LED12WT8/PRM/48/840-G7D	GLASS BALLAST BYPASS PREMIUM DLC V4.0 T8 4FT 12.5W-1800LM 4000K NON-DIM 80CRI 120-277V
LED12WT8/PRM/48/850-G7D	GLASS BALLAST BYPASS PREMIUM DLC V4.0 T8 4FT 12.5W-1800LM 5000K NON-DIM 80CRI 120-277V
LED14WT8/P/48/850-G7D	5000K NANO POLYCARB BALLAST BYPASS T8 4FT 14W-1800LM 5000K NON-DIM 80CRI 120-277V
LED15WA21/300/830K-DIM-G5	LED LiteSpan A21 Omni-Directional 300 Degree Beam, 15W - 1600lm, Dimmable, 3000K, E26
LED15WT8F/48/835K-G7D	Glass Ballast Bypass DLC T8 4FT 15W-1800LM 3500K 80CRI Bi-Pin 120-277VAC
LED15WT8F/48/840K-G7D	Glass Ballast Bypass DLC T8 4FT 15W-1800LM 4000K 80CRI Bi-Pin 120-277VAC
LED15WT8F/48/840K-G7DM	Glass Ballast/AC Dual Mode DLC T8 4FT 15W-1800LM 4000K 80CRI Bi-Pin 120-277VAC
LED15WT8F/48/850K-G7D	Glass Ballast Bypass DLC T8 4FT 15W-1800LM 5000K 80CRI Bi-Pin 120-277VAC
LED15WT8F/48/850K-G7DM	Glass Ballast/AC Dual Mode DLC T8 4FT 15W-1800LM 5000K 80CRI Bi-Pin 120-277VAC
LED17WPAR38/FL/830K-DIM-G4A	LED LiteSpan PAR38, Flood 40 Degree Beam, 17W - 1300lm, Dimmable, 3000K, 80+CRI,
LED18T8F/48/835-G6DR	GLASS Ballast Compatible T8 1800lm 14W 4ft G13 Bi-Pin 80+CRI 3500K Froste
LED18T8F/48/840-G6DR	GLASS Ballast Compatible T8 1800lm 14W 4ft G13 Bi-Pin 80+CRI 4000K Froste
LED18T8F/48/850-G6DR	GLASS Ballast Compatible T8 1800lm 14W 4ft G13 Bi-Pin 80+CRI 5000K Froste
LED18T8F/U6/850-G5DR	GLASS DIRECT FIT T8 6 INCH UBEND NON-DLC 12W-1800LM 5000K NON-DIM 80CRI 120-277V
LED18WT8F/48/840-G7D	GLASS BALLAST BYPASS DLC V4.0 T8 4FT 18W-2200LM 4000K NON-DIM 80CRI 120-277V
LED18WT8F/48/850-G7D	GLASS BALLAST BYPASS DLC V4.0 T8 4FT 18W-2200LM 5000K NON-DIM 80CRI 120-277V
LED19WPT40KMED-G7	LED HID REPLACEMENT 19W-2375LM 4000K 80CRI NON-DIM E26 UNIV BURN POS 100-277V
LED19WPT50KMED-G7	LED HID REPLACEMENT 19W-2470LM 5000K 80CRI NON-DIM E26 UNIV BURN POS 100-277V
LED22T8F/48/840-G6DR	DISC GLASS DIRECT FIT DLC V3.1 T8 4FT 17W-2200LM 4000K DIMMABLE/EMERGENCY 80CRI 120-277V,347V
LED22T8F/48/850-G6DR	5000K GLASS DIRECT FIT DLC V3.1 T8 4FT 17W-2200LM 5000K DIMMABLE/EMERGENCY 80CRI 120-277V,347V
LED32T5HO/46/840-G6DR	GLASS 25W-3200lm Ballast Compatible replaces 54WT5HO, G5 bi-pin 80+CRI 4000K Frost
LED32T5HO/46/850-G6DR	GLASS 25W-3200lm Ballast Compatible replaces 54WT5HO, G5 bi-pin 80+CRI 5000K Frost
LED54WPT40KMED-G7	LED HID REPLACEMENT 54W-7020LM 4000K 80CRI NON-DIM E26 UNIV BURN POS 100-277V
LED54WPT40KMOG-G7	LED HID REPLACEMENT 54W-7020LM 4000K 80CRI NON-DIM EX39 UNIV BURN POS 100-277V
LED54WPT50KMED-G7	LED HID REPLACEMENT 54W-7290LM 5000K 80CRI NON-DIM E26 UNIV BURN POS 100-277V
LED54WPT50KMOG-G7	LED HID REPLACEMENT 54W-7290LM 5000K 80CRI NON-DIM EX39 UNIV BURN POS 100-277V
LED6WG25/FIL/827K-DIM-G6	LED Advantage Filament G25 320 Deg, 5.5W-400lm, Dimmable, 80CRI, 2700K, E26, 120VAC
LED7WBR20/827K-DIM-G5	LED LiteSpan BR20 Reflector Flood, 7W - 550lm, Dimmable, 2700K, 80+CRI, 120VAC,
LED7WMR16/20/830-G5	3000K LED GEN5 MR16 GU5.3, 20 deg beam, 7W - 400lm, Non-Dimmable, 2BD, 80+CRI, 12V
LED7WMR16/40/830-G5	3000K LED GEN5 MR16 GU5.3, 40 deg beam, 7W - 400lm, Non-Dimmable, 2BD, 80+CRI, 12V
LED9W2PV/835DR-G6	LED Magnetic ballast compatible 2pin CFL 9W-900lm Vert G24d Base 80CRI 35K 120-277V
LED9W4PH/840DR-G6	LED Electronic ballast compatible 4pin CFL 9W-900lm Horiz G24q Base 80CRI 40K 120-277V
LED9W4PV/840DR-G6	LED Electronic ballast compatible 4pin CFL 9W-900lm Vert G24q Base 80CRI 40K 120-277V
LED9WA19/OMN/830K-DIM-G7 2PK	LED Litespan A19 Omni-directional 9W-800lm Dim 80CRI 3000K E26 120VAC 2 Pack
LLH-2C-U	LED Linear Highbay 110W, 13750LM, 0-10V Dimming, 5000K, 120-277V
LLH-3C-U	LED Linear Highbay 155W, 19280LM, 0-10V Dimming, 5000K, 120-277V
LLH-4C-U	LED Linear Highbay 220W, 26730LM, 0-10V Dimming, 5000K, 120-277V
LLW-5C-40K-U	LED Linear Wrap 4 ft. 42W-5334LM, 0-10V Dimmable, 4000K 120-277V
SCRS-3C-U	Surface Canopy Round, Shallow 57W-5824LM 5000K +70CRI Bronze 120-277V
SLM22-3C-40K-U	EDGE-LIT SLIM PANEL 2X2 DLC V4.0 STANDARD 30W-3000LM 0-10V DIMMABLE 80CRI 4000K 100-277V
SLM24-5C-40K-U	EDGE-LIT SLIM PANEL 2X4 DLC V4.0 STANDARD 40W-4000LM 0-10V DIMMABLE 80CRI 4000K 100-277V
VOL22-3C-40K-U	Volumetric Troffer 2x2 DLC V4.0 Premium 26W-3275LM 0-10V Dimmable 80CRI 4000K
VOL24-5C-40K-U	Volumetric Troffer 2x4 DLC V4.0 Premium 48W-5970LM 0-10V Dimmable 80CRI 4000K

Full spec sheets can be found at www.eiko.com.