

Model		RX 5032-HD	
System	Main Processor	Hisilicon Hi3531	
	System Resource	Sixfold operation: Live recording, Playback, Backup, Remote access, PTZ control, Mobile monitoring	
	Control Mode	Front panel, USB mouse, IR remote control, Keyboard, Network	
Video	Input	32×BNC,(1.0Vp-p,75Ω)	
	Standard	32 CIF NTSC 960FPS ;PAL 800FPS	
	Output	1×BNC,(1.0Vp-p,75Ω),1×VGA,1× HDMI	
Audio	Input	8×RCA	
	Output	1×RCA	
Display	Display Split	1/4/8/9/16/24	
	Resolution	BNCx1, VGA+HDMI: 1024*768, 1280*1024, 1280*720@60P, 1920*1080@60P	
	Tour Display	Support	
Recording	OSD	Camera title, Time, Video loss, Motion detection, Recording	
	Video/Audio	H.264/ADPCM	
	Image Resolution	D1(720*576/720*480), HD1(720*288/720*240), CIF(352*288/352*240)	
	Performance	24CH CIF real time	
	Encoding stream	Main stream	CIF:600fps@PAL, 720fps@NTSC
		Extra	CIF:5FPS/CH
	Recording Mode	Manual, schedule,Motion detection,Alarm	
Recording Priority	Manual>Alarm>Motion detection		
Video detection	Trigger events	Recording, PTZ movement, Alarm, E-mail	
	Motion detection	Zones:396 (22*18) ,Sensitivity:1-5 (Level 5 is the highest)	
	Video loss	Support	
	Alarm	8 IN / 1 OUT	
Playback & Backup	Playback channel	24CH CIF	
	Playback speed	CIF: 600fps@PAL, 720fps@NTSC	
	Search mode	Time/date, Motion detection	
	Playback function	Play, Pause, Stop, Fast forward, Slow forward, Full screen etc. Recording files can be viewed by dragging the progress bar back and forth	

	Backup mode	U-disk /USB-HDD /Network
Network	Physical interface	RJ-45port(10/100M)
	Network function	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS,DNS Binding
	Remote operation	Monitor, PTZ control, Playback, System setting, files download, Log information
	Mobile Phone	Support Window Mobile, Symbian, Android, iPhone, Blackberry etc.
Hard Disk	Hard disk	4 SATA port, the capacity of single hard disk MAX 3T
	Space occupation	Audio: 14.4MB/H, Video: 56-900MB/H
	HDD management	Hard disk hibernation technology, HDD faulty alarm, file restoration
Auxiliary Interface	USB	Two USB2.0 interface, for connecting mouse, U-disk, USB hard disk
	RS485	PTZ control
Environment	Power supply	12V/6A
	Working environment	-10°C~+55°C10~90%RH/86~106Kpa
	Dimension	440*380*70mm(Product size)
	Weight	Package Weight:7.2Kg