

## Gasoline Engine Oils



Product Name & Description		Specifications	Approvals	FUCHS Recommendations
<b>TITAN Supersyn LONGLIFE SAE 0W-40</b>	Ultra High Performance, fully synthetic, fuel-economy oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	API SN ACEA A3/B4	MB-APPROVAL 229.5 PORSCHE A40 VW 502 00/505 00	AMG ASTON-MARTIN BMW LONGLIFE-01 FORD M2C937-A
<b>TITAN SYN SN SAE 5W-30</b>	Ultra High Performance, extreme fuel-economy oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	API SN ILSAC GF-5		
<b>TITAN Supersyn SAE 5W-40</b>	Ultra High Performance, fuel-economy oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/CF	MB-APPROVAL 229.3 PORSCHE A40 VW 502 00/505 00 PSA B71 2296 RENAULT RN0700/RN0710	FIAT 9.55535-H2 / M2 / N2 / Z2 BMW LONGLIFE-98
<b>TITAN SYN MC SAE 10W-40</b>	Super High Performance, fuel-economy oil for a variety of gasoline and diesel engines in passenger cars. Good cold starting and lower oil consumption.	ACEA A3/B4 API SL/CF	MB-APPROVAL 229.1	BMW SPECIAL FIAT 9.55535-D2/G2 VW 500 00/505 00
<b>TITAN SUPERSYN D1 SAE 5W-30</b>	Ultra High Performance, extreme fuel economy engine oil, specially developed for GM vehicles requiring dexos1™-fluid. Optimum cold starting, lower oil consumption and minimized exhaust emissions. Also recommended for gasoline engines requiring API SN/GF-5, SAE 5W-30.	API SN ILSAC GF-5	dexos1™ (GM License No. RB1C0907088)	Supersedes GM-LL-A-025 Supersedes GM6094M Supersedes GM4718M
<b>TITAN SUPER GT SAE 10W-30, 10W-40, 20W-50</b>	Premium quality, high performance, multigrade oil for Gasoline Engines with and without Turbo charging. It meets the service requirements of the API Engine Service Classification SL. SAE 20W-50 and 10W-30 bear API donut and are also certified by Saudi Arabian Standard Organization (SASO) and bears a SASO quality seal.	API SL		

## Diesel Engine Oils



Product Name & Description	Specifications	Approvals	FUCHS Recommendations	
<b>TITAN CARGO SAE 14W-40</b>	Ultra high-performance, fuel-economy oil for a variety of commercial vehicle diesel engines. Specially developed for Volvo with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9/E7 API CJ-4/CI-4 PLUS/CI-4 CAT ECF-2/ECF-3	CUMMINS CES 20081 DEUTZ DQC III-10 LA DETROIT DIESEL 93K218 FAWDE Q/XC 3135-2007 MACK EO-O PREMIUM PLUS MAN M 3575/3275-1 MB 228.31 MTU DDC TYPE 2.1 RENAULT RLD-3 VOLVO VDS-4	ALLISON C-4
<b>TITAN CARGO MC SAE 10W-40</b>	Ultra High Performance, fuel-economy oil for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7/E4 API CI-4	CUMMINS CES 20077/8 DEUTZ DQC III-10 MAN M 3277 MB 228.5 MB 235.27 MTU DDC TYPE-3 RENAULT RXD/RLD-2 MACK EO-M PLUS MACK EO-N VOLVO VDS-3 SCANIA LDF-2 VOITH-RETARDER "A"	DAF IVECO 18-1804 SDFG OM-1901A
<b>TITAN UNIMAX PLUS MC SAE 10W-40</b>	Ultra High Performance, MC-synthesis, fuel economy oil for all commercial vehicles, off-highway equipment and passenger cars. Substantial rationalization opportunities for mixed fleets. Prolongation of drain intervals possible with some manufacturers.	ACEA E7/B3/A3 API CH-4	DEUTZ DQC II-10 MAN M 3275-1 MB 228.3/229.1 MB 235.27 MTU DDC TYPE-2 VOITH-RETARDER "A" RENAULT RD / RD-2 VOLVO VDS-2 CUMMINS CES 20077	ALLISON C-4 DAF MACK EO-M PLUS SCANIA CUMMINS 20071/2/6
<b>TITAN TRUCK PLUS SAE 14W-40</b>	Super High Performance oil for a variety of diesel and gasoline engines. Specially for highly loaded commercial vehicle diesel engines. Lower oil consumption.	ACEA E7 API CI-4/SL GLOBAL DHD-1 CAT ECF-1-a/ECF-2	CUMMINS CES 20076/7/8 DEUTZ DQC III-10 MAN M 3275-1 MB 228.3 MTU DDC TYPE-2 RENAULT RLD / RLD-2 VOLVO VDS-3 MACK EO-N	ACEA A3/B4 ALLISON C-4 CAT TO-2 CASE MS 1121 IVECO 18-1804 CLASSE T2 E7 DAF CUMMINS CES 20071/2 STEYR A-201 NH 330 H
<b>TITAN UNIVERSAL HD SAE 14W-40</b>	High Performance multi-grade oil for mixed fleets operated under normal conditions. Good performance in normally aspirated and turbocharged diesel engines.	API CG-4/CF/SL ACEA A3/B3/B4	MB 228.1/229.1 DEUTZ DQC I-02 MAN 271 MTU DDC Type-2	MIL-L-2104 E ACEA E2 ALLISON C-4 CASE MS 1120 DAF NH 330 G SCANIA STEYR A-202 VOLVO VDS VW 501 01/505 00 MAC EO-L

## Diesel Engine Oils



Product Name & Description		Specifications	Approvals	FUCHS Recommendations
<b>TITAN CFE</b> SAE 14W-40	All season engine oil containing a carefully selected base oil and additive combination with solid lubricants.	API CG-4/SJ		
<b>TITAN UNIVERSAL HD</b> SAE 10W, 20W-20, 30, 40, 50	High-performance mono-grade oils for diesel engines. Specially developed for offroad vehicles.	ACEA E2 API CF	DEUTZ DQC I-02 (30, 40 & 50) MAN 270 (10W, 20W-20, 30 & 40) MAN M 3275-2 (50) MB 235.12 (40) MB 235.27 (20W20) MB 228.0 (10W, 20W-20 & 50) MB-228.2 (30 & 40) MTU DDC TYP-2 (30 & 40) ZF TE-ML 04B (30 & 40) ZF TE-ML 03B (10W) VOITH-RETARDER "A" (20W-20)	MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C API CF-2 (SAE 40 Only)
<b>TITAN POWER 100</b> SAE 10W, 10W-30, 15W-40, 20W-20, 20W-50, 25W-50, 30, 40, 50	High quality diesel engine oil for naturally aspirated and Turbo Charger engines.	API CF		
<b>TITAN POWER 200</b> SAE 30, 40, 50	High quality engine oil designed specifically for naturally aspirated and some turbocharged engines using fuel with high sulphur content.	API CF		
<b>TITAN TRAIN</b> SAE 40, 50	High quality zinc free oil for medium speed high output locomotive diesel engines.	API CF/CF-2		EMD (Electro-Motive Division of GM) Caterpillar 3600 GE Generation 4 LMOA Generation 5