<b>GEN-1630</b> (120V-3000W-19.2kW-60Hz-16yr-SW)	Geneforce Emergency Power System
Product Features	
Silent operation. Safe for indoors. No gas or emissions.	
No Installation; No Maintenance; No Permits required	The second second
Arrives fully charged and ready to work.	
Automatic & one-touch start.	
System Control Panel with Graphical 128 x 64-pixel, backlit	
LCD displays power reserves, amp hours consumed, fault	f
conditions, solar panel output, charging, power	
consumption.  Overheat Temperature Sensor & Automatic Shutdown	
feature.	
Built-in voltage regulation system for sensitive electronics.	
Built-in 30A solar charge controller for solar panel	
charging.	
Electrical Specifications	GEN- <mark>1630</mark> (120 Volt)
Output power (continuous)	3,000 Watts
Surge power (AC amps)	6,000 W atts
Peak output current	80 Amps
Output frequency regulation	60 Hz +/- 0.2 Hz
Voltage regulation	120 V +/-5% true RMS
Output wave form	True Sine Wave
Service Life	12-16 years
Stored battery reserves	19.2 kW (19,200 Watts)
AC input 1	One (30A/125V) NEMA L5-30P input plug with 8 ft. cord
AC output 1	Four (20A/125V) NEMA 5-20R isolated ground receptacles
AC output 2	One (30A/125V) NEMA L5-30R female receptacle
Automatic transfer switch	30A (Transfer time < 20 ms.)
Charge rate	150 A DC
AC input voltage range	85 - 140 Vac
Charge control	3-stage (Bulk, Acceptance, Float)
Solar charge controller	30A/12V (~360 W per hour/sunlight) *(60A/12V-24V) optional
General Specifications	
Optimal operating temperature range	- 4°F to 140°F (- 20°C to 60°C)
Monitor	LED Display (reads V, DC amps, Power Share, etc.)
Product Dimensions (H x D x W) and weight	(36" x 24" x 36") & (1482 Lbs.) 673 kg.
Shipping Dimensions (H x W x L) and weight	Custom Pallet 48" x 36" x 48" (1682 lbs.) 765 kg.
Construction	Strong Steel, Four Casters, Color-Black or Charcoal
Warranty	24-month warranty on components; up to 4-years on batteries
Part Number	GEN-1630-120-3000-16-SW
Regulatory Approvals & Protection	
Safety - UL Listing	Components ETL certified to CSA 107.1, UL458 with marine
	supplement, FCC Part 15, Class B
Voltage Regulation	Over voltage and under voltage protection
Temperature & output	Over-temperature & overload protection
Electrical	Short circuit protection
Price	\$12,797
Geneforce Incorporated www.geneforcepower.com	Tel: (786) 823-0700 email: info@geneforcepower.com