

BPM FARM CLASS RULES

1. 2WD only
2. No steel wheels or tire chains
3. Rubber tires only-No cut tires-Radials allowed
4. (5 and 8 MPH) 6500-9500 lb classes are 18.4x38 tire size max, 10,500 lb+ are any tire size
5. (12.5 MPH) – Any tire size
6. Stock appearing blocks with stock appearing pump in stock location with sheet metal matching the rear end of that tractor
7. Hitch is 20" (6500-9500lb) and 22" (10,500lb & up) high max and no shorter than 18" from center of rear axle. Hitch hole should be 3x3 ¼" Hitch to be stationary in all directions.
8. 13ft rule for front weights. (measured from center of rear axle) Rear weights to be mounted so the hitch is easily accessible.
9. Any tractor part falling off while hooked to the sled will result in DQ – all weights must be secure.
10. No down draft carburetors. Single bbl carburetors only.
11. Fuel limited to gas, LP, or diesel only. (Subject to random check) No extra injected fuels.(re: LP added to Diesel-No NOS etc.) Blue fuel-av gas etc - ok
12. Skid bars highly recommended for all tractors.
13. Any tractor running over 3000 rpm's must have a scatter blanket or a 3/8" steel shield covering the bell housing by 360 degrees. 4000 rpm max.
14. No excessive stripping – 3 point arm removal okay. Judges decision is final.
15. No homemade front axles.
16. All tractors to be operated in a safe manner on and off the track.
17. Exhaust pipes to be straight- No curved pipes