



**SHEET METAL PRODUCTS**  
**COMMERCIAL GRADE**  
**FLSOC FLANGE & GASKET**

**FLANGE & GASKET COLLAR - MODEL FLSOD, FLSOC-D1 & FLSOCD3**

Expedite field installations with Peppertree Model FLSOC quality Flange and Gasket Fittings (with or without damper). These fittings are available in 5" or 7" body lengths. All FLSOC's are fabricated with a seamless 1" Mounting Flange and a bead for non-slip positioning of draw bands or gear clamps. Our damper blades are fabricated with quality hardware including stamped handles, spring loaded & solid bearings and locking adjustable wing nuts. We can also provide heavy duty handles and stand-off regulators with full locking quadrants for insulated ductwork.



FLSOCD	FLSOCD1	FLSOCD3
<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• Damper &amp; hardware</li> <li>• 5" overall body length</li> <li>• Beaded sleeve</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>	<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• 2" Extended Handle</li> <li>• 5" overall body length</li> <li>• Beaded sleeve</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>	<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• 2" stand-off</li> <li>• Locking quadrant</li> <li>• 3/8" square rod</li> <li>• Nylon bushings</li> <li>• 7" overall body length</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>

These products simplify installation and enhance design efficiencies. Submittal data is available on our website. We also offer a variety of fittings including Spin-on Collars and Connecting collars. These fittings are available with or without dampers.