

6D



POLYESTER DOUBLE JACKET HOSE

Our 6D hose is designed almost identically to our type 8D hose but for lower operating pressures at 300 PSI (2070 kPa) maximum. When the pressures are lower and the economics demand consideration, this double jacketed, rubber lined hose can't be beat. As an added benefit, most sizes of type 6D are UL listed, some are ULC (UL Canada) listed or FM approved and can be labeled if required.



ATTACK




SUPPLY



USA MADE

FEATURES AND BENEFITS

- Exceptional quality, double jacket, rubber lined municipal fire hose made from 100% high tensile strength polyester yarn with a lining of extruded EPDM.
- Optional Dura-Cote treatment greatly increases abrasion, heat, flame and petrochemical resistance while virtually eliminating water pick-up. When treated, 6D is protected from mildew and no drying time is required.
- Remains flexible to temperatures as low as -40°F (-40°C) and is resistant to ozone and oxidation.
- Manufactured in accordance with NFPA 1961 standard, latest edition within our ISO-9001:2015 certified quality assurance system.



CONSTRUCTION

Polyester Double Jacket
EPDM
Rubber Inner Liner


TEMPERATURE

-40°F to 150°F (-40°C to 65°C)

COUPLINGS

Aluminum or brass NH/NST or IPT Threaded

COLORS



WOVEN DOUBLE JACKET

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (50' Coupled)	BOWL SIZE	CERTIFICATION AVAILABLE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	
1"	300 (2070)	600 (4140)	900 (6200)	12 (5.4)	1 1/2"	
1 1/2"	300 (2070)	600 (4140)	900 (6200)	14 (6.4)	1 5/16"	UL, ULC, FM
1 3/4"	300 (2070)	600 (4140)	900 (6200)	16 (7.3)	2 3/16"	UL
2 1/2"	300 (2070)	600 (4140)	900 (6200)	25 (11.3)	3"	UL, ULC, FM
3"	300 (2070)	600 (4140)	900 (6200)	37 (16.8)	3 1/2"	UL
4"	300 (2070)	600 (4140)	900 (6200)	70 (31.8)	4 1/2"	
5"	200 (1379)	400 (2760)	600 (4140)	85 (38.6)	5 3/4"	
6"	200 (1380)	400 (2760)	600 (4140)	100 (45.4)	6 3/4"	

TYPE	HOSE I.D.	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL	OPTIONS
6D	10 = 1" 15 = 1 1/2" 17 = 1 3/4" 25 = 2 1/2" 30 = 3" 40 = 4" 50 = 5" 60 = 6"	50 = 50' 100 = 100'	Y = Yellow R = Red W = White *uncoated	10 = 1" 15 = 1 1/2" 25 = 2 1/2" 30 = 3" 40 = 4" 50 = 5" 60 = 6"	N = NH I = IPT	Blank = Aluminum BR = Brass Rocker Lug (1 1/2" and 2 1/2" only) BP = Brass Pin Lug	UL = UL Listed ULC = UL Canada Listed FM = Factory Mutual

