

5-7/8" OD, HWDP, INTEGRAL, STANDARD, 7.000" OD x 4.000" ID, XT57

## HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	5-7/8
Nominal ID (in)	4.000
Pipe Grade	AISI 4145
Heavy Weight Type	STANDARD
HWConstruction	INTEGRAL
Pipe Wall Thickness (in)	0.938
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	14.542
Cross Sectional Area OD (in <sup>2</sup> )	27.109
Cross Sectional Area ID (in <sup>2</sup> )	12.566
Section Modulus (in <sup>3</sup> )	15.630
Polar Section Modulus (in <sup>3</sup> )	31.260
Torsional Strength (lbs/ft)	180,380
Tensile Strength (lbs)	1,745,100
Burst Pressure (psi)	33,510
Collapse Pressure (psi)	32,190

## HEAVY WEIGHT DRILL PIPE CONNECTION

OD (in)	7.000
ID (in)	4.000
Connection	XT57
Torsional Strength (lbs/ft)	106,200
Tensile Yield Strength (lbs)	1,394,900
Tool Joint/Drill Pipe Torsional Ratio (New)	0.59

## HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.84
Closed End Displacement (gal/ft)	1.49
Fluid Capacity (gal/ft)	0.65
Drift Size (in)	3.875
Adjusted Weight (lbs/ft)	55.10
Hardbanding	ARNCO 300 XT

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.