

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Whisper

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Limestone	Number of Faces/Screens:	
Thickness in mm:	9mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	2 colors 40% Pre; 2 colors 0%	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.65
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:		Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.57	Pieces per Carton:	7
SqFt per Pallet:	542.80	Pounds per Carton:	51.70
Boxes per Pallet:	40	SqFt per Container:	11941.60
Pallets per Container:	22		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".