



RPT-260IV ECO Thermal Printer

FEATURES

- ✚ Command protocol is based on ESC/POS standard
- ✚ Low-noise thermal printing
- ✚ Various Layouts are by using page mode.
- ✚ Repeated operation and copy printing are possible
- ✚ Character font size optional
- ✚ Easy paper-roll installation
- ✚ Easy paper jam clearance
- ✚ Easy maintenance for tasks such as head cleaning
- ✚ Built-in interface provides control capability for Cash Drawer

TECHNICAL SPECIFICATIONS:

- | | |
|----------------------------|---|
| ✚ PRINTING METHOD | : Direct Thermal |
| ✚ PRINTING SPEED | : 260 mm/sec |
| ✚ DOT DENSITY (DPI) | : 203*180, 180*180 |
| ✚ EFFECTIVE PRINTING WIDTH | : 79.5mm, 576 Dots, 79.5mm, 512 Dots |
| ✚ PRINTING DIRECTION | : Unidirectional with friction feed |
| ✚ CHARACTER/LINE | : Font A (12*24): 48/ 42 columns
Font B (9*17): 64/ 56 columns |
| ✚ PAPER TYPE | : Thermal paper |
| ✚ PAPERWIDTH | : 80mm ± 0.1mm |
| ✚ PAPER THICKNESS | : 0.06 ~ 0.09mm |
| ✚ PAPER ROLL DIAMETER | : Max. 80 mm |

RELIABILITY:

⚡ TPH LIFE	: 100Km
⚡ MCBF	: 10,000,000Lines
⚡ Barcode	: EAN-8, EAN-13, CODE 39, CODE 93, CODE 128, ITF , UPC-A, UPC-E, CODABAR, PDF 417
⚡ EMULATION	: ESC/POS, EPSON EMULATION
⚡ SENSOR	: Paper end sensor
⚡ INTERFACE	: Serial USB Ethernet or Parallel USB
⚡ Cash Drawer Port	: RJ 11(DC 12 - 24 V/1 A)
⚡ AUTO CUTTER LIFE	: 1,500,000 cuts
⚡ PAPER THICKNESS	: 0.06 ~ 0.09mm
⚡ CUTTING METHOD	: Full/Partial Cut
⚡ WEIGHT	: INCLUDE AUTO CUTTER 1.6 Kg

POWER:

⚡ AC Adapter input	: AC220V, 50Hz
⚡ AC Adapter output	: DC 24V/2.5A
⚡ Printer input voltage	: DC 24V/2.5A
⚡ Operating temperature	: 0~45°C Relative
⚡ Storage Temperature	: 10°C ~ 50°C
⚡ Humidity	: Operating Humidity 10 ~ 80 % Storage Humidity 10 ~ 90 %



Phone: 9004566257 / 7738647344
Email: sales@realpostechonology.in