

Sustainable Coils

Replacement Coil Solutions!

NORDYNE replacement coils for ReplCoil 1-7, B3BM, GB3BM, B4VMX, B5BM, GB5BM Air Handlers:

7/17/17

Some of our Nordyne replacement coils are a non-stock item and may require up to 7 business days to manufacture. Please contact the factory for current lead time.

Please note: Due to the multiple use of the coil model numbers in various tonnages and air handlers, it may be necessary to field install a supplied TXV kit or change a piston for a proper refrigerant match to the outdoor unit. Replacement coils may be ordered with the correct piston or TXV factory installed with a minimal up-charge to fit the desired application.

NORDYNE CROSS REFERENCE UTILIZATION CHART

OEM Model #	Sustainable Model #	Specified Metering
ReplCoil01	RC3BA-36U-A	.073 PISTON
ReplCoil02	RC3BA-36U-B	.073 PISTON
ReplCoil03	RC5BA-37U-B	.080 PISTON
ReplCoil04	RC3BA-60U-C	.093 PISTON
ReplCoil05	RC5BA-60U-C	.097 PISTON
ReplCoil06	RC3BA-24U-A	.059 PISTON
ReplCoil07	RC3BA-48U-C	.093 PISTON

OEM Model #	Sustainable Model #	Specified Metering
B3BM-024K-A	RC3BA-36U-A	R-22 PISTON
B3BM-030K-A	RC3BA-36U-A	R-22 PISTON
B3BM-030K-B	RC3BA-36U-B	R-22 PISTON
B3BM-036K-B	RC3BA-36U-B	R-22 PISTON
B3BM-042K-B	RC3BA-48U-B	R-22 PISTON
B3BM-048K-B	RC3BA-48U-B	R-22 PISTON
B3BM-060K-C	RC3BA-48U-C	R-22 PISTON

OEM Model #	Sustainable Model #	Specified Metering
GB3BM-024K-A	RC3BA-36U-A	R-22 PISTON
GB3BM-030K-A	RC3BA-36U-A	R-22 PISTON
GB3BM-030K-B	RC3BA-36U-B	R-22 PISTON
GB3BM-036K-B	RC3BA-36U-B	R-22 PISTON
GB3BM-042K-B	RC3BA-48U-B	R-22 PISTON
GB3BM-048K-B	RC3BA-48U-B	R-22 PISTON
GB3BM-060K-C	RC3BA-48U-C	R-22 PISTON

NORDYNE Air Handler replacement coils:

7/17/17

Page 2

OEM Model #	Sustainable Model #	Specified Metering
B4VM-X24K-A	RC3BA-36U-A+4X3	R-410A HP-TXV
B4VM-X24K-B	RC3BA-36U-B+4X3	R-410A HP-TXV
B4VM-X24K-B After 2008	RC3BA-60U-C+4X3	R-410A HP-TXV
B4VM-X30K-A	RC3BA-36U-A+4X3	R-410A HP-TXV
B4MV-X30K-B	RC3BA-36U-B+4X3	R-410A HP-TXV
B4MV-X36K-B	RC5BA-37U-B+4X3	R-410A HP-TXV
B4MV-X48K-B	RC5BA-37U-B+4X5	R-410A HP-TXV
B4VM-X48K-C	RC5BA-60U-C+4X5	R-410A HP-TXV
B4VM-X60K-C	RC5BA-60U-C+4X5	R-410A HP-TXV

OEM Model #	Sustainable Model #	Specified Metering
B5BM-024K-A	RC3BA-36U-A	R-22 PISTON
B5BM-024K-B	RC3BA-36U-B	R-22 PISTON
B5BM-025K-A	RC3BA-36U-A	R-22 PISTON
B5BM-025K-B	RC3BA-36U-B	R-22 PISTON
B5BM-030K-A	RC3BA-36U-A	R-22 PISTON
B5BM-030K-B	RC3BA-36U-B	R-22 PISTON
B5BM-036K-A	RC3BA-36U-A	R-22 PISTON
B5BM-036K-B	RC3BA-36U-B	R-22 PISTON
B5BM-037K-B	RC5BA-37U-B	R-22 PISTON
B5BM-042K-B	RC5BA-37U-B	R-22 PISTON
B5BM-048K-B	RC5BA-37U-B	R-22 PISTON
B5BM-048K-C	RC3BA-60U-C	R-22 PISTON
B5BM-049K-C	RC5BA-60U-C	R-22 PISTON
B5BM-060K-C	RC5BA-60U-C	R-22 PISTON

OEM Model #	Sustainable Model #	Specified Metering
GB5BM-024K-A	RC3BA-36U-A	R-22 OR R410A
GB5BM-024K-B	RC3BA-36U-B	R-22 OR R410A
GB5BM-030K-A	RC3BA-36U-A	R-22 OR R410A
GB5BM-030K-B	RC3BA-36U-B	R-22 OR R410A
GB5BM-036K-B	RC3BA-36U-B	R-22 OR R410A
GB5BM-042K-B	RC5BA-37U-B	R-22 OR R410A
GB5BM-048K-C	RC3BA-60U-C	R-22 OR R410A
GB5BM-060K-C	RC5BA-60U-C	R-22 OR R410A

3/8 O.D. UNIGUARD® by Luvata copper alloy tubing to block formicary corrosion.

Aluminum end plates for rust reduction.

Enhanced louvered fins spaced at 14 FPI.

Piston models metered for R-22, R-410A available upon request.

Factory installed heat pump expansion valves available upon request.

Expansion valve kits with chatleff fittings available upon request.

Suction and liquid lines positioned to access panel locations.

Pre-swaged suction and liquid lines, shipped with dry nitrogen holding charge.

Coils utilize a coated G-90 paint grip metal drain pan.

Drains positioned to match access panel.

Proper internal refrigerant volumes maintained for heat pump compatibility.

Coils carry a 5 year replacement warranty from date of installation.

Proudly manufactured and assembled in Lindale, Texas.