

Stock Gas and Stock Diesel 4X4 Trucks

All trucks competing in this class must:

- Be stock appearing and the floor in bed must be solid.
 - Be powered by the OEM diesel or gas engine for the make and model year of the truck.
 - Must have current license, registration, inspection, and insurance card.
 - Must have factory manufactured wheel base.
 - Must be available for under hood inspections.
 - May not exceed Diesel 10,000 lbs. / Gas 7,500 lbs. with driver.
-
- Diesel fuel only in diesel trucks. (No water injection, alcohol, propane or nitrous. (Nitrous bottle must be removed, if so equipped)
 - Pump gas only for gas trucks. (No alcohol or racing fuels allowed.)
 - No studded, cut, or grooved tires or any other tires not intended for street use. No tire chains. Tires must have stamped D.O.T. number on sidewall.
 - All added weight must be placed inside of truck bed and secured to prevent weight from sliding around in truck bed. No weight brackets, boxes and hanging weights. NO weights allowed in cab.
 - Original front and rear axles must be used; raising or lowering of truck height with suspension modifications is permitted.
 - A fully functional front and rear suspension is required. No blocking suspension, traction stabilizer bars, spring-clamps, or locking of springs is allowed.
 - Front and rear bumpers must remain unaltered and in the factory position. No home manufactured bumpers allowed. Snowplow frames and brush guards are allowed. Tailgate or cargo net must be in place.
 - The hitch point must be from OEM factory style receiver hitch, mounted in the factory designed position. Maximum hitch point allowance is 26" from top of hitch to level ground. Hitch must be rigid in all directions, NO trick hitches allowed. Pulling ring must

have a 3" to 3 ½" opening. No vertical hitch or opening. Hitch hook point must be the furthest point to the back of the truck. (or the first thing to hit if you backed into a wall!!)

- Receiver hitch MUST be in place on truck at scale weigh-in.
- Clutch transmission, drive shafts and all drive line must be OEM for make/model of truck.
- Any computer programmer or chip is permitted. Air cleaner and components required.
- Use of seat belt during pulling is required. Fire extinguisher is highly recommended.
- Drivers must be a licensed driver 16 years old or older.