

## High Speed Dome Laser IR Camera

### Business Terms:

Warranty: 1 year

Packing: 2pcs/Carton,


Carton: 65\*34\*47cm

G.Weight:11kg/pc

### Details:

- Laser IR for 200meter IR vision,
- LED adjustable according to IR distance.
- Pan Range 360° continuous, Tilt range: 180°, Pan speed: 0.5°-280°/S, Tilt speed: 0.5°-210°/S.
- 150-200meters IR view distance

- 8 cruising track, each track has 16 preset positions.
- Shift rate: multilevel shift.
- English OSD Function.
- Auto replacement optional.
- RS-485 data communication.
- Integrative Camera: Original SONY module,.
- Lightning proof rate: 3 grade
- Working temperature: -40°C+60°C Humidity<90%RH
- Materials: High Die-cast aluminum alloy construction.

Model	AS-JG88IRH	
Image Sensor Device	1/4" EX View SONY HAD CCD 530TVL	
Effective Pixel	About 440,000	
Resolution	PAL/NTSC: 752 x 582 pixels	
Lens	F=3.4 mm-122.4mm,F1.4 to F4.5	
Zoom	36x optical zoom & 12x digital zoom	
IR distance	150-200M	
Pan turn speed	360°continuous rotation, speed:0.5°-280°/S	
Tilt turn speed	90°, speed: 0°-210°/S.	
Preset	128, speed and settle time could optional	
Preset positions each group	16	
Pattern Tours	1 group programmable Pattern Tours, Each linkage	
A-B Scan	YES	
A-B Scan speed	1-64 grade available	
Multi-Scan	Speed, Idle time programmable	
Two points-Scan	Speed, Idle time programmable	
Pattern-Scan	90 Secs track memory	
Cruise	8 groups Multi-Scan cruise	
Heater & Fan	YES	
Baud rate	1200,2400,4800,9600 selectable	
Power supply	DC12V	
Condition	Outdoor	
Install bracket	Ceil/Wall	
G. Weight	11kg	

**Surveillance Camera**

CCTV