

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

DI CAVA

TECHNICAL CHARACTERISTICS

Available Formats:	16x32, 16x14 Hexagon, 3x32 Bullnose		
Style Description:	Vien Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Carrara/Calacatta/Bardiglio	Number of Faces/Screens:	16x32: 14; Hex: 28
Thickness in mm:	10	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	32%	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.70
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	> 35N/mm
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Conforms		

PACKING INFORMATION - 16x32 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.33	Pieces per Carton:	3
SqFt per Pallet:	619.80	Pounds per SqFt:	4.89 lbs
Boxes per Pallet:	60	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".