

# HYDRAULICS INDEX

---

## **ADAPTERS (STEEL)**

|                              |          |
|------------------------------|----------|
| 37° Flare.....               | 769-778  |
| 37° Flare (with O-Ring)..... | 775-776A |
| Female Pipe Swivel.....      | 782-784  |
| Ferulok.....                 | 787      |
| Metric Adapters.....         | 777-778  |
| Pipe.....                    | 779-784  |
| Seal Lok.....                | 785-786  |
| Stainless Steel.....         | 774A     |

## **FITTINGS**

|                                   |           |
|-----------------------------------|-----------|
| 20 Series.....                    | 749-754   |
| 22 Series.....                    | 757       |
| 26 Series (Air Conditioning)..... | 748K-748N |
| 30 Series.....                    | 760-761   |
| 43 Series.....                    | 740-745A  |
| 43 Series Stainless.....          | 745A      |
| 55 Series.....                    | 746-747A  |
| 71 Series.....                    | 748-748C  |
| 78 Series.....                    | 748E-748J |
| Caterpillar Style.....            | 748H-748J |
| 88 Series.....                    | 764       |
| 90 Series.....                    | 767       |
| 91 Series.....                    | 768-768A  |
| 91 Series.Stainless.....          | 718       |
| Ferulok.....                      | 787       |

## **HOSES**

### **LOW PRESSURE**

|                                   |     |
|-----------------------------------|-----|
| 285 "Air Conditioning".....       | 737 |
| 881/811 "Suction & Return Lines.. | 720 |

### **MEDIUM PRESSURE**

|                            |     |
|----------------------------|-----|
| 201 "Hi-Temperature".....  | 726 |
| 426 "Hi-Temperature.....   | 724 |
| 518C "Non-Conductive"..... | 734 |
| 919 "TFE Stainless".....   | 736 |

### **HIGH PRESSURE**

|                               |      |
|-------------------------------|------|
| SS25UL "LPG".....             | 728  |
| 302 High Pressure.....        | 730  |
| 351TC Abrasion Resistant..... | 731  |
| 451TC Tough Cover.....        | 732  |
| 471TC High Pressure.....      | 733  |
| 772TC High Pressure.....      | 733B |
| 78C High Pressure.....        | 733C |
| Pressure Washer.....          | 798  |

## **MISCELLANEOUS**

|                                |         |
|--------------------------------|---------|
| Armor Guards.....              | 795     |
| Caplugs.....                   | 796-797 |
| Flaretite Seals.....           | 768B    |
| Hose Fitting Thread Guide..... | 719     |
| Partek Sleeve.....             | 794A    |
| Strain Relievers.....          | 795     |

## **O-RINGS**

|                                 |      |
|---------------------------------|------|
| 26 Series Air Conditioning..... | 748N |
| 43 Series Flange.....           | 744  |
| Caterpillar style Flanges.....  | 748I |
| ORFS.....                       | 786  |
| SAE Straight Thread port.....   | 776A |



## **QUICK COUPLERS** **(HYDRAULIC)**

|                  |     |
|------------------|-----|
| 20 Series.....   | 791 |
| 60 Series.....   | 792 |
| 4000 Series..... | 793 |
| 6100 Series..... | 790 |
| FF Series.....   | 794 |



# HOSE THREAD FITTING GUIDES

|              |  |  |  |  |  |  |  |  |  |
|--------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Fitting Size | DIN "L" Swivel Female Thread Size                                                 | DIN "S" Swivel Female Thread Size                                                 | DIN "L" Male Stud Thread Size                                                     | DIN "S" Male Stud Thread Size                                                     | Male BSPP Thread Size                                                             | BSP Swivel Female Thread Size                                                      | French Swivel Female Gaz Series                                                     | French Swivel Female Metric Series                                                  | French Male Stud Metric Series                                                      |
| 4            | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | 1/4x19                                                                            | 1/4x19                                                                             | —                                                                                   | —                                                                                   | —                                                                                   |
| 6            | M12x1.5                                                                           | M14x1.5                                                                           | M12x1.5                                                                           | M14x1.5                                                                           | 3/8x19                                                                            | 3/8x19                                                                             | —                                                                                   | —                                                                                   | M12x1                                                                               |
| 8            | M14x1.5                                                                           | M16x1.5                                                                           | M14x1.5                                                                           | M16x1.5                                                                           | 1/2x14                                                                            | 1/2x14                                                                             | —                                                                                   | —                                                                                   | M14x1.5                                                                             |
| 10           | M16x1.5                                                                           | M18x1.5                                                                           | M16x1.5                                                                           | M18x1.5                                                                           | 5/8x14                                                                            | 5/8x14                                                                             | —                                                                                   | —                                                                                   | M16x1.5                                                                             |
| 12           | M18x1.5                                                                           | M20x1.5                                                                           | M18x1.5                                                                           | M20x1.5                                                                           | 3/4x14                                                                            | 3/4x14                                                                             | —                                                                                   | —                                                                                   | M18x1.5                                                                             |
| —            | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                  | M20x1.5                                                                             | —                                                                                   | —                                                                                   |
| 14           | —                                                                                 | M22x1.5                                                                           | —                                                                                 | M22x1.5                                                                           | —                                                                                 | —                                                                                  | —                                                                                   | —                                                                                   | M20x1.5                                                                             |
| 15           | M22x1.5                                                                           | —                                                                                 | M22x1.5                                                                           | —                                                                                 | —                                                                                 | —                                                                                  | —                                                                                   | —                                                                                   | M22x1.5                                                                             |
| 16           | —                                                                                 | M24x1.5                                                                           | —                                                                                 | M24x1.5                                                                           | 1x11                                                                              | 1x 11                                                                              | —                                                                                   | —                                                                                   | M24x1.5                                                                             |
| —            | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                  | M24x1.5                                                                             | —                                                                                   | —                                                                                   |
| 18           | M26x1.5                                                                           | —                                                                                 | M26x1.5                                                                           | —                                                                                 | —                                                                                 | —                                                                                  | —                                                                                   | —                                                                                   | M27x1.5                                                                             |
| 20           | —                                                                                 | M30x2                                                                             | —                                                                                 | M30x2                                                                             | 1 1/4x11                                                                          | 1 1/4x11                                                                           | —                                                                                   | —                                                                                   | M27x1.5                                                                             |
| —            | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                  | M30x 1.5                                                                            | —                                                                                   | —                                                                                   |
| 22           | M30x2                                                                             | —                                                                                 | M30x2                                                                             | —                                                                                 | —                                                                                 | —                                                                                  | —                                                                                   | —                                                                                   | M30x1.5                                                                             |
| 25           | —                                                                                 | M36x2                                                                             | —                                                                                 | M36x2                                                                             | 1 1/2x11                                                                          | 1 1/2x11                                                                           | —                                                                                   | —                                                                                   | M33x1.5                                                                             |
| —            | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                  | M36x1.5                                                                             | —                                                                                   | —                                                                                   |
| 28           | M36x2                                                                             | —                                                                                 | M36x2                                                                             | —                                                                                 | —                                                                                 | —                                                                                  | —                                                                                   | —                                                                                   | M36x1.5                                                                             |
| 30           | —                                                                                 | M42x2                                                                             | —                                                                                 | M42x2                                                                             | 2x11                                                                              | 2x11                                                                               | —                                                                                   | —                                                                                   | M39x1.5                                                                             |
| 33           | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                 | —                                                                                  | M45x1.5                                                                             | —                                                                                   | —                                                                                   |

|           |  |  |  |  |  |  |  |  |
|-----------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Dash Size | NPTF Pipe Thread Size                                                               | SAE (JIC) 37° Flare Thread Size                                                     | SAE 45° Flare Thread Size                                                           | "O" Ring Style Straight Thread Size                                                 | SAE Inverted Flare Thread Size                                                      | PTT 30° Flare Thread Size                                                            | SAE Flareless Thread Size                                                             | Seal-Lok Thread                                                                       |
| 2         | 1/8-27                                                                              | 5/16-24                                                                             | 5/16-24                                                                             | 5/16-24                                                                             | —                                                                                   | —                                                                                    | 5/16-24                                                                               | —                                                                                     |
| 3         | —                                                                                   | 3/8-24                                                                              | 3/8-24                                                                              | 3/8-24                                                                              | —                                                                                   | —                                                                                    | 3/8-24                                                                                | —                                                                                     |
| 4         | 1/4-18                                                                              | 7/16-20                                                                             | 7/16-20                                                                             | 7/16-20                                                                             | 1/4-18                                                                              | —                                                                                    | 7/16-20                                                                               | 9/16-18                                                                               |
| 5         | —                                                                                   | 1/2-20                                                                              | 1/2-20                                                                              | 1/2-20                                                                              | —                                                                                   | —                                                                                    | 1/2-20                                                                                | —                                                                                     |
| 6         | 3/8-18                                                                              | 9/16-18                                                                             | 5/8-18                                                                              | 9/16-18                                                                             | 3/8-18                                                                              | —                                                                                    | 9/16-18                                                                               | 11/16-16                                                                              |
| 8         | 1/2-14                                                                              | 3/4-16                                                                              | 3/4-16                                                                              | 3/4-16                                                                              | 1/2-14                                                                              | —                                                                                    | 3/4-16                                                                                | 13/16-16                                                                              |
| 10        | —                                                                                   | 7/8-14                                                                              | 7/8-14                                                                              | 7/8-14                                                                              | —                                                                                   | —                                                                                    | 7/8-14                                                                                | 1-14                                                                                  |
| 12        | 3/4-14                                                                              | 11/16-12                                                                            | 11/16-12                                                                            | 11/16-12                                                                            | —                                                                                   | —                                                                                    | 11/16-12                                                                              | 13/16-12                                                                              |
| 14        | —                                                                                   | 13/16-12                                                                            | —                                                                                   | 13/16-12                                                                            | —                                                                                   | —                                                                                    | 13/16-12                                                                              | —                                                                                     |
| 16        | 1-11 1/2                                                                            | 15/16-12                                                                            | —                                                                                   | 15/16-12                                                                            | —                                                                                   | 15/16-14                                                                             | 15/16-12                                                                              | 17/16-12                                                                              |
| 20        | 1 1/4-11 1/2                                                                        | 15/8-12                                                                             | —                                                                                   | 15/8-12                                                                             | —                                                                                   | 15/8-14                                                                              | 15/8-12                                                                               | —                                                                                     |
| 24        | 1 1/2-11 1/2                                                                        | 17/8-12                                                                             | —                                                                                   | 17/8-12                                                                             | —                                                                                   | 17/8-14                                                                              | 17/8-12                                                                               | —                                                                                     |
| 32        | 2-11 1/2                                                                            | 2 1/2-12                                                                            | —                                                                                   | 2 1/2-12                                                                            | —                                                                                   | 2 1/2-12                                                                             | 2 1/2-12                                                                              | —                                                                                     |

# HOSES / RUBBER

## 881/811 (SAE 100R4) LOW PRESSURE

"Suction and Return Lines"

881/811 (SAE 100R4) HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

43 Series                      Pages 740 - 745

88 Series                      Page 764

### Applications:

881 hose can be used for all hydraulic system hose suction or return lines.

### Construction:

Synthetic rubber tube; reinforced by two textile braids or a woven ply, combined with wire spiraled throughout the textile reinforcement to prevent collapse under vacuum.



### **Hose Cover**

need not be removed for assembly of no-skive fittings


### Temperature Range:

-40°F to +257°F (-40°C to +125°C)

| J&B # | HOSE I.D. | HOSE O.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI)<br>88HC-H Clamp | MAXIMUM WORKING PRESSURE (PSI)<br>88HC Clamp | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|----------|------------------------------------------------|----------------------------------------------|------------------------------|--------|
| 50812 | 3/4       | 1.20      | 811-12   | 300**                                          | 100*                                         | 1,200                        | Per/Ft |
| 50816 | 1         | 1.49      | 811-16   | 250**                                          | 70*                                          | 1,000                        | Per/Ft |
| 50817 | 1-1/4     | 1.78      | 811-20   | 200**                                          | 50*                                          | 800                          | Per/Ft |
| 50819 | 1-1/2     | 2.06      | 881-24   | 150**                                          | 50*                                          | 600                          | Per/Ft |
| 50821 | 2         | 2.48      | 881-32   | 100**                                          | 50*                                          | 400                          | Per/Ft |

\* Pressure is below 100R4 requirements.

\*\* Parkrimp fitting pressure ratings.



See brochure for crimp machine information. . .

# HOSE / RUBBER

## 426 (SAE 100R1 AT) MEDIUM PRESSURE "Hi-Temp Hose"

426 (SAE 100R1 AT) HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

43 Series

Pages 740 - 745

### Applications :

For air above 250 PSI (1,7 Mpa), the cover should be pin-pricked. **Makes excellent pressure washer hose.**



### **Hose Cover**

need not be removed for assembly of no-skive fittings


### Construction:

Synthetic rubber tube; single high tensile steel wire braid reinforcement; MSHA accepted synthetic rubber cover.

### Temperature Range:

Water, water/glycol, and water/oil emulsion hydraulic fluids up to +185°F (+85°C). Petroleum based hydraulic fluid and lubricating oils within a temperature range of -50°F to +302°F (-46°C to +150°C). Air within a temperature range of -40°F to + 158°F (-40°C to + 70°C).

| J&B # | HOSE I.D. | HOSE O.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|----------|--------------------------------|------------------------------|--------|
| 50520 | 3/8       | .69       | 426-6    | 2,250                          | 9,000                        | Per/Ft |
| 50522 | 1/2       | .81       | 426-8    | 2,000                          | 8,000                        | Per/Ft |



*See brochure for crimp machine information. . .*



# HOSE / RUBBER

## 201 (SAE J1402 All) MEDIUM PRESSURE "Hi-Temp Hose"

201 (SAE J1402 All) HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

|           |                 |
|-----------|-----------------|
| 20 Series | Pages 750 - 754 |
| 22 Series | Page 757        |
| 26 Series | Pages 748K-748N |

### Applications:

Medium pressure hydraulic, turbo charger, filtration and lube oil lines, diesel fuel filter, engine and transmission coolant lines, ^air brake, power steering, and tilt cab. SAE J1402 and D.O.T. FMVSS 106-All air brake hose requirements.



### Hose Cover

need not be removed for  
assembly of no-skive fittings

### Construction:

Synthetic rubber tube, textile inner braid, high tensile steel wire braid reinforcement, textile braid cover.

### Temperature Range:

-40°F to +302°F (-40°C to +150°C) ^+158°F maximum.

| J&B # | HOSE I.D. | HOSE O.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|----------|--------------------------------|------------------------------|--------|
| 50204 | 3/16      | .52       | 201-4    | 2,500                          | 10,000                       | Per/Ft |
| 50205 | 1/4       | .58       | 201-5    | 2,250                          | 9,000                        | Per/Ft |
| 50206 | 5/16      | .68       | 201-6    | 2,000                          | 9,000                        | Per/Ft |
| 50208 | 13/32     | .77       | 201-8    | 1,850                          | 8,000                        | Per/Ft |
| 50210 | 1/2       | .92       | 201-10   | 1,400                          | 5,600                        | Per/Ft |
| 50212 | 5/8       | 1.08      | 201-12   | 1,200                          | 4,800                        | Per/Ft |
| 50216 | 7/8       | 1.23      | 201-16   | 600                            | 2,400                        | Per/Ft |
|       | 1-1/8     | 1.50      | 201-20   | 500                            | 2,000                        | Per/Ft |

\* Usage at temperatures exceeding +200°F is based on reduced working pressure.

# HOSE / RUBBER

---

## SS25UL "LPG Hose"

SS25UL LPG HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

20 Series                      Pages 750 - 754

22 Series                      Page 757

---

### Applications:

Designed for use with liquefied petroleum gas (LPG).

### Construction:

Synthetic rubber high temperature tube, one stainless steel wire braid and two textile braids.



### Temperature Range:

-40°F to +257°F (-40°C to +125°C).

| J&B # | HOSE I.D. | HOSE O.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|----------|--------------------------------|------------------------------|--------|
| 50106 | 5/16      | .68       | SS25UL-6 | 350                            | 1,750                        | Per/Ft |

# HOSE / RUBBER

## 302 (SAE 100R2 TYPE AT) HIGH PRESSURE

302 (SAE 100R2 TYPE AT) HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

30 Series                      Pages 760 - 761

43 Series                      Pages 740 - 745

### Applications:

High pressure service with petroleum base hydraulic fluids, \*water glycol and \*water-oil emulsion hydraulic fluids, hot oil, grease, lubricants, crude and fuel oils, ^air, \*water. For air or gas applications above 250 psi the cover should be pin pricked. MSHA accepted cover.



### **Hose Cover**

need not be removed for  
assembly of no-skive fittings


### Construction:

Synthetic rubber tube, two braids of high tensile steel wire reinforcement separated by synthetic rubber layer. Oil, weather and abrasion resistant synthetic rubber outer cover.

### Temperature Range:

-40°F to +212°F. (-40°C to +100°C) ^+158°F (+70°C) maximum, \*+185°F (+85°C) maximum.

| J&B # | HOSE<br>I.D. | HOSE<br>O.D. | PARKER # | MAXIMUM<br>WORKING<br>PRESSURE<br>(PSI) | MINIMUM<br>BURST<br>PRESSURE<br>(PSI) | QTY    |
|-------|--------------|--------------|----------|-----------------------------------------|---------------------------------------|--------|
| 50554 | 1/4          | .59          | 302-4    | 5,800                                   | 20,000                                | Per/Ft |
| 50556 | 3/8          | .75          | 302-6    | 4,750                                   | 16,000                                | Per/Ft |
| 50558 | 1/2          | .88          | 302-8    | 4,000                                   | 14,000                                | Per/Ft |
|       | 5/8          | 1.00         | 302-10   | 3,600                                   | 11,000                                | Per/Ft |
| 50562 | 3/4          | 1.16         | 302-12   | 3,100                                   | 9,000                                 | Per/Ft |
| 50564 | 1            | 1.50         | 302-16   | 2,400                                   | 8,000                                 | Per/Ft |
|       | 1-1/4        | 1.86         | 302-20   | 1,800                                   | 6,500                                 | Per/Ft |
|       | 1-1/2        | 2.16         | 302-24   | 1,300                                   | 5,000                                 | Per/Ft |
|       | 2            | 2.66         | 302-32   | 1,150                                   | 4,500                                 | Per/Ft |



See brochure for crimp machine information. . .

# HOSE / RUBBER

## 351TC ABRASION RESISTANT

351TC HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

43 Series

Pages 740-745

### Applications:

Petroleum-based hydraulic fluids and lubrication oils.

### Construction:

Inner tube of oil resistant Nitrile Synthetic rubber, two braids of high tensile steel wire reinforcement and an oil, weather and abrasion resistant, black, synthetic rubber, MSHA accepted cover.

### Temperature Range:

Petroleum base hydraulic fluids and lubricating oils within a temperature range of -40 C to +100 C (-40 F to +212 F). Water, water/glycol, and water/oil emulsion hydraulic fluids up to +85 C (+185 F). Air up to 70 C (158 F).


PARKER 351TC



### **Hose Cover**

need not be removed for assembly of no-skive fittings

| J&B # | HOSE I.D. | HOSE O.D. | MIN. BEND RADIUS | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|------------------|----------|--------------------------------|------------------------------|--------|
| 50584 | 1/4       | .51       | 2                | 351TC-4  | 4000                           | 16,000                       | Per/Ft |
| 50585 | 3/8       | .67       | 2-1/2            | 351TC-6  | 4000                           | 16,000                       | Per/Ft |
| 50588 | 1/2       | .80       | 3-1/2            | 351TC-8  | 4000                           | 16,000                       | Per/Ft |
| 50589 | 5/8       | .93       | 4                | 351TC-10 | 4000                           | 16,000                       | Per/Ft |
| 50591 | 3/4       | 1.09      | 4-3/4            | 351TC-12 | 4000                           | 16,000                       | Per/Ft |



See brochure for crimp machine information. . .

# HOSE / RUBBER

## 451TC 3000 PSI CONSTANT PRESSURE TOUGH COVER HOSE

451TC HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

43 Series

Pages 740 - 745

### Applications:

3000 PSI hose for applications where greater protection against abrasion is required.

### Construction:

Synthetic rubber tube compatible with most petroleum-base hydraulic fluids; a high-tensile steel wire reinforcement; and an oil, weather, and abrasion resistant black synthetic rubber cover.

### Temperature Range:


Most petroleum – base hydraulic and lubricating oils within a temperature range of -40°F to +212°F (40°C to +100°C). Water, water/glycol, and water/oil emulsion hydraulic fluids up to +185°F (+85°C). Air within a temperature range of -40°F to +158°F (-40°C to +70°C).



### **Hose Cover**

need not be removed for assembly of no-skive fittings

| J&B # | HOSE I.D. | HOSE O.D. | MIN. BEND RADIUS | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|------------------|----------|--------------------------------|------------------------------|--------|
| 50057 | 1/4       | .52       | 2                | 451TC-4  | 3,000                          | 12,000                       | Per/Ft |
| 50059 | 3/8       | .68       | 2-1/2            | 451TC-6  | 3,000                          | 12,000                       | Per/Ft |
| 50050 | 1/2       | .80       | 3-1/2            | 451TC-8  | 3,000                          | 12,000                       | Per/Ft |
| 50051 | 5/8       | .94       | 4                | 451TC-10 | 3,000                          | 12,000                       | Per/Ft |
| 50052 | 3/4       | 1.10      | 4-3/4            | 451TC-12 | 3,000                          | 12,000                       | Per/Ft |
| 50054 | 1         | 1.40      | 6                | 451TC-16 | 3,000                          | 12,000                       | Per/Ft |
| 50590 | 1-1/4     | 1.85      | 8-1/4            | 451TC-20 | 3,000                          | 12,000                       | Per/Ft |



See brochure for crimp machine information. . .

# HOSE / RUBBER

## 471TC (EN857 TYPE 25C) HIGH PRESSURE HYDRAULIC HOSE

471TC HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

43 Series

Pages 740-745

### Applications:

Petroleum-based hydraulic fluids and lubrication oils.

### Construction:

Inner tube of oil resistant Nitrile Synthetic rubber, Multiple high tensile steel wire reinforcements; and an oil, weather and abrasion-resistant black MSHA-accepted synthetic rubber cover.

### Temperature Range:


Petroleum base hydraulic fluids and lubricating oils within a temperature range of -40 C to +100 C (-40 F to +212 F). Water, water/glycol, and water/oil emulsion hydraulic fluids up to +85 C (+185 F). Air up to 70 C (158 F).



### **Hose Cover**

need not be removed for assembly of no-skive fittings

| J&B # | HOSE I.D. | HOSE O.D. | MIN. BEND RADIUS | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|------------------|----------|--------------------------------|------------------------------|--------|
| 50576 | 3/8       | .68       | 2-1/2            | 471TC-6  | 5,000                          | 20,000                       | Per/Ft |
| 50578 | 1/2       | .80       | 3-1/2            | 471TC-8  | 4,250                          | 17,000                       | Per/Ft |
| 50582 | 3/4       | 1.09      | 4-3/4            | 471TC-12 | 3,125                          | 12,500                       | Per/Ft |
| 50583 | 1         | 1.39      | 6                | 471TC-16 | 2,500                          | 10,000                       | Per/Ft |



See brochure for crimp machine information. . .

# HOSE / RUBBER

## 772TC (SAE 100R12) HIGH PRESSURE HYDRAULIC HOSE

772TC HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

71 Series

Pages 748-748B

### Applications:

Four heavy spiral hose for use on high pressure hydraulics.

### Construction:

Inner tube of oil resistant Nitrile Synthetic rubber, 4 spiral piles of high tensile steel wire reinforcement; and an oil, weather, and abrasion resistant black synthetic MSHA accepted rubber cover.

### Temperature Range:


Petroleum base hydraulic fluids and lubricating oils within a temperature range of -40 C to +125 C (-40 F to +257 F). Water, water/glycol, and water/oil emulsion hydraulic fluids up to +85 C (+185 F). Air up to 70 C (158 F).



### **Hose Cover**

need not be removed for assembly of no-skive fittings

| J&B # | HOSE I.D. | HOSE O.D. | MIN. BEND RADIUS | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|------------------|----------|--------------------------------|------------------------------|--------|
| 55712 | 3/4       | 1.20      | 9-1/2            | 772TC-12 | 4,000                          | 16,000                       | Per/Ft |
| 55716 | 1         | 1.48      | 12               | 772TC-16 | 4,000                          | 16,000                       | Per/Ft |
| 55720 | 1-1/4     | 1.84      | 16-1/2           | 772TC-20 | 3,000                          | 12,000                       | Per/Ft |
| 55724 | 1-1/2     | 2.07      | 20               | 772TC-24 | 2,500                          | 10,000                       | Per/Ft |
| 55732 | 2         | 2.59      | 25               | 772TC-32 | 2,500                          | 10,000                       | Per/Ft |



See brochure for crimp machine information. . .



# HOSE / RUBBER

## 782TC (SAE 100R13) HIGH PRESSURE HYDRAULIC HOSE

782TC HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .

78 Series Pages 748E-748J

### Applications:

Multiple plies of spiral wire, red rubber cover hose for use on high pressure hydraulics.

### Construction:

Synthetic rubber tube; multiple spirals of high tensile steel wire reinforcement; MSHA accepted red synthetic rubber cover.

### Temperature Range:


Petroleum based hydraulic fluids and lubricating oils within a temperature range of -40 F to +257 F (-40 C to +125 C). Water, water/glycol, and water/oil emulsion hydraulic fluids up to +185 F (+85 C). Air within a temperature range of -40 F to +158 F (-40 C to +70 C.) For air above 250psi(1,7 Mpa), the cover should be pin-pricked.



### **Hose Cover**

need not be removed for assembly of no-skive fittings

| J&B # | HOSE I.D. | HOSE O.D. | MIN. BEND RADIUS | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|-------|-----------|-----------|------------------|----------|--------------------------------|------------------------------|--------|
| 55740 | 1         | 1.52      | 12               | 782TC-16 | 5,000                          | 20,000                       | Per/Ft |
| 55742 | 1-1/4     | 1.96      | 16-1/2           | 782TC-20 | 5,000                          | 20,000                       | Per/Ft |
| 55744 | 1-1/2     | 2.26      | 20               | 782TC-24 | 5,000                          | 20,000                       | Per/Ft |



See brochure for crimp machine information. . .

# HOSE / THERMOPLASTIC

## 518C MEDIUM PRESSURE

"Non-Conductive Hose"

518C HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

55 Series

Pages 746-747

### Applications:

Hydraulic circuits and systems. Excellent low temperature flexibility and flex fatigue life, broad range of chemical compatibility, low elongation and volumetric expansion. Can be installed with very low bend radii. For hydraulic circuits and systems found on utility vehicles and equipment where exposure and contact with high voltage may be encountered.



Meets SAEJ343 for less than 50 microamps leakage under 75000 volts per ft. Meets or exceeds SAE 100R7 specifications.

### Construction:


Elastomeric core, fiber reinforcement, abrasion-resistant special PFX cover. All layers bonded for optimum kink resistance and flexibility. High density braid for maximum impulse life without loss of flexibility. Standard cover is orange, non-perforated.

### Temperature Range:

-40°F to +212°F (-40°C to +100°C) except limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids.

| J&B #  | HOSE I.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY    |
|--------|-----------|----------|--------------------------------|------------------------------|--------|
| V50038 | 1/8       | 518C-2   | 3,000                          | 10,000                       | Per/Ft |
| 50039  | 3/16      | 518C-3   | 3,000                          | 12,000                       | Per/Ft |
| 50040  | 1/4       | 518C-4   | 3,000                          | 10,000                       | Per/Ft |
| 50042  | 5/16      | 518C-5   | 3,000                          | 10,000                       | Per/Ft |
| 50046  | 3/8       | 518C-6   | 3,000                          | 9,000                        | Per/Ft |
| 50048  | 1/2       | 518C-8   | 3,000                          | 9,000                        | Per/Ft |

**NOTE:** The above hose is not intended for use in static discharge applications; i.e., airless paint spray.



See brochure for crimp machine information. . .

# HOSE / THERMOPLASTIC

## 919 (SAE100R14) MEDIUM PRESSURE "TFE Stainless"

919 (SAE100R14) HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . . .

90 Series                      Page    767

91 Series                      Page    768

### Applications:

TFE liner is inert to almost all chemicals. Outstanding flex fatigue and shock resistance for hydraulic systems. Smooth, low friction, non-stick inner surface and corrosion resistant wire. PTFE is flexible at low temperatures, non-aging and low moisture permeation. Can be used for steam up to 200 psi (+388°F).



### Construction:

Extruded PTFE core tube, 304 stainless steel wire braid for reinforcement and mechanical protection.

### **Hose Cover**

need not be removed for assembly of no-skive fittings

### Temperature Range:

-100°F to +450°F (-73°C to +232°C).

| J&B # | HOSE I.D. | PARKER # | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | MIN. BEND RADIUS | QTY    |
|-------|-----------|----------|--------------------------------|------------------------------|------------------|--------|
| 50307 | 3/16      | 919-4    | 3,000                          | 12,000                       | 2                | Per/Ft |
| 50305 | 1/4       | 919-5    | 3,000                          | 12,000                       | 3                | Per/Ft |
| 50308 | 5/16      | 919-6    | 2,500                          | 10,000                       | 4                | Per/Ft |
| 50309 | 13/32     | 919-8    | 2,000                          | 8,000                        | 5                | Per/Ft |
| 50310 | 1/2       | 919-10   | 1,500                          | 6,000                        | 6-1/2            | Per/Ft |
| 50312 | 5/8       | 919-12   | 1,200                          | 5,000                        | 7-1/2            | Per/Ft |

# AIR CONDITONING HOSE

## 285 (SAE J2064 TYPE C, CLASS 1) REFRIGERANT HOSE

285 HOSE CAN BE USED WITH THE FOLLOWING FITTINGS . .


26 Series

Pages

748K-748N

### Construction:

The hose has a nylon barrier between two elastomeric layers, a fabric braid reinforcement and a heat, moisture and ozone resistant elastomer cover.



### Temperature Range:


Refrigerant 12, 134a and 22 within a temperature range of -22 F to +257 F (-30 C to +125 C).

### **Hose Cover**

need not be removed for assembly of no-skive fittings

285 HOSE IS ON OUR SHELF 50 FEET PER BOX

| J&B # | HOS<br>E I.D. | HOSE<br>O.D. | MIN.<br>BEND<br>RADIUS | PARKER #  | MAXIMUM<br>WORKING<br>PRESSURE<br>(PSI) | MINIMUM<br>BURST<br>PRESSURE<br>(PSI) | QTY    |
|-------|---------------|--------------|------------------------|-----------|-----------------------------------------|---------------------------------------|--------|
| 46032 | 5/16          | 0.62         | 1-1/2                  | 285-6-BX  | 500                                     | 2,500                                 | Per/Ft |
| 46033 | 13/32         | 0.74         | 2                      | 285-8-BX  | 500                                     | 2,500                                 | Per/Ft |
| 46034 | 1/2           | 0.83         | 2-1/2                  | 285-10-BX | 500                                     | 2,500                                 | Per/Ft |
| 46035 | 5/8           | 0.96         | 3                      | 285-12-BX | 500                                     | 2,500                                 | Per/Ft |



See brochure for crimp machine information. . .

# PARKRIMP HOSE FITTINGS


## 43 SERIES

43 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSES . . . .

|                      |                      |           |
|----------------------|----------------------|-----------|
| 881 (SAE 100R4)      | LOW PRESSURE HOSE    | Page 720  |
| 426HT (SAE 100R1 AT) | MEDIUM PRESSURE HOSE | Page 724  |
| 301 (SAE 100R2 AT)   | HIGH PRESSURE HOSE   | Page 730  |
| 341 (SAE 100R9 AT)   | HIGH PRESSURE HOSE   | Page 732  |
| 451TC (3000 PSI)     | HIGH PRESSURE HOSE   | Page 733  |
| 471TC                | HIGH PRESSURE HOSE   | Page 733A |


| J&B # | PARKER #    | HOSE I.D. | PIPE THREAD | QTY |
|-------|-------------|-----------|-------------|-----|
| 52698 | 10143-2-4   | 1/4       | 1/8         | 1   |
| 52700 | 10143-4-4   | 1/4       | 1/4         | 1   |
| 52701 | 10143-6-4   | 1/4       | 3/8         | 1   |
| 52702 | 10143-4-6   | 3/8       | 1/4         | 1   |
| 52703 | 10143-6-6   | 3/8       | 3/8         | 1   |
| 52704 | 10143-8-6   | 3/8       | 1/2         | 1   |
| 52705 | 10143-6-8   | 1/2       | 3/8         | 1   |
| 52706 | 10143-8-8   | 1/2       | 1/2         | 1   |
| 52707 | 10143-12-8  | 1/2       | 3/4         | 1   |
| 52713 | 10143-8-10  | 5/8       | 1/2         | 1   |
| 52711 | 10143-12-10 | 5/8       | 3/4         | 1   |
| 52715 | 10143-8-12  | 3/4       | 1/2         | 1   |
| 52708 | 10143-12-12 | 3/4       | 3/4         | 1   |
| 52718 | 10143-16-12 | 3/4       | 1           | 1   |
| 52709 | 10143-12-16 | 1         | 3/4         | 1   |
| 52710 | 10143-16-16 | 1         | 1           | 1   |
| 52712 | 10143-20-20 | 1-1/4     | 1-1/4       | 1   |
| 52719 | 10143-24-24 | 1-1/2     | 1-1/2       | 1   |
| 52728 | 10143-32-32 | 2         | 2           | 1   |

**MALE PIPE NPTF  
10143**



| J&B # | PARKER #    | HOSE I.D. | PIPE THREAD | QTY |
|-------|-------------|-----------|-------------|-----|
| 56515 | 11343-2-4   | 1/4       | 1/8         | 1   |
| 54304 | 11343-4-4   | 1/4       | 1/4         | 1   |
| 54305 | 11343-4-6   | 3/8       | 1/4         | 1   |
| 54306 | 11343-6-6   | 3/8       | 3/8         | 1   |
| 54307 | 11343-8-6   | 3/8       | 1/2         | 1   |
| 54309 | 11343-6-8   | 1/2       | 3/8         | 1   |
| 54308 | 11343-8-8   | 1/2       | 1/2         | 1   |
| 54310 | 11343-12-12 | 3/4       | 3/4         | 1   |
| 54312 | 11343-16-16 | 1         | 1           | 1   |

**MALE PIPE  
NPTF SWIVEL  
11343**



\* The fitting allows minor movement under pressure to relieve stress on hose, but is not to be used for continuous or extensive swiveling.


# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #  | HOSE SIZE | MALE PIPE | QTY |
|-------|-----------|-----------|-----------|-----|
| 56120 | 11L43-4-4 | 1/4       | 1/4       | 1   |
| 56121 | 11L43-6-6 | 3/8       | 3/8       | 1   |
| 56122 | 11L43-8-8 | 1/2       | 1/2       | 1   |

### MALE NPTF PIPE 90° ELBOW SWIVEL


**11L43**



| J&B # | PARKER #    | HOSE SIZE | FEMALE PIPE | QTY |
|-------|-------------|-----------|-------------|-----|
| 56417 | 10243-4-4   | 1/4       | 1/4         | 1   |
| 56419 | 10243-6-4   | 1/4       | 3/8         | 1   |
| 56420 | 10243-6-6   | 3/8       | 3/8         | 1   |
| 56421 | 10243-8-6   | 3/8       | 1/2         | 1   |
| 56422 | 10243-8-8   | 1/2       | 1/2         | 1   |
| 56424 | 10243-12-12 | 3/4       | 3/4         | 1   |

### FEMALE NPTF PIPE - RIGID


**10243**



| J&B # | PARKER #    | HOSE SIZE | PIPE THREAD | QTY |
|-------|-------------|-----------|-------------|-----|
| 55020 | 10743-4-4   | 1/4       | 1/4         | 1   |
| 55022 | 10743-6-6   | 3/8       | 3/8         | 1   |
| 55025 | 10743-8-8   | 1/2       | 1/2         | 1   |
| 55026 | 10743-12-12 | 3/4       | 3/4         | 1   |

### FEMALE NPSM PIPE SWIVEL (60° CONE)

**10743**




# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B #   | PARKER #    | HOSE<br>I. D. | TUBE  |           | QTY |
|---------|-------------|---------------|-------|-----------|-----|
|         |             |               | SIZE  | THREAD    |     |
| * 52714 | 10643-4-4   | 1/4           | 1/4   | 7/16-20   | 1   |
| * 52716 | 10643-5-4   | 1/4           | 5/16  | 1/2-20    | 1   |
| 52717   | 10643-6-4   | 1/4           | 3/8   | 9/16-18   | 1   |
| 52721   | 10643-4-6   | 3/8           | 1/4   | 7/16-20   | 1   |
| 52723   | 10643-5-6   | 3/8           | 5/16  | 1/2-20    | 1   |
| 52720   | 10643-6-6   | 3/8           | 3/8   | 9/16-18   | 1   |
| * 52722 | 10643-8-6   | 3/8           | 1/2   | 3/4-16    | 1   |
| 55970   | 10643-10-6  | 3/8           | 5/8   | 7/8-14    | 1   |
| 52725   | 10643-6-8   | 1/2           | 3/8   | 9/16-18   | 1   |
| * 52724 | 10643-8-8   | 1/2           | 1/2   | 3/4-16    | 1   |
| * 52726 | 10643-10-8  | 1/2           | 5/8   | 7/8-14    | 1   |
| 52730   | 10643-12-8  | 1/2           | 3/4   | 1-1/16-12 | 1   |
| 52727   | 10643-8-10  | 5/8           | 1/2   | 3/4-16    | 1   |
| 52731   | 10643-10-10 | 5/8           | 5/8   | 7/8-14    | 1   |
| 52729   | 10643-12-10 | 5/8           | 3/4   | 1-1/16-12 | 1   |
| 52733   | 10643-8-12  | 3/4           | 1/2   | 3/4-16    | 1   |
| * 52732 | 10643-10-12 | 3/4           | 5/8   | 7/8-14    | 1   |
| 52734   | 10643-12-12 | 3/4           | 3/4   | 1-1/16-12 | 1   |
| * 52736 | 10643-14-12 | 3/4           | 7/8   | 1-3/16-12 | 1   |
| * 52738 | 10643-16-12 | 3/4           | 1     | 1-5/16-12 | 1   |
| 52735   | 10643-12-16 | 1             | 3/4   | 1-1/16-12 | 1   |
| * 52740 | 10643-16-16 | 1             | 1     | 1-5/16-12 | 1   |
| 52737   | 10643-20-16 | 1             | 1-1/4 | 1-5/8-12  | 1   |
| * 52742 | 10643-20-20 | 1-1/4         | 1-1/4 | 1-5/8-12  | 1   |
| 52743   | 10643-24-24 | 1-1/2         | 1-1/2 | 1-7/8-12  | 1   |

**JIC 37° SWIVEL  
10643**




\* Note: The 10643 couplings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations, except in sizes - 6 (3/8") and - 12 (3/4")

| J&B # | PARKER #    | HOSE<br>I. D. | TUBE  |           | QTY |
|-------|-------------|---------------|-------|-----------|-----|
|       |             |               | SIZE  | THREAD    |     |
| 56140 | 14143-4-4   | 1/4           | 1/4   | 7/16-20   | 1   |
| 56142 | 14143-6-6   | 3/8           | 3/8   | 9/16-18   | 1   |
| 56144 | 14143-8-8   | 1/2           | 1/2   | 3/4-16    | 1   |
| 56145 | 14143-10-10 | 5/8           | 5/8   | 7/8-14    | 1   |
| 56146 | 14143-12-12 | 3/4           | 3/4   | 1-1/16-12 | 1   |
| 56147 | 14143-16-16 | 1             | 1     | 1-5/16-12 | 1   |
| 56148 | 14143-20-20 | 1-1/4         | 1-1/4 | 1-5/8-12  | 1   |

**JIC 37° SWIVEL 90°  
ELBOW (LONG)**

**14143**




# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE  |           | QTY |
|-------|-------------|--------------|-------|-----------|-----|
|       |             |              | SIZE  | THREAD    |     |
| 54244 | 10343-4-4   | 1/4          | 1/4   | 7/16-20   | 1   |
| 54242 | 10343-5-4   | 1/4          | 5/16  | 1/2-20    | 1   |
| 54245 | 10343-6-4   | 1/4          | 3/8   | 9/16-18   | 1   |
| 54247 | 10343-5-6   | 3/8          | 5/16  | 1/2-20    | 1   |
| 54249 | 10343-6-6   | 3/8          | 3/8   | 9/16-18   | 1   |
| 54250 | 10343-8-6   | 3/8          | 1/2   | 3/4-16    | 1   |
| 54252 | 10343-8-8   | 1/2          | 1/2   | 3/4-16    | 1   |
| 54253 | 10343-10-8  | 1/2          | 5/8   | 7/8-14    | 1   |
| 54263 | 10343-12-8  | 1/2          | 3/4   | 1-1/16-12 | 1   |
| 54251 | 10343-8-10  | 5/8          | 1/2   | 3/4-16    | 1   |
| 54254 | 10343-10-10 | 5/8          | 5/8   | 7/8-14    | 1   |
| 54255 | 10343-12-10 | 5/8          | 3/4   | 1-1/16-12 | 1   |
| 54256 | 10343-12-12 | 3/4          | 3/4   | 1-1/16-12 | 1   |
| 54258 | 10343-16-12 | 3/4          | 1     | 1-5/16-12 | 1   |
| 54259 | 10343-16-16 | 1            | 1     | 1-5/16-12 | 1   |
| 55930 | 10343-20-20 | 1-1/4        | 1-1/4 | 1-5/8-12  | 1   |

**MALE JIC 37°**


**10343**



| J&B # | PARKER #    | HOSE<br>SIZE | TUBE  |           | QTY |
|-------|-------------|--------------|-------|-----------|-----|
|       |             |              | SIZE  | THREAD    |     |
| 54202 | 13743-4-4   | 1/4          | 1/4   | 7/16-20   | 1   |
| 54204 | 13743-6-4   | 1/4          | 3/8   | 9/16-18   | 1   |
| 54206 | 13743-6-6   | 3/8          | 3/8   | 9/16-18   | 1   |
| 54205 | 13743-8-6   | 3/8          | 1/2   | 3/4-16    | 1   |
| 54208 | 13743-8-8   | 1/2          | 1/2   | 3/4-16    | 1   |
| 54207 | 13743-10-8  | 1/2          | 5/8   | 7/8-14    | 1   |
| 54209 | 13743-10-10 | 5/8          | 5/8   | 7/8-14    | 1   |
| 54215 | 13743-12-10 | 5/8          | 3/4   | 1-1/16-12 | 1   |
| 54212 | 13743-12-12 | 3/4          | 3/4   | 1-1/16-12 | 1   |
| 54214 | 13743-16-16 | 1            | 1     | 1-5/16-12 | 1   |
| 55932 | 13743-20-20 | 1-1/4        | 1-1/4 | 1-5/8-12  | 1   |

**JIC 37° SWIVEL 45°  
ELBOW**

**13743**





# PARKRIMP HOSE FITTINGS


---

## 43 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE  |           | QTY |
|-------|-------------|--------------|-------|-----------|-----|
|       |             |              | SIZE  | THREAD    |     |
| 54219 | 13943-4-4   | 1/4          | 1/4   | 7/16-20   | 1   |
| 54225 | 13943-5-4   | 1/4          | 5/16  | 1/2-20    | 1   |
| 54222 | 13943-6-4   | 1/4          | 3/8   | 9/16-18   | 1   |
| 54295 | 13943-4-6   | 3/8          | 1/4   | 7/16-20   | 1   |
| 54223 | 13943-6-6   | 3/8          | 3/8   | 9/16-18   | 1   |
| 54224 | 13943-8-6   | 3/8          | 1/2   | 3/4-16    | 1   |
| 54296 | 13943-6-8   | 1/2          | 3/8   | 9/16-16   | 1   |
| 54226 | 13943-8-8   | 1/2          | 1/2   | 3/4-16    | 1   |
| 54227 | 13943-10-8  | 1/2          | 5/8   | 7/8-14    | 1   |
| 54228 | 13943-10-10 | 5/8          | 5/8   | 7/8-14    | 1   |
| 54298 | 13943-12-10 | 5/8          | 3/4   | 1-1/16-12 | 1   |
| 54230 | 13943-12-12 | 3/4          | 3/4   | 1-1/16-12 | 1   |
| 54231 | 13943-16-12 | 3/4          | 1     | 1-5/16-12 | 1   |
| 54232 | 13943-16-16 | 1            | 1     | 1-5/16-12 | 1   |
| 55934 | 13943-20-20 | 1-1/4        | 1-1/4 | 1-5/8-12  | 1   |

**JIC 37° SWIVEL 90°  
ELBOW (Short)**

**13943**




# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 56290 | 1JS43-4-4   | 1/4          | 1/4      | 9/16-18    | 1   |
| 56292 | 1JS43-6-4   | 1/4          | 3/8      | 11/16-16   | 1   |
| 56293 | 1JS43-4-6   | 3/8          | 1/4      | 9/16-18    | 1   |
| 56294 | 1JS43-6-6   | 3/8          | 3/8      | 11/16-16   | 1   |
| 56295 | 1JS43-8-6   | 3/8          | 1/2      | 13/16-16   | 1   |
| 56296 | 1JS43-6-8   | 1/2          | 3/8      | 11/16-16   | 1   |
| 56300 | 1JS43-8-8   | 1/2          | 1/2      | 13/16-16   | 1   |
| 56301 | 1JS43-10-8  | 1/2          | 5/8      | 1-14       | 1   |
| 56299 | 1JS43-12-8  | 1/2          | 3/4      | 1-3/16-12  | 1   |
| 56297 | 1JS43-8-10  | 5/8          | 1/2      | 13/16-16   | 1   |
| 56302 | 1JS43-10-10 | 5/8          | 5/8      | 1-14       | 1   |
| 56304 | 1JS43-12-10 | 5/8          | 3/4      | 1-3/16-12  | 1   |
| 56306 | 1JS43-10-12 | 3/4          | 5/8      | 1-14       | 1   |
| 56307 | 1JS43-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 56308 | 1JS43-16-12 | 3/4          | 1        | 1-7/16-12  | 1   |
| 56311 | 1JS43-12-16 | 1            | 3/4      | 1-3/16-12  | 1   |
| 56309 | 1JS43-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 56310 | 1JS43-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

### FEMALE "SEAL LOK" SWIVEL STRAIGHT


**1JS43**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |           | QTY |
|-------|-------------|--------------|----------|-----------|-----|
|       |             |              | SIZE     | THREAD    |     |
| 52820 | 1J043-4-4   | 1/4          | 1/4      | 9/16-18   | 1   |
| 52821 | 1J043-6-6   | 3/8          | 3/8      | 11/16-16  | 1   |
| 52822 | 1J043-8-6   | 3/8          | 1/2      | 13/16-16  | 1   |
| 52823 | 1J043-8-8   | 1/2          | 1/2      | 13/16-16  | 1   |
| 52825 | 1J043-10-8  | 1/2          | 5/8      | 1-14      | 1   |
| 52824 | 1J043-10-10 | 5/8          | 5/8      | 1-14      | 1   |
| 52826 | 1J043-12-10 | 5/8          | 3/4      | 1-3/16-12 | 1   |
| 52828 | 1J043-12-12 | 3/4          | 3/4      | 1-3/16-12 | 1   |
| 52830 | 1J043-16-12 | 3/4          | 1        | 1-7/16-12 | 1   |


### MALE "SEAL LOK" STRAIGHT WITH NITRILE O-RING

**1J043**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |          | QTY |
|-------|-------------|--------------|----------|----------|-----|
|       |             |              | SIZE     | THREAD   |     |
| 56510 | 1JC43-4-4   | 1/4          | 1/4      | 9/16-18  | 1   |
| 56512 | 1JC43-6-6   | 3/8          | 3/8      | 11/16-16 | 1   |
| 56514 | 1JC43-8-8   | 1/2          | 1/2      | 13/16-16 | 1   |
| 56509 | 1JC43-10-10 | 5/8          | 5/8      | 1-1/4    | 1   |

### FEMALE "SEAL LOK" SWIVEL STRAIGHT (CLOSE NUT) **1JC43**



# PARKRIMP HOSE FITTINGS


## 43 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 56388 | 1J943-4-4   | 1/4          | 1/4      | 9/16-18    | 1   |
| 56389 | 1J943-6-4   | 1/4          | 3/8      | 11/16-16   | 1   |
| 56390 | 1J943-6-6   | 3/8          | 3/8      | 11/16-16   | 1   |
| 56392 | 1J943-8-6   | 3/8          | 1/2      | 13/16-16   | 1   |
| 56418 | 1J943-6-8   | 1/2          | 3/8      | 11/16-16   | 1   |
| 56400 | 1J943-8-8   | 1/2          | 1/2      | 13/16-16   | 1   |
| 56402 | 1J943-10-8  | 1/2          | 5/8      | 1-14       | 1   |
| 56404 | 1J943-12-8  | 1/2          | 3/4      | 1-3/16-12  | 1   |
| 56405 | 1J943-8-10  | 5/8          | 1/2      | 13/16-16   | 1   |
| 56406 | 1J943-10-10 | 5/8          | 5/8      | 1-14       | 1   |
| 56408 | 1J943-12-10 | 5/8          | 3/4      | 1-3/16-12  | 1   |
| 56409 | 1J943-10-12 | 3/4          | 5/8      | 1-14       | 1   |
| 56410 | 1J943-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 56412 | 1J943-16-12 | 3/4          | 1        | 1-7/16-12  | 1   |
| 56414 | 1J943-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 56415 | 1J943-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

### FEMALE "SEAL LOK"

#### SWIVEL 90° ELBOW (SHORT)

1J943




| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55140 | 1J743-4-4   | 1/4          | 1/4      | 9/16-18    | 1   |
| 55142 | 1J743-6-4   | 1/4          | 3/8      | 11/16-16   | 1   |
| 55144 | 1J743-6-6   | 3/8          | 3/8      | 11/16-16   | 1   |
| 55146 | 1J743-8-6   | 3/8          | 1/2      | 13/16-16   | 1   |
| 55148 | 1J743-8-8   | 1/2          | 1/2      | 13/16-16   | 1   |
| 55150 | 1J743-10-8  | 1/2          | 5/8      | 1-14       | 1   |
| 55152 | 1J743-12-8  | 1/2          | 3/4      | 1-3/16-12  | 1   |
| 55154 | 1J743-10-10 | 5/8          | 5/8      | 1-14       | 1   |
| 55156 | 1J743-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 55158 | 1J743-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55160 | 1J743-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

### FEMALE "SEAL LOK"

#### SWIVEL 45 ELBOW

1J743




| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |           | QTY |
|-------|-------------|--------------|----------|-----------|-----|
|       |             |              | SIZE     | THREAD    |     |
| 52560 | 1J143-4-4   | 1/4          | 1/4      | 9/16-18   | 1   |
| 52561 | 1J143-6-6   | 3/8          | 3/8      | 11/16-16  | 1   |
| 52562 | 1J143-8-8   | 1/2          | 1/2      | 13/16-12  | 1   |
| 52564 | 1J143-12-12 | 3/4          | 3/4      | 1-3/16-12 | 1   |

### FEMALE "SEAL LOK"

#### SWIVEL 90 ELBOW LONG DROP

1J143




# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #    | HOSE SIZE | THREAD SIZE | QTY |
|-------|-------------|-----------|-------------|-----|
| 55000 | 10543-4-4   | 1/4       | 7/16-20     | 1   |
| 55003 | 10543-6-6   | 3/8       | 9/16-18     | 1   |
| 55004 | 10543-8-6   | 3/8       | 3/4-16      | 1   |
| 55005 | 10543-6-8   | 1/2       | 9/16-18     | 1   |
| 55006 | 10543-8-8   | 1/2       | 3/4-16      | 1   |
| 55009 | 10543-10-8  | 1/2       | 7/8-14      | 1   |
| 55010 | 10543-12-8  | 1/2       | 1-1/16-12   | 1   |
| 55011 | 10543-10-10 | 5/8       | 7/8-14      | 1   |
| 55012 | 10543-12-10 | 5/8       | 1-1/16-12   | 1   |
| 55014 | 10543-12-12 | 3/4       | 1-1/16-12   | 1   |
| 55016 | 10543-16-16 | 1         | 1-5/16-12   | 1   |

**MALE SAE  
STRAIGHT THREAD  
WITH O-RING - RIGID**

**10543**




| J&B # | PARKER #  | HOSE SIZE | THREAD SIZE | QTY |
|-------|-----------|-----------|-------------|-----|
| 56470 | 10L43-6-6 | 3/8       | 9/16-18     | 1   |
| 56472 | 10L43-8-8 | 1/2       | 3/4-16      | 1   |

**MALE SAE  
STRAIGHT THREAD  
WITH O-RING**

**90° ELBOW SWIVEL**


**10L43**



| J&B # | PARKER #  | HOSE SIZE | THREAD | QTY |
|-------|-----------|-----------|--------|-----|
| 56440 | 12843-5-6 | 3/8       | 1/2-20 | 1   |

**MALE INVERTED  
SAE 45° - SWIVEL**


**12843**



| J&B # | PARKER #  | HOSE SIZE | THREAD | QTY |
|-------|-----------|-----------|--------|-----|
| 56450 | 16943-5-6 | 3/8       | 1/2-20 | 1   |

**MALE INVERTED  
SAE 45° - SWIVEL  
90° ELBOW**

**16943**




# PARKRIMP HOSE FITTINGS

## 43 SERIES


| J&B #   | PARKER #    | HOSE SIZE | TUBE |           | QTY |
|---------|-------------|-----------|------|-----------|-----|
|         |             |           | SIZE | THREAD    |     |
| 52744   | 10843-6-6   | 3/8       | 3/8  | 5/8-18    | 1   |
| ^ 52747 | 10843-12-12 | 3/4       | 3/4  | 1-1/16-14 | 1   |

**SAE 45° SWIVEL  
10843**



| J&B #   | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|---------|-------------|-----------|-------------|-------------|---------------|-----|
| 52749   | 11543-8-8   | 1/2       | 1/2         | 1-3/16      | .265"         | 1   |
| 52754   | 11543-12-12 | 3/4       | 3/4         | 1-1/2       | .265"         | 1   |
| ^ 52755 | 11543-16-12 | 3/4       | 1           | 1-3/4       | .315"         | 1   |
| 52756   | 11543-16-16 | 1         | 1           | 1-3/4       | .315"         | 1   |
| ^ 52753 | 11543-20-16 | 1         | 1-1/4       | 2"          | .315"         | 1   |


**SAE (Code 61)  
FLANGE STRAIGHT  
11543**



O-rings not included

| J&B #   | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|---------|-------------|-----------|-------------|-------------|---------------|-----|
| ^ 52751 | 11943-8-8   | 1/2       | 1/2         | 1-3/16      | .265"         | 1   |
| ^ 52757 | 11943-12-8  | 1/2       | 3/4         | 1-1/2       | .265"         | 1   |
| 52758   | 11943-12-12 | 3/4       | 3/4         | 1-1/2       | .265"         | 1   |
| ^ 52759 | 11943-16-12 | 3/4       | 1           | 1-3/4       | .315"         | 1   |
| 52760   | 11943-16-16 | 1         | 1           | 1-3/4       | .315"         | 1   |
| ^ 52761 | 11943-20-16 | 1         | 1-1/4       | 2           | .315"         | 1   |


**SAE (Code 61)  
FLANGE 90° ELB.  
11943**



O-rings not included

## 90 DUROMETER NITRILE O-RINGS

| J&B # | PARKER # | FLANGE DASH SIZE | FLANGE SIZE | WIDTH | I.D.  | QTY |
|-------|----------|------------------|-------------|-------|-------|-----|
| 56278 | 711510-6 | -8               | 1/2         | .139  | .734  | 1   |
| 56280 | 711510-5 | -12              | 3/4         | .139  | .984  | 1   |
| 56282 | 711510-4 | -16              | 1           | .139  | 1.296 | 1   |
| 56284 | 711510-3 | -20              | 1-1/4       | .139  | 1.484 | 1   |
| 56286 | 711510-2 | -24              | 1-1/2       | .139  | 1.859 | 1   |
| 56288 | 711510-1 | -32              | 2           | .139  | 2.234 | 1   |



**O-RING**

\* Numbers with a "^" are not necessarily stocked in large quantities


# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B #   | PARKER #    | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-------------|-----------|-----------------|-----|
| ^ 54234 | 1FU43-4-4   | 1/4       | 1/4-19          | 1   |
| ^ 54236 | 1FU43-6-6   | 3/8       | 3/8-19          | 1   |
| ^ 54237 | 1FU43-8-8   | 1/2       | 1/2-14          | 1   |
| ^ 54238 | 1FU43-12-12 | 3/4       | 3/4-14          | 1   |

### JIS/BSP 30 FLARE SWIVEL FEMALE


1FU43



| J&B #   | PARKER #  | HOSE SIZE | TUBE |         | QTY |
|---------|-----------|-----------|------|---------|-----|
|         |           |           | SIZE | THREAD  |     |
| ^ 55120 | 1MU43-4-4 | 1/4       | 1/4  | M14-1.5 | 1   |
| ^ 55122 | 1MU43-6-6 | 3/8       | 3/8  | M18-1.5 | 1   |
| ^ 55124 | 1MU43-8-8 | 1/2       | 1/2  | M22-1.5 | 1   |

### JIS METRIC 30 FLARE SWIVEL FEMALE


1MU43



| J&B #   | PARKER #    | HOSE SIZE | TUBE |         | QTY |
|---------|-------------|-----------|------|---------|-----|
|         |             |           | SIZE | THREAD  |     |
| ^ 55126 | 1XU43-10-10 | 5/8       | 5/8  | M24-1.5 | 1   |

### JIS METRIC 30 FLARE SWIVEL FEMALE


1XU43



| J&B #   | PARKER #  | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-----------|-----------|-----------------|-----|
| ^ 55110 | 1GU43-4-4 | 1/4       | 1/4-19          | 1   |
| ^ 55114 | 1GU43-6-6 | 3/8       | 3/8-19          | 1   |
| ^ 55116 | 1GU43-8-8 | 1/2       | 1/2-14          | 1   |

### JIS/BSP 60 CONE SWIVEL FEMALE


1GU43



| J&B #   | PARKER #  | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-----------|-----------|-----------------|-----|
| ^ 55130 | 1UT43-4-4 | 1/4       | 1/4-19          | 1   |
| ^ 55132 | 1UT43-6-6 | 3/8       | 3/8-19          | 1   |
| ^ 55134 | 1UT43-8-8 | 1/2       | 1/2-14          | 1   |

### MALE JIS/BSP TAPER 60 CONE

1UT43



\* Numbers with a "^" are not necessarily stocked in large quantities


# PARKRIMP HOSE FITTINGS

## 43 SERIES


| J&B #   | PARKER #    | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-------------|-----------|-----------------|-----|
| ^ 55030 | 19243-4-4   | 1/4       | 1/4-19          | 1   |
| ^ 55032 | 19243-6-6   | 3/8       | 3/8-19          | 1   |
| ^ 55034 | 19243-8-8   | 1/2       | 1/2-14          | 1   |
| ^ 55036 | 19243-12-12 | 3/4       | 3/4-14          | 1   |
| ^ 55038 | 19243-16-16 | 1         | 1-11            | 1   |

**BSP SWIVEL  
FEMALE  
BALL NOSE**

**19243**




| J&B #   | PARKER #    | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-------------|-----------|-----------------|-----|
| ^ 55060 | 1B243-4-4   | 1/4       | 1/4-19          | 1   |
| ^ 55062 | 1B243-6-6   | 3/8       | 3/8-19          | 1   |
| ^ 55064 | 1B243-8-8   | 1/2       | 1/2-14          | 1   |
| ^ 55066 | 1B243-12-12 | 3/4       | 3/4-14          | 1   |



**BSP SWIVEL  
FEMALE 90 ELBOW  
BALLNOSE**

**1B243**

| J&B #   | PARKER #  | HOSE SIZE | BSP PIPE THREAD | QTY |
|---------|-----------|-----------|-----------------|-----|
| ^ 55044 | 1B143-4-4 | 1/4       | 1/4-19          | 1   |
| ^ 55046 | 1B143-6-6 | 3/8       | 3/8-19          | 1   |
| ^ 55048 | 1B143-8-8 | 1/2       | 1/2-14          | 1   |



**BSP SWIVEL  
FEMALE 45 ELBOW  
BALLNOSE**

**1B143**


# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-------------|--------------|------|---------|-----|
|       |             |              | SIZE | THREAD  |     |
| 55070 | 1C343-6-4   | 1/4          | 6mm  | M12-1.5 | 1   |
| 55072 | 1C343-8-4   | 1/4          | 8mm  | M14-1.5 | 1   |
| 55074 | 1C343-10-6  | 3/8          | 10mm | M16-1.5 | 1   |
| 55076 | 1C343-12-6  | 3/8          | 12mm | M18-1.5 | 1   |
| 55078 | 1C343-15-8  | 1/2          | 15mm | M22-1.5 | 1   |
| 55080 | 1C343-18-10 | 5/8          | 18mm | M26-1.5 | 1   |
| 55082 | 1C343-22-12 | 3/4          | 22mm | M30-2.0 | 1   |

**METRIC SWIVEL  
FEMALE BALL NOSE  
LIGHT SERIES**


**1C343**



| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-------------|--------------|------|---------|-----|
|       |             |              | SIZE | THREAD  |     |
| 55088 | 1C543-8-4   | 1/4          | 8mm  | M14-1.5 | 1   |
| 55090 | 1C543-10-6  | 3/8          | 10mm | M16-1.5 | 1   |
| 55092 | 1C543-12-6  | 3/8          | 12mm | M18-1.5 | 1   |
| 55094 | 1C543-15-8  | 1/2          | 15mm | M22-1.5 | 1   |
| 55095 | 1C543-18-10 | 5/8          | 18mm | M26-1.5 | 1   |
| 55096 | 1C543-22-12 | 3/4          | 22mm | M30-2.0 | 1   |

**METRIC SWIVEL  
FEMALE BALL NOSE  
LIGHT SERIES  
90 ELBOW**

**1C543**






# PARKRIMP HOSE FITTINGS

## 43 SERIES

| J&B # | PARKER #   | HOSE<br>SIZE | TUBE |         | QTY |
|-------|------------|--------------|------|---------|-----|
|       |            |              | SIZE | THREAD  |     |
| 55100 | 1C943-8-4  | 1/4          | 8mm  | M16-1.5 | 1   |
| 55102 | 1C943-10-4 | 1/4          | 10mm | M18-1.5 | 1   |
| 55104 | 1C943-12-6 | 3/8          | 12mm | M20-1.5 | 1   |
| 55106 | 1C943-14-6 | 3/8          | 14mm | M22-1.5 | 1   |
| 55107 | 1C943-16-8 | 1/2          | 16mm | M24-1.5 | 1   |

**METRIC SWIVEL  
FEMALE 24° CONE  
HEAVY SERIES  
WITH O-RING**


**1C943**



| J&B # | PARKER #   | HOSE<br>SIZE | TUBE |         | QTY |
|-------|------------|--------------|------|---------|-----|
|       |            |              | SIZE | THREAD  |     |
| 55410 | 1D243-12-6 | 3/8          | 12mm | M20-1.5 | 1   |

**METRIC RIGID  
MALE 24° CONE  
HEAVY SERIES  
WITH O-RING**


**1D243**



| J&B # | PARKER #   | HOSE<br>SIZE | TUBE |         | QTY |
|-------|------------|--------------|------|---------|-----|
|       |            |              | SIZE | THREAD  |     |
| 55438 | 1CA43-8-4  | 1/4          | 8mm  | M14-1.5 | 1   |
| 55440 | 1CA43-10-4 | 1/4          | 10mm | M16-1.5 | 1   |
| 55442 | 1CA43-12-6 | 3/8          | 12mm | M18-1.5 | 1   |


**METRIC SWIVEL  
FEMALE 24° CONE  
LIGHT SERIES  
WITH O-RING**

**1CA43**



| J&B # | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 55446 | 1CF43-8-4 | 1/4          | 8mm  | M14-1.5 | 1   |

**METRIC SWIVEL  
90° ELBOW  
FEMALE 24° CONE  
LIGHT SERIES  
WITH O-RING**  
**1CF43**



# PARKRIMP HOSE FITTINGS

## 43 SERIES "FERRUL-FIX"

**Fast, On-The-Job Repair For Ruptured Bent Tube Hose Assemblies And Power Steering Lines**

### Problem . . .

The life of the combination tube-hose assembly is often limited to the service life of the hose alone. A replacement assembly may not be available, since equipment dealers are unable to stock all of the many odd tube configurations.

### Solution . . .

Parker FERRUL-FIX, a field attachable, reusable hose end fitting, now makes it possible to salvage the bent tube section of the original assembly for replacement. Most important, it gets you back into operation FAST!

**GETS YOU BACK IN OPERATION FAST** - No costly delays while replacement assemblies are rushed from the factory.

**LETS YOU REUSE EXPENSIVE BENT TUBE ENDS** - You can replace the hose at a fraction of the cost of complete assembly.

**ELIMINATES NEED FOR EMERGENCY BRAZING OR WELDING IN THE FIELD** - Ferrul-Fix can be assembled without special tools or equipment.


### Result . . .

### Features . . .

**3-Piece Design** - body, nut, ferrule. Wedging action of ferrule, when drawn down by nut, forms seal between body and ferrule, while cutting edge of ferrule "bites" into tube wall forming another positive seal.

**Visible Bite** - Extent of bite at cutting edge of ferrule is completely visible when fitting is dis-assembled; an important safety feature. Self-centering action assures even bite around circumference of tube.


**Parkerize Finish** - Ferrul-Lok fittings have the Parkerize black finish, providing "built-in" lubrication which reduces wrench torque in make-up.



| J&B #   | PARKER #    | HOSE<br>I.D. | TUBE |           | QTY |
|---------|-------------|--------------|------|-----------|-----|
|         |             |              | SIZE | THREAD    |     |
| ^ 52745 | 11143-4-4   | 1/4          | 1/4  | 7/16-20   | 1   |
| ^ 52840 | 11143-5-4   | 1/4          | 5/16 | 1/2-20    | 1   |
| ^ 52842 | 11143-4-6   | 3/8          | 1/4  | 7/16-20   | 1   |
| ^ 52844 | 11143-5-6   | 3/8          | 5/16 | 1/2-20    | 1   |
| 52746   | 11143-6-6   | 3/8          | 3/8  | 9/16-18   | 1   |
| 52748   | 11143-8-8   | 1/2          | 1/2  | 3/4-16    | 1   |
| 52750   | 11143-10-8  | 1/2          | 5/8  | 7/8-14    | 1   |
| 52752   | 11143-12-12 | 3/4          | 3/4  | 1-1/16-12 | 1   |
| ^ 52789 | 11143-16-16 | 1            | 1    | 1-5/16-12 | 1   |

(SAE Flareless)  
"Ferrul-Fix"

**11143**



\* Numbers with a "^^" are not necessarily stocked in large quantities

### FERRUL-FIX INSTALLATION INSTRUCTIONS:


1. Cut the formed tube off squarely next to the permanent hose fitting. Lightly deburr the end of the tube internally and externally.
2. Disassemble the Ferrul-Fix fitting, and lubricate threads and both ends of the ferrule with an extreme pressure lubricant. Slide nut and ferrule onto tubing, with the long, straight end of the ferrule pointing toward the tube end.
3. Insert tube end into the Ferrul-Fix body until it bottoms against the shoulder. Slide ferrule inside body, and screw nut down finger tight.
4. Tighten nut with a wrench until tube no longer can be rotated easily. From this point, tighten nut one more complete turn. Disconnect nut and inspect lead edge of ferrule to make certain that the biting edge has turned up a shoulder completely around the tube.
5. Assemble Ferrul-Fix fitting to hose. Refer to assembly instructions listed in appropriate fittings section.
6. Reassemble tubing into Ferrul-Fix end and turn nut finger tight. Turn bent tube to proper position if required. Using two wrenches, one on the fitting nipple hex and the other on the nut, tighten nut from 1/6 to 1/3 turn.

# PARKRIMP HOSE FITTINGS

## \*\*\*STAINLESS STEEL\*\*\* 43 SERIES

| J&B #    | PARKER #     | HOSE<br>I. D. | TUBE  |           | QTY |
|----------|--------------|---------------|-------|-----------|-----|
|          |              |               | SIZE  | THREAD    |     |
| * V53080 | 10643-4-4C   | 1/4           | 1/4   | 7/16-20   | 1   |
| V53081   | 10643-6-6C   | 3/8           | 3/8   | 9/16-18   | 1   |
| * V53082 | 10643-8-8C   | 1/2           | 1/2   | 3/4-16    | 1   |
| V53084   | 10643-12-12C | 3/4           | 3/4   | 1-1/16-12 | 1   |
| * V53085 | 10643-16-16C | 1             | 1     | 1-5/16-12 | 1   |
| * V53086 | 10643-20-20C | 1-1/4         | 1-1/4 | 1-5/8-12  | 1   |

### JIC 37° SWIVEL 10643



- \* Note: The 10643 couplings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations, except in sizes - 6 (3/8") and - 12 (3/4")

# PARFLEX HOSE FITTINGS

## 55 SERIES


55 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

558H or 518C (SAE100R7) NON-CONDUCTIVE MEDIUM PRESSURE HOSE -  
Page 734

| J&B #   | PARKER #  | HOSE I.<br>D. | PIPE THREAD | QTY |
|---------|-----------|---------------|-------------|-----|
| ^ 54018 | 10155-2-4 | 1/4           | 1/8         | 1   |
| 54020   | 10155-4-4 | 1/4           | 1/4         | 1   |
| ^ 54021 | 10155-4-5 | 5/16          | 1/4         | 1   |
| ^ 54022 | 10155-4-6 | 3/8           | 1/4         | 1   |
| ^ 54023 | 10155-6-5 | 5/16          | 3/8         | 1   |
| 54025   | 10155-6-6 | 3/8           | 3/8         | 1   |
| 54028   | 10155-6-8 | 1/2           | 3/8         | 1   |
| 54029   | 10155-8-8 | 1/2           | 1/2         | 1   |

### MALE PIPE


10155



| J&B #      | PARKER #    | HOSE<br>I. D. | TUBE |         | QTY |
|------------|-------------|---------------|------|---------|-----|
|            |             |               | SIZE | THREAD  |     |
| ** ^ 54038 | **10657-4-2 | 1/8           | 1/4  | 7/16-20 | 1   |
| 54039      | 10655-4-3   | 3/16          | 1/4  | 7/16-20 | 1   |
| 54040      | 10655-4-4   | 1/4           | 1/4  | 7/16-20 | 1   |
| 54042      | 10655-6-4   | 1/4           | 3/8  | 9/16-18 | 1   |
| 54043      | 10655-5-5   | 5/16          | 5/16 | 1/2-20  | 1   |
| 54044      | 10655-6-5   | 5/16          | 3/8  | 9/16-18 | 1   |
| 54045      | 10655-6-6   | 3/8           | 3/8  | 9/16-18 | 1   |
| 54046      | 10655-8-6   | 3/8           | 1/2  | 3/4-16  | 1   |
| 54047      | 10655-8-8   | 1/2           | 1/2  | 3/4-16  | 1   |
| 54048      | 10655-10-8  | 1/2           | 5/8  | 7/8-14  | 1   |

### JIC 37° SWIVEL

10655




\*\* 57 Series fittings for use on 518C hose only.

| J&B #   | PARKER #  | HOSE<br>I. D. | TUBE |         | QTY |
|---------|-----------|---------------|------|---------|-----|
|         |           |               | SIZE | THREAD  |     |
| ^ 54059 | 10355-4-3 | 3/16          | 1/4  | 7/16-20 | 1   |
| ^ 54060 | 10355-4-4 | 1/4           | 1/4  | 7/16-20 | 1   |
| ^ 54062 | 10355-5-5 | 5/16          | 5/16 | 1/2-20  | 1   |
| 54063   | 10355-6-4 | 1/4           | 3/8  | 9/16-18 | 1   |
| ^ 54064 | 10355-6-5 | 5/16          | 3/8  | 9/16-18 | 1   |
| 54066   | 10355-6-6 | 3/8           | 3/8  | 9/16-18 | 1   |
| 54067   | 10355-8-6 | 3/8           | 1/2  | 3/4-16  | 1   |
| 54068   | 10355-8-8 | 1/2           | 1/2  | 3/4-16  | 1   |

### MALE JIC 37°

10355



\* Numbers with a "A" are not necessarily stocked in large quantities


# PARFLEX HOSE FITTINGS

## 55 SERIES

| J&B #   | PARKER #  | HOSE<br>I. D. | TUBE |         | QTY |
|---------|-----------|---------------|------|---------|-----|
|         |           |               | SIZE | THREAD  |     |
| ^ 56508 | 13755-4-4 | 1/4           | 1/4  | 7/16-20 | 1   |
| ^ 56704 | 13755-6-5 | 5/16          | 3/8  | 9/16-18 | 1   |
| ^ 56705 | 13755-6-6 | 3/8           | 3/8  | 9/16-18 | 1   |

**JIC 37° SWIVEL 45°  
ELBOW**


**13755**



| J&B #    | PARKER #  | HOSE<br>I. D. | TUBE |         | QTY |
|----------|-----------|---------------|------|---------|-----|
|          |           |               | SIZE | THREAD  |     |
| *^ 56600 | 14155-6-5 | 5/16          | 3/8  | 9/16-18 | 1   |

**(JIC) 37° SWIVEL  
90° LONG ELBOW**


**14155**



| J&B #    | PARKER #  | HOSE<br>I. D. | TUBE |         | QTY |
|----------|-----------|---------------|------|---------|-----|
|          |           |               | SIZE | THREAD  |     |
| ^ 56494  | 13955-4-3 | 3/16          | 1/4  | 7/16-20 | 1   |
| ^ 56495  | 13955-4-4 | 1/4           | 1/4  | 7/16-20 | 1   |
| *^ 56497 | 13955-6-4 | 1/4           | 3/8  | 9/16-18 | 1   |
| *^ 56500 | 13955-6-6 | 3/8           | 3/8  | 9/16-18 | 1   |
| ^ 56498  | 13955-8-6 | 3/8           | 1/2  | 3/4-16  | 1   |
| ^ 56501  | 13955-8-8 | 1/2           | 1/2  | 3/4-16  | 1   |


**FEMALE SAE (JIC) 37°  
SWIVEL 90° ELBOW**

**13955**



| J&B #    | PARKER #  | HOSE<br>I. D. | TUBE |         | QTY |
|----------|-----------|---------------|------|---------|-----|
|          |           |               | SIZE | THREAD  |     |
| ^ 56502  | 1L955-4-4 | 1/4           | 1/4  | 7/16-20 | 1   |
| *^ 56504 | 1L955-6-5 | 5/16          | 3/8  | 9/16-18 | 1   |

**SAE (JIC) 37° SWIVEL  
90° ELBOW SPECIAL**



“^” Numbers are not necessarily stocked in large quantities

\* JIC only (not SAE)


# PARFLEX HOSE FITTINGS

---

## 55 SERIES

| J&B # | PARKER #  | HOSE<br>I. D. | SEAL LOK |          | QTY |
|-------|-----------|---------------|----------|----------|-----|
|       |           |               | SIZE     | THREAD   |     |
| 54074 | 1JC55-6-6 | 3/8           | 3/8      | 11/16-16 | 1   |

**FEMALE  
"SEAL LOK"  
SWIVEL STRAIGHT  
1JC55**



# PARKRIMP HOSE FITTINGS

## 71 SERIES

71 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSES . . . .

772TC (SAE 100R12)


HIGH PRESSURE HOSE -

Page 733B

| J&B # | PARKER #    | HOSE<br>I. D. | TUBE  |           | QTY |
|-------|-------------|---------------|-------|-----------|-----|
|       |             |               | SIZE  | THREAD    |     |
| 55184 | 10671-12-12 | 3/4           | 3/4   | 1-1/16-12 | 1   |
| 55186 | 10671-16-12 | 3/4           | 1     | 1-5/16-12 | 1   |
| 55188 | 10671-16-16 | 1             | 1     | 1-5/16-12 | 1   |
| 55190 | 10671-20-20 | 1-1/4         | 1-1/4 | 1-5/8-12  | 1   |
| 55192 | 10671-24-20 | 1-1/4         | 1-1/2 | 1-7/8-12  | 1   |
| 55194 | 10671-24-24 | 1-1/2         | 1-1/2 | 1-7/8-12  | 1   |
| 55196 | 10671-32-32 | 2             | 2     | 2-1/2-12  | 1   |

JIC 37° SWIVEL


10671



| J&B # | PARKER #    | HOSE<br>I.D. | PIPE<br>THREAD | QTY |
|-------|-------------|--------------|----------------|-----|
| 55170 | 10171-12-12 | 3/4          | 3/4            | 1   |
| 55172 | 10171-16-16 | 1            | 1              | 1   |
| 55174 | 10171-20-20 | 1-1/4        | 1-1/4          | 1   |
| 55176 | 10171-24-24 | 1-1/2        | 1-1/2          | 1   |
| 55178 | 10171-32-32 | 2            | 2              | 1   |

MALE PIPE NPTF

10171




# PARKRIMP HOSE FITTINGS

## 71 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55200 | 11571-12-12 | 3/4       | 3/4         | 1-1/2       | .265"         | 1   |
| 55202 | 11571-16-12 | 3/4       | 1           | 1-3/4       | .315"         | 1   |
| 55204 | 11571-16-16 | 1         | 1           | 1-3/4       | .315"         | 1   |
| 55206 | 11571-20-16 | 1         | 1-1/4       | 2           | .315"         | 1   |
| 55208 | 11571-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55210 | 11571-24-20 | 1-1/4     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55212 | 11571-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55214 | 11571-32-32 | 2         | 2           | 2-13/16     | .375"         | 1   |

SAE (Code 61)  
FLANGE STRAIGHT

**11571**




O-rings not included

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55236 | 11971-12-12 | 3/4       | 3/4         | 1-1/2       | .265"         | 1   |
| 55238 | 11971-16-16 | 1         | 1           | 1-3/4       | .315"         | 1   |
| 55240 | 11971-20-16 | 1         | 1-1/4       | 2           | .315"         | 1   |
| 55242 | 11971-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55244 | 11971-24-20 | 1-1/4     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55246 | 11971-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55248 | 11971-32-32 | 2         | 2           | 2-13/16     | .375"         | 1   |

SAE (Code 61)  
FLANGE 90° ELB.

**11971**




O-rings not included

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55218 | 11771-12-12 | 3/4       | 3/4         | 1-1/2       | .265"         | 1   |
| 55220 | 11771-16-12 | 3/4       | 1           | 1-3/4       | .315"         | 1   |
| 55222 | 11771-16-16 | 1         | 1           | 1-3/4       | .315"         | 1   |
| 55224 | 11771-20-16 | 1         | 1-1/4       | 2           | .315"         | 1   |
| 55226 | 11771-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55228 | 11771-24-20 | 1-1/4     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55230 | 11771-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |
| 55232 | 11771-32-32 | 2         | 2           | 2-13/16     | .375"         | 1   |

SAE (Code 61)  
FLANGE 45° ELB.

**11771**



O-rings not included



# PARKRIMP HOSE FITTINGS


## 71 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55254 | 16A71-12-12 | 3/4       | 3/4         | 1-5/8       | .345"         | 1   |
| 55256 | 16A71-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55258 | 16A71-20-16 | 1         | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55260 | 16A71-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55262 | 16A71-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55264 | 16A71-32-32 | 2         | 2           | 3-1/8       | .495"         | 1   |

O-rings not included

SAE (Code 62)  
FLANGE STRAIGHT

16A71




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55270 | 16F71-12-12 | 3/4       | 3/4         | 1-5/8       | .345"         | 1   |
| 55272 | 16F71-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55274 | 16F71-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55276 | 16F71-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55278 | 16F71-32-32 | 2         | 2           | 3-1/8       | .495"         | 1   |

O-rings not included

SAE (Code 62)  
FLANGE 45° ELB.

16F71




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55280 | 16N71-12-12 | 3/4       | 3/4         | 1-5/8       | .345"         | 1   |
| 55282 | 16N71-16-12 | 3/4       | 1           | 1-7/8       | .375"         | 1   |
| 55284 | 16N71-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55286 | 16N71-20-16 | 1         | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55288 | 16N71-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55290 | 16N71-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55292 | 16N71-32-32 | 2         | 2           | 3-1/8       | .495"         | 1   |

O-rings not included

SAE (Code 62)  
FLANGE 90° ELB.

16N71




# PARKRIMP HOSE FITTINGS

## 71 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55682 | 1JS71-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 55683 | 1JS71-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55684 | 1JS71-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

**FEMALE "SEAL LOK"  
SWIVEL STRAIGHT**


**1JS71**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55692 | 1J971-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 55693 | 1J971-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55694 | 1J971-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

**FEMALE "SEAL LOK"  
SWIVEL 90° ELBOW  
(SHORT)**


**1J971**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55687 | 1J771-12-12 | 3/4          | 3/4      | 1-3/16-12  | 1   |
| 55688 | 1J771-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55689 | 1J771-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |

**FEMALE "SEAL LOK"  
SWIVEL 45 ELBOW**

**1J771**



# PARKRIMP HOSE FITTINGS

## 78 SERIES

78 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSES . . . .


78C (SAE 100R13)

HIGH PRESSURE HOSE -

Page 733C


| J&B # | PARKER #    | HOSE<br>I. D. | TUBE  |           | QTY |
|-------|-------------|---------------|-------|-----------|-----|
|       |             |               | SIZE  | THREAD    |     |
| 55310 | 10678-16-16 | 1             | 1     | 1-1/16-12 | 1   |
| 55312 | 10678-20-20 | 1-1/4         | 1-1/4 | 1-5/8-12  | 1   |
| 55314 | 10678-24-24 | 1-1/2         | 1-1/2 | 1-7/8-12  | 1   |

**FEMALE JIC 37°  
SWIVEL  
10678**



| J&B # | PARKER #    | HOSE<br>I.D. | PIPE<br>THREAD | QTY |
|-------|-------------|--------------|----------------|-----|
| 55300 | 10178-16-16 | 1            | 1              | 1   |
| 55302 | 10178-20-20 | 1-1/4        | 1-1/4          | 1   |
| 55304 | 10178-24-24 | 1-1/2        | 1-1/2          | 1   |

**MALE PIPE NPTF  
10178**



# PARKRIMP HOSE FITTINGS


## 78 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55320 | 14A78-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55322 | 14A78-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |

SAE (Code 61)  
FLANGE STRAIGHT

14A78

O-rings not included




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55340 | 14N78-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55342 | 14N78-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |

SAE (Code 61)  
FLANGE 90° ELB.

14N78

O-rings not included




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55330 | 14F78-20-20 | 1-1/4     | 1-1/4       | 2           | .315"         | 1   |
| 55332 | 14F78-24-24 | 1-1/2     | 1-1/2       | 2-3/8       | .315"         | 1   |

SAE (Code 61)  
FLANGE 45° ELB.

14F78

O-rings not included




# PARKRIMP HOSE FITTINGS

## 78 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55350 | 16A78-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55352 | 16A78-20-16 | 1         | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55354 | 16A78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55356 | 16A78-24-20 | 1-1/4     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55358 | 16A78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |


SAE (Code 62)  
FLANGE STRAIGHT  
**16A78**



O-rings not included

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55380 | 16N78-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55382 | 16N78-20-16 | 1         | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55384 | 16N78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55386 | 16N78-24-20 | 1-1/4     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55388 | 16N78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |


SAE (Code 62)  
FLANGE 90° ELB.  
**16N78**



O-rings not included

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55365 | 16F78-16-16 | 1         | 1           | 1-7/8       | .375"         | 1   |
| 55367 | 16F78-20-16 | 1         | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55369 | 16F78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .405"         | 1   |
| 55371 | 16F78-24-20 | 1-1/4     | 1-1/2       | 2-1/2       | .495"         | 1   |
| 55373 | 16F78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .495"         | 1   |

SAE (Code 62)  
FLANGE 45° ELB.  
**16F78**



O-rings not included

# PARKRIMP HOSE FITTINGS


## 78 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55395 | 1XA78-16-16 | 1         | 1           | 1-7/8       | .560"         | 1   |
| 55397 | 1XA78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .560"         | 1   |
| 55399 | 1XA78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .560"         | 1   |

O-rings not included

**CATERPILLAR STYLE  
FLANGE STRAIGHT**

**1XA78**




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55415 | 1XN78-16-16 | 1         | 1           | 1-7/8       | .560"         | 1   |
| 55417 | 1XN78-20-16 | 1         | 1-1/4       | 2-1/8       | .560"         | 1   |
| 55419 | 1XN78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .560"         | 1   |
| 55421 | 1XN78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .560"         | 1   |

O-rings not included

**CATERPILLAR STYLE  
FLANGE 90° ELBOW**

**1XN78**




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55402 | 1XF78-16-16 | 1         | 1           | 1-7/8       | .560"         | 1   |
| 55403 | 1XF78-20-16 | 1         | 1-1/4       | 2-1/8       | .560"         | 1   |
| 55405 | 1XF78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .560"         | 1   |
| 55407 | 1XF78-24-24 | 1-1/2     | 1-1/2       | 2-1/2       | .560"         | 1   |

O-rings not included

**CATERPILLAR STYLE  
FLANGE 45° ELBOW**

**1XF78**



# PARKRIMP HOSE FITTINGS


## 78 SERIES

| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55434 | 1XE78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .560"         | 1   |

CATERPILLAR STYLE  
FLANGE 30° ELBOW

1XE78

O-rings not included




| J&B # | PARKER #    | HOSE SIZE | FLANGE SIZE | FLANGE O.D. | FLANGE HEIGHT | QTY |
|-------|-------------|-----------|-------------|-------------|---------------|-----|
| 55428 | 1XG78-20-20 | 1-1/4     | 1-1/4       | 2-1/8       | .560"         | 1   |

CATERPILLAR STYLE  
FLANGE 60° ELBOW


1XG78

O-rings not included



## FLANGE "D" RING CATERPILLAR STYLE FLANGES

| J&B # | FLANGE SIZE | PARKER # | DASH SIZE | I.D. | O.D. | QTY |
|-------|-------------|----------|-----------|------|------|-----|
| 55361 | 1           | XARG-16  | -16       | 0.20 | 1.25 | 1   |
| 55362 | 1-1/4       | XARG-20  | -20       | 0.20 | 1.50 | 1   |
| 55363 | 1-1/2       | XARG-24  | -24       | 0.20 | 1.75 | 1   |



O-RING


# PARKRIMP HOSE FITTINGS

## 78 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55697 | 1JS78-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55698 | 1JS78-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |
| 55699 | 1JS78-24-24 | 1-1/2        | 1-1/2    | 2-12       | 1   |

**FEMALE "SEAL LOK"  
SWIVEL STRAIGHT**


**1JS78**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55707 | 1J978-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55708 | 1J978-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |
| 55709 | 1J978-24-24 | 1-1/2        | 1-1/2    | 2-12       | 1   |

**FEMALE "SEAL LOK"  
SWIVEL 90° ELBOW  
(SHORT)**


**1J978**



| J&B # | PARKER #    | HOSE<br>SIZE | SEAL LOK |            | QTY |
|-------|-------------|--------------|----------|------------|-----|
|       |             |              | SIZE     | THREAD     |     |
| 55702 | 1J778-16-16 | 1            | 1        | 1-7/16-12  | 1   |
| 55703 | 1J778-20-20 | 1-1/4        | 1-1/4    | 1-11/16-12 | 1   |
| 55704 | 1J778-24-24 | 1-1/2        | 1-1/2    | 2-12       | 1   |

**FEMALE "SEAL LOK"  
SWIVEL 45 ELBOW**

**1J778**






# PARKRIMP HOSE FITTINGS

## 26 SERIES

### Male Tube O-Ring Swivel - Straight, Short Pilot


## 1S526



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
|             |           |                |                | 1S526-6-6   | 55600  |
|             |           |                |                | 1S526-8-8   | 55601  |
| 7/8x18      | 5/8       | -10            | 2.56           | 1S526-10-10 | 55602  |
| 7/8x18      | 5/8       | -12            | 2.57           | 1S526-10-12 | 55603  |

### Male Tube O-Ring Swivel - 45° Elbow, Short Pilot


## 15R26



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 2.12           | 15R26-6-6   | 55604  |
| 3/4x18      | 1/2       | -8             | 2.17           | 15R26-8-8   | 55605  |
| 7/8x18      | 5/8       | -10            | 2.64           | 15R26-10-10 | 55606  |
| 7/8x18      | 5/8       | -12            | 2.65           | 15R26-10-12 | 55607  |

### Male Tube O-Ring Swivel - 90° Elbow, Short Pilot

## 15K26




| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.     | J&B NO |
|-------------|-----------|----------------|----------------|--------------|--------|
| 5/8x18      | 3/8       | -6             | 1.35           | 15K26-6-6    | 55608  |
| 3/4x18      | 1/2       | -8             | 2.02           | 15K26-8-8    | 55609  |
| 7/8x18      | 5/8       | -10            | 1.70           | 15K26-10-10+ |        |
| 7/8x18      | 5/8       | -12            | 1.69           | 15K26-10-12  | 55610  |

-Non-standard.

### Male Tube O-Ring Swivel - 90° Elbow, Short Pilot with Charge Port for R12


## 15K26-PR



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 7/8x18      | 5/8       | -10            | 2.63           | 15K26-10-10-PR | 55611  |
| 7/8x18      | 5/8       | -12            | 2.64           | 15K26-10-12-PR | 55612  |

### Male Tube O-Ring Swivel - Straight, Long Pilot with Charge Port for R134a

## 14526-PT



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 7/8x18      | 5/8       | -12            | 2.54           | 14526-10-12-PT | 55613  |




# PARKRIMP HOSE FITTINGS

## 26 SERIES

**Male Tube O-Ring Swivel -  
90° Elbow, Long Pilot with  
Charge Port for R12**


**15M26-PR**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.     | J&B NO |
|-------------|-----------|----------------|----------------|--------------|--------|
| 5/8x18      | 3/8       | -6             | 2.19           | 15M26-6-6-PR | 55614  |

**Male Tube O-Ring Rigid -  
Straight, Internal Long Pilot**


**15G26**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 0.92           | 15G26-6-6   | 55616  |
| 7/8x14      | 5/8       | -10            | 1.25           | 15G26-10-10 | 55618  |
| 7/8x14      | 5/8       | -12            | 1.25           | 15G26-10-12 | 55619  |
|             |           |                |                | 15G26-8-8   | 55617  |

**Male Tube O-Ring Swivel -  
90° Elbow, Long Pilot with  
Charge Port for R134a**


**15M26-PT**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 7/8x18      | 5/8       | -12            | 2.64           | 15M26-10-12-PT | 55615  |

**Male Tube O-Ring Rigid -  
Straight, Internal Long Pilot**


**15G26-PR**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 7/8x14      | 5/8       | -12            | 2.88           | 15G26-10-12-PR | 55620  |

**Female Tube O-Ring Swivel -  
Straight, Short Pilot**

**15S26**




| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 1.73           | 15S26-6-6   | 55621  |
| 3/4x16      | 1/2       | -8             | 1.78           | 15S26-8-8   | 55622  |
| 7/8x14      | 5/8       | -10            | 1.85           | 15S26-10-10 | 55623  |
| 7/8x14      | 5/8       | -12            | 1.86           | 15S26-10-12 | 55624  |

# PARKRIMP HOSE FITTINGS

## 26 SERIES

**Female Tube O-Ring Swivel  
- 45° Elbow, Short Pilot**


**15H26**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 1.54           | 15H26-6-6   | 55625  |
| 3/4x16      | 1/2       | -8             | 1.68           | 15H26-8-8   | 55626  |
| 7/8x14      | 5/8       | -10            | 2.07           | 15H26-10-10 | 55627  |
| 7/8x14      | 5/8       | -12            | 2.08           | 15H26-10-12 | 55628  |

**Female Tube O-Ring Swivel  
- 90° Elbow, Short Pilot**


**15T26**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 1.35           | 15T26-6-6   | 55629  |
| 3/4x16      | 1/2       | -8             | 1.62           | 15T26-8-8   | 55630  |
| 7/8x14      | 5/8       | -10            | 1.94           | 15T26-10-10 | 55631  |
| 7/8x14      | 5/8       | -12            | 1.95           | 15T26-10-12 | 55632  |

**Female Tube O-Ring Swivel  
- Straight, Long Pilot with  
Charge Port for R134a**


**15926-PB & PT**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 5/8x18      | 3/8       | -6             | 2.40           | 15926-6-6-PB   | 55633  |
| 3/4x16      | 1/2       | -8             | 2.04           | 15926-8-8-PB   | 55634  |
| 7/8x14      | 5/8       | -12            | 2.54           | 15926-10-12-PT | 55635  |

**Female Tube O-Ring Swivel  
- 45° Elbow, Long Pilot with  
Charge Port for R134a**

**15N26-PB & PT**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 3/4x16      | 1/2       | -8             | 2.85           | 15N26-8-8-PB   | 55636  |
| 7/8x14      | 5/8       | -12            | 3.19           | 15N26-10-12-PT | 55637  |




# PARKRIMP HOSE FITTINGS

## 26 SERIES

**Female Tube O-Ring Swivel  
- 90° Elbow, Long Pilot with  
Charge Port for R12**


**15L26-PR**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 3/4x16      | 1/2       | -8             | 2.37           | 15L26-8-8-PR   | 55638  |
| 7/8x14      | 5/8       | -10            | 2.63           | 15L26-10-10-PR | 55639  |
| 7/8x14      | 5/8       | -12            | 2.64           | 15L26-10-12-PR | 55640  |

**Male Tube O-Ring Swivel -  
45° Elbow, Long Pilot with  
Charge Port for R134a**


**15P26-PT**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 7/8x18      | 5/8       | -12            | 3.09           | 15P26-10-12-PT | 55645  |

**Female Tube O-Ring Swivel  
- 90° Elbow, Long Pilot with  
Charge Port for R134a**


**15L26-PB & PT**



| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.       | J&B NO |
|-------------|-----------|----------------|----------------|----------------|--------|
| 5/8x18      | 3/8       | -6             | 2.19           | 15L26-6-6-PB   | 55641  |
| 3/4x16      | 1/2       | -8             | 2.37           | 15L26-8-8-PB   | 55642  |
| 7/8x14      | 5/8       | -10            | 2.63           | 15L26-10-10-PT | 55643  |
| 7/8x14      | 5/8       | -12            | 2.64           | 15L26-10-12-PT | 55644  |

**Male Refrigerant Tube  
Mender - Straight (with Nut  
and Ferrule)**

**1T126**




| Thread Size | Tube Size | Hose Dash Size | Cut-off Allow. | Part No.    | J&B NO |
|-------------|-----------|----------------|----------------|-------------|--------|
| 5/8x18      | 3/8       | -6             | 1.10           | 1T126-6-6   | 55646  |
| 3/4x16      | 1/2       | -8             | 1.21           | 1T126-8-8   | 55647  |
| 7/8x14      | 5/8       | -10            | 1.33           | 1T126-10-10 | 55648  |
| 7/8x14      | 5/8       | -12            | 1.33           | 1T126-10-12 | 55649  |
| 1-16x14     | 3/4       | -12            | 1.39           | 1T126-12-12 | 55650  |

### O-Rings

**For Tube O-Ring Air Conditioning  
and Refrigeration Fittings.  
(Compound N1173-70)\***

| Tube Size | I.D.      | Part No. | J&B NO |
|-----------|-----------|----------|--------|
| 3/8       | .301±.005 | 771513-1 | 55651  |
| 1/2       | .426±.005 | 771513-2 | 55652  |
| 5/8       | .551±.005 | 771513-4 | 55653  |
| 3/4       | .676±.005 | 771513-4 | 55654  |



\*For use with R12 or R134a and

lubricants.


# PARKRIMP HOSE FITTINGS

## 26 SERIES

| J&B # | PARKER #  | HOSE | TUBE |        | QTY |
|-------|-----------|------|------|--------|-----|
|       |           | SIZE | SIZE | THREAD |     |
| 55680 | 10826-6-6 | -6   | 3/8  | 5/8-18 | 1   |

**FEMALE SAE 45  
SWIVEL STRAIGHT**


**10826**



| J&B # | PARKER #    | HOSE | TUBE |        | QTY |
|-------|-------------|------|------|--------|-----|
|       |             | SIZE | SIZE | THREAD |     |
| 55669 | 16826-8-6   | -6   | 1/2  | 3/4-16 | 1   |
| 55670 | 16826-8-8   | -8   | 1/2  | 3/4-16 | 1   |
| 55671 | 16826-10-10 | -10  | 5/8  | 7/8-14 | 1   |

**FEMALE JIC 37/SAE  
45 SWIVEL –  
STRAIGHT  
(DUAL SEAT)**


**16826**



| J&B # | PARKER #  | HOSE | TUBE |         | QTY |
|-------|-----------|------|------|---------|-----|
|       |           | SIZE | SIZE | THREAD  |     |
| 55665 | 10626-6-6 | -6   | 3/8  | 9/16-18 | 1   |

**FEMALE JIC 37  
SWIVEL**


**10626**



| J&B # | PARKER #  | HOSE | PIPE   | QTY |
|-------|-----------|------|--------|-----|
|       |           | I.D. | THREAD |     |
| 55660 | 10126-4-6 | 3/8  | 1/4    | 1   |
| 55661 | 10126-6-6 | 3/8  | 3/8    | 1   |
| 55663 | 10126-8-8 | 1/2  | 1/2    | 1   |

**MALE NPTF PIPE -  
RIGID**

**10126**



# REUSABLE HOSE FITTINGS

## 20 SERIES

20 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSES . . . .

201 (SAE J1402 All)      MEDIUM PRESSURE HOSE -      Page    726


235 (SAE J51D)      LOW PRESSURE HOSE -      Page    722

SS25UL LPG      SERVICE HOSE -      Page    728

| J&B # | PARKER #    | HOSE SIZE | PIPE THREAD | QTY |
|-------|-------------|-----------|-------------|-----|
| 51000 | 20120-2-4   | -4        | 1/8         | 1   |
| 51002 | 20120-4-4   | -4        | 1/4         | 1   |
| 51003 | 20120-4-5   | -5        | 1/4         | 1   |
| 51004 | 20120-4-6   | -6        | 1/4         | 1   |
| 51006 | 20120-6-6   | -6        | 3/8         | 1   |
| 51008 | 20120-6-8   | -8        | 3/8         | 1   |
| 51010 | 20120-8-8   | -8        | 1/2         | 1   |
| 51012 | 20120-8-10  | -10       | 1/2         | 1   |
| 51014 | 20120-12-12 | -12       | 3/4         | 1   |
| 51016 | 20120-16-16 | -16       | 1           | 1   |

### MALE PIPE


#### 20120



| J&B # | PARKER #    | HOSE SIZE | TUBE |         | QTY |
|-------|-------------|-----------|------|---------|-----|
|       |             |           | SIZE | THREAD  |     |
| 51200 | 20420-4-4   | -4        | 1/4  | 7/16-20 | 1   |
| 51202 | 20420-6-6   | -6        | 3/8  | 5/8-18  | 1   |
| 51204 | 20420-8-8   | -8        | 1/2  | 3/4-16  | 1   |
| 51203 | 20420-10-10 | -10       | 5/8  | 7/8-14  | 1   |

### MALE SAE 45°

#### 20420



\*    Notch in hex for SAE 45° identification (for sizes -6 and -12 only.)

# REUSABLE HOSE FITTINGS


## 20 SERIES

| J&B #   | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|---------|-----------|--------------|------|---------|-----|
|         |           |              | SIZE | THREAD  |     |
| 51260   | 27920-4-4 | -4           | 1/4  | 7/16-20 | 1   |
| 51261   | 27920-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| * 51262 | 27920-6-6 | -6           | 3/8  | 5/8-18  | 1   |
| 51264   | 27920-8-8 | -8           | 1/2  | 3/4-16  | 1   |

\* SAE only. Will have notch on the nut. (for sizes -6 and -12 only.)

SAE 45°/ JIC 37°  
SWIVEL 90°  
ELBOW

**27920**




| J&B #   | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|---------|-----------|--------------|------|---------|-----|
|         |           |              | SIZE | THREAD  |     |
| 52574   | 23720-4-4 | -4           | 1/4  | 7/16-20 | 1   |
| 52576   | 23720-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| * 52578 | 27720-6-6 | -6           | 3/8  | 5/8-18  | 1   |
| 52580   | 23720-8-8 | -8           | 1/2  | 3/4-16  | 1   |

\* SAE only. Will have notch on the nut. (for sizes -6 and -12 only.)

SAE 45°/ JIC 37°  
SWIVEL 45°  
ELBOW

**27720**




| J&B #   | PARKER #    | HOSE<br>SIZE | TUBE |           | QTY |
|---------|-------------|--------------|------|-----------|-----|
|         |             |              | SIZE | THREAD    |     |
| 51206   | 20820-4-4   | -4           | 1/4  | 7/16-20   | 1   |
| 51205   | 20820-5-5   | -5           | 5/16 | 1/2-20    | 1   |
| * 51208 | 20820-6-6   | -6           | 3/8  | 5/8-18    | 1   |
| 51210   | 20820-8-8   | -8           | 1/2  | 3/4-16    | 1   |
| 51211   | 20620-10-8  | -8           | 5/8  | 7/8-14    | 1   |
| 51212   | 20820-10-10 | -10          | 5/8  | 7/8-14    | 1   |
| * 51214 | 20820-12-12 | -12          | 3/4  | 1-1/16-14 | 1   |

\* SAE only. Will have notch on the nut. (for sizes -6 and -12 only.)

SAE 45°/ JIC 37°  
SWIVEL

**20820**



# REUSABLE HOSE FITTINGS


## 20 SERIES

| J&B #   | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|---------|-----------|--------------|------|---------|-----|
|         |           |              | SIZE | THREAD  |     |
| 51260   | 23920-4-4 | -4           | 1/4  | 7/16-20 | 1   |
| 51261   | 23920-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| * 51263 | 23920-6-6 | -6           | 3/8  | 9/16-18 | 1   |
| 51264   | 23920-8-8 | -8           | 1/2  | 3/4-16  | 1   |

\* JIC 37 only / not SAE 45

SAE 45°/ JIC 37°  
90° ELBOW

23920




| J&B #   | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|---------|-----------|--------------|------|---------|-----|
|         |           |              | SIZE | THREAD  |     |
| 52574   | 23720-4-4 | -4           | 1/4  | 7/16-20 | 1   |
| 52576   | 23720-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| * 52572 | 23720-6-6 | -6           | 3/8  | 9/16-18 | 1   |
| 52580   | 23720-8-8 | -8           | 1/2  | 3/4-16  | 1   |

\* JIC 37 only / not SAE 45

SAE 45°/ JIC 37°  
45° ELBOW


23720



| J&B # | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 52806 | 20320-6-6 | -6           | 3/8  | 9/16-18 | 1   |

MALE  
(JIC) 37° RIGID

20320




| J&B #   | PARKER #    | HOSE<br>SIZE | TUBE  |           | QTY |
|---------|-------------|--------------|-------|-----------|-----|
|         |             |              | SIZE  | THREAD    |     |
| 51206   | 20620-4-4   | -4           | 1/4   | 7/16-20   | 1   |
| 51205   | 20620-5-5   | -5           | 5/16  | 1/2-20    | 1   |
| * 52807 | 20620-6-6   | -6           | 3/8   | 9/16-18   | 1   |
| 51210   | 20620-8-8   | -8           | 1/2   | 3/4-16    | 1   |
| 51211   | 20620-10-8  | -8           | 5/8   | 7/8-14    | 1   |
| 51212   | 20620-10-10 | -10          | 5/8   | 7/8-14    | 1   |
| * 52808 | 20620-12-12 | -12          | 3/4   | 1-1/16-12 | 1   |
| * 51216 | 20620-16-16 | -16          | 1     | 1-5/16-12 | 1   |
| * 51218 | 20620-20-20 | -20          | 1-1/4 | 1-5/8-12  | 1   |

\* JIC 37 only / not SAE 45

FEMALE  
SAE 45°/ JIC 37°  
SWIVEL

20620






# REUSABLE HOSE FITTINGS

## 20 SERIES

| J&B # | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 51230 | 22820-4-4 | -4           | 1/4  | 7/16-24 | 1   |
| 51231 | 22820-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| 51232 | 22820-6-6 | -6           | 3/8  | 5/8-18  | 1   |
| 51234 | 22820-8-8 | -8           | 1/2  | 3/4-18  | 1   |

### SAE MALE INVERTED SWIVEL


22820



| J&B # | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 51240 | 26720-4-4 | -4           | 1/4  | 7/16-24 | 1   |
| 51242 | 26720-6-6 | -6           | 3/8  | 5/8-18  | 1   |
| 51244 | 26720-8-8 | -8           | 1/2  | 3/4-18  | 1   |

### SAE MALE INVERTED SWIVEL 45° ELBOW


26720



| J&B # | PARKER #  | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 51250 | 26920-4-4 | -4           | 1/4  | 7/16-24 | 1   |
| 51251 | 26920-5-5 | -5           | 5/16 | 1/2-20  | 1   |
| 51252 | 26920-6-6 | -6           | 3/8  | 5/8-18  | 1   |

### SAE MALE INVERTED SWIVEL 90° ELBOW

26920



# REUSABLE HOSE FITTINGS

## 20 SERIES "FERRUL-FIX"

**Fast, On-The-Job Repair For Ruptured Bent Tube Hose Assemblies And Power Steering Lines**

### Problem . . .

The life of the combination tube-hose assembly is often limited to the service life of the hose alone. A replacement assembly may not be available, since equipment dealers are unable to stock all of the many odd tube configurations.

### Solution . . .

Parker FERRUL-FIX, a field attachable, reusable hose end fitting, now makes it possible to salvage the bent tube section of the original assembly for replacement. Most important, it gets you back into operation FAST!

**GETS YOU BACK IN OPERATION FAST** - No costly delays while replacement assemblies are rushed from the factory.

**LETS YOU REUSE EXPENSIVE BENT TUBE ENDS** - You can replace the hose at a fraction of the cost of complete assembly.

**ELIMINATES NEED FOR EMERGENCY BRAZING OR WELDING IN THE FIELD** - Ferrul-Fix can be assembled without special tools or equipment.


### Result . . .

### Features . . .

**3-Piece Design** - body, nut, ferrule. Wedging action of ferrule, when drawn down by nut, forms seal between body and ferrule, while cutting edge of ferrule "bites" into tube wall forming another positive seal.

**Visible Bite** - Extent of bite at cutting edge of ferrule is completely visible when fitting is dis-assembled; an important safety feature. Self-centering action assures even bite around circumference of tube.


**Parkerize Finish** - Ferrul-Lok fittings have the Parkerize black finish, providing "built-in" lubrication which reduces wrench torque in make-up.



| J&B # | PARKER #  | HOSE<br>I.D. | TUBE |         | QTY |
|-------|-----------|--------------|------|---------|-----|
|       |           |              | SIZE | THREAD  |     |
| 52550 | 21120-6-6 | 3/8          | 3/8  | 9/16-18 | 1   |
| 52552 | 21120-8-8 | 1/2          | 1/2  | 3/4-16  | 1   |

(SAE Flareless)  
"Ferrul-Fix"

**21120**



### FERRUL-FIX INSTALLATION INSTRUCTIONS:

1. Cut the formed tube off squarely next to the permanent hose fitting. Lightly deburr the end of the tube internally and externally.
2. Disassemble the Ferrul-Fix fitting, and lubricate threads and both ends of the ferrule with an extreme pressure lubricant. Slide nut and ferrule onto tubing, with the long, straight end of the ferrule pointing toward the tube end.
3. Insert tube end into the Ferrul-Fix body until it bottoms against the shoulder. Slide ferrule inside body, and screw nut down finger tight.
4. Tighten nut with a wrench until tube no longer can be rotated easily. From this point, tighten nut one more complete turn. Disconnect nut and inspect lead edge of ferrule to make certain that the biting edge has turned up a shoulder completely around the tube.
5. Assemble Ferrul-Fix fitting to hose. Refer to assembly instructions listed in appropriate fittings section.
6. Reassemble tubing into Ferrul-Fix end and turn nut finger tight. Turn bent tube to proper position if required. Using two wrenches, one on the fitting nipple hex and the other on the nut, tighten nut from 1/6 to 1/3 turn.

# REUSABLE HOSE FITTINGS

## 30 SERIES

30 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

302 (SAE 100R2 AT)


HIGH PRESSURE HOSE -

Page 730

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |           | QTY |
|-------|-------------|--------------|------|-----------|-----|
|       |             |              | SIZE | THREAD    |     |
| 52400 | 20630-4-4   | 1/4          | 1/4  | 7/16-20   | 1   |
| 52402 | 20630-6-4   | 1/4          | 3/8  | 9/16-18   | 1   |
| 52404 | 20630-6-6   | 3/8          | 3/8  | 9/16-18   | 1   |
| 52406 | 20630-8-6   | 3/8          | 1/2  | 3/4-16    | 1   |
| 52408 | 20630-8-8   | 1/2          | 1/2  | 3/4-16    | 1   |
| 52410 | 20630-10-8  | 1/2          | 5/8  | 7/8-14    | 1   |
| 52411 | 20630-10-12 | 3/4          | 5/8  | 7/8-14    | 1   |
| 52412 | 20630-12-12 | 3/4          | 3/4  | 1-1/16-12 | 1   |
| 52413 | 20630-12-8  | 1/2          | 3/4  | 1-1/16-12 | 1   |
| 52416 | 20630-16-16 | 1            | 1    | 1-5/16-12 | 1   |

SAE (JIC) 37°  
SWIVEL


20630



| J&B # | PARKER #    | HOSE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|-------------|--------------|----------------|-----|
| 52424 | 20130-4-4   | 1/4          | 1/4            | 1   |
| 52426 | 20130-6-6   | 3/8          | 3/8            | 1   |
| 52427 | 20130-6-8   | 1/2          | 3/8            | 1   |
| 52428 | 20130-8-6   | 3/8          | 1/2            | 1   |
| 52430 | 20130-8-8   | 1/2          | 1/2            | 1   |
| 52434 | 20130-12-8  | 1/2          | 3/4            | 1   |
| 52438 | 20130-12-12 | 3/4          | 3/4            | 1   |
| 52440 | 20130-12-16 | 1            | 3/4            | 1   |
| 52442 | 20130-16-16 | 1            | 1              | 1   |

MALE PIPE NPTF

20130



# REUSABLE HOSE FITTINGS


---

## 30 SERIES

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |           | QTY |
|-------|-------------|--------------|------|-----------|-----|
|       |             |              | SIZE | THREAD    |     |
| 52450 | 20330-8-8   | 1/2          | 1/2  | 3/4-16    | 1   |
| 52460 | 20330-12-12 | 3/4          | 3/4  | 1-1/16-12 | 1   |

MALE SAE  
(JIC) 37°

20330



# REUSABLE HOSE FITTINGS

## 88 SERIES

88 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

881 (SAE 100R4) VACUUM OR LOW PRESSURE HOSE -


Page 720

---

| J&B #   | PARKER #   | HOSE SIZE | PIPE THREAD   | QTY |
|---------|------------|-----------|---------------|-----|
| 54350   | 0188-12-12 | 3/4       | 3/4-14        | 1   |
| 54352   | 0188-16-16 | 1         | 1- 11 1/2     | 1   |
| ^ 56100 | 0188-20-20 | 1-1/4     | 1-1/4- 11 1/2 | 1   |
| 56108   | 0188-24-24 | 1-1/2     | 1-1/2- 11 1/2 | 1   |

### MALE PIPE NPTF

0188




---

| J&B #   | PARKER # | HOSE SIZE | QTY |
|---------|----------|-----------|-----|
| 54360   | 88DB-12  | 3/4       | 1   |
| 54362   | 88DB-16  | 1         | 1   |
| ^ 56200 | 88DB-20  | 1-1/4     | 1   |

### HEAVY DUTY HOSE CLAMP

88DB



\* Numbers with a “^” are not necessarily stocked in large quantities

# PARKRIMP HOSE FITTINGS

---

## \*\*\*STAINLESS STEEL\*\*\* 91 SERIES


91 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

919 (SAE 100R14) TFE STAINLESS MEDIUM PRESSURE HOSE      Page 736

---

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |         | QTY |
|-------|-------------|--------------|------|---------|-----|
|       |             |              | SIZE | THREAD  |     |
| 56520 | 10691N-4-4C | -4           | 1/4  | 7/16-20 | 1   |
| 56521 | 10691N-5-5C | -5           | 5/16 | 1/2-20  | 1   |
| 56522 | 10691N-6-6C | -6           | 3/8  | 9/16-18 | 1   |

**FEMALE SAE (JIC)  
37° SWIVEL  
STRAIGHT  
10691N**



\* 300 Series SS nipple, nut & shell

\* Dual 37 degree / 45 degree seat on sizes -4 and -5.

---

# REUSABLE HOSE FITTINGS

## 90 SERIES

90 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .


919 (SAE 100R14) TFE STAINLESS MEDIUM PRESSURE HOSE Page 736

| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |        | QTY |
|-------|-------------|--------------|------|--------|-----|
|       |             |              | SIZE | THREAD |     |
| 51342 | 20690-10-10 | -10          | 5/8  | 7/8-14 | 1   |

\* Brass nipple, ferrule, steel socket

### SAE (JIC) 37° SWIVEL

20690




| J&B # | PARKER #   | HOSE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------|--------------|----------------|-----|
| 51340 | 20190-8-10 | -10          | 1/2-14         | 1   |

\* Brass nipple, ferrule, steel socket

### MALE PIPE

20190



| J&B # | PARKER #    | HOSE<br>SIZE | TUBE<br>SIZE | QTY |
|-------|-------------|--------------|--------------|-----|
| 51350 | 23490-10-10 | -10          | 5/8          | 1   |

\* Brass nipple, ferrule, steel socket  
Use with HAB nut and sleeve

### STRAIGHT TUBE

23490



| J&B # | PARKER #    | HOSE<br>SIZE | TUBE |          | QTY |
|-------|-------------|--------------|------|----------|-----|
|       |             |              | SIZE | THREAD   |     |
| 51360 | 26190-8-10  | -10          | 1/2  | 11/16-20 | 1   |
| 51362 | 26190-10-10 | -10          | 5/8  | 13/16-18 | 1   |

\* Brass nipple, ferrule, steel socket  
Use with HAB nut and sleeve

### SAE COMPRESSION AIR BRAKE

26190



# PARKRIMP HOSE FITTINGS


## 91 SERIES

91 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

919 (SAE 100R14) TFE STAINLESS MEDIUM PRESSURE HOSE Page 736

| J&B #   | PARKER #     | HOSE<br>SIZE | TUBE |          | QTY |
|---------|--------------|--------------|------|----------|-----|
|         |              |              | SIZE | THREAD   |     |
| ^ 55590 | 10691N-4-4   | -4           | 1/4  | 7/16-20  | 1   |
| ^ 55591 | 10691N-5-5   | -5           | 5/16 | 1/2-20   | 1   |
| 42210   | 10691N-6-6   | -6           | 3/8  | 9/16-18  | 1   |
| ^ 55594 | 10691N-8-8   | -8           | 1/2  | 3/4-16   | 1   |
| ^ 55596 | 10691N-8-10  | -10          | 1/2  | 7/8-14   | 1   |
| 42212   | 10691N-10-10 | -10          | 5/8  | 7/8-14   | 1   |
| 42214   | 10691N-12-12 | -12          | 3/4  | 1-1/6-12 | 1   |


**FEMALE SAE (JIC)  
37° SWIVEL  
STRAIGHT  
10691N**



\* Brass nipple, steel nut and shell


| J&B #   | PARKER #   | HOSE<br>SIZE | PIPE<br>THREAD | QTY |
|---------|------------|--------------|----------------|-----|
| ^ 55580 | 10191N-4-4 | -4           | 1/4            | 1   |
| ^ 55582 | 10191N-6-6 | -6           | 3/8            | 1   |
| ^ 55584 | 10191N-8-8 | -8           | 1/2            | 1   |

**MALE PIPE  
10191N**



| J&B #   | PARKER #   | HOSE<br>SIZE | TUBE |        | QTY |
|---------|------------|--------------|------|--------|-----|
|         |            |              | SIZE | THREAD |     |
| ^ 55579 | 10891N-6-6 | -6           | 3/8  | 5/8-18 | 1   |

**FEMALE SAE  
45 SWIVEL  
STRAIGHT  
10891N**





# PARKRIMP HOSE FITTINGS

## 91 SERIES


91 SERIES FITTINGS CAN BE USED WITH THE FOLLOWING HOSE . . . .

919 (SAE 100R14) TFE STAINLESS MEDIUM PRESSURE HOSE Page 736

---

| J&B #   | PARKER #     | HOSE<br>SIZE | TUBE |          | QTY |
|---------|--------------|--------------|------|----------|-----|
|         |              |              | SIZE | THREAD   |     |
| ^ 55575 | 16191N-10-10 | -10          | 5/8  | 13/16-18 | 1   |

\* Use with HAB nut and sleeve.




**COMPRESSION  
AIR BRAKE  
16191N**

---

| J&B #   | PARKER #     | HOSE<br>SIZE | TUBE<br>SIZE | QTY |
|---------|--------------|--------------|--------------|-----|
| ^ 55570 | 13491N-10-10 | -10          | 5/8          | 1   |

\* Numbers with a "^" are not necessarily stocked in large quantities.

\* Without nut and ferrule.



**STRAIGHT TUBE  
13491N**

# FLARETITE SEALS

## 304 STAINLESS STEEL SEALS


### THE FLARED FITTING

Designed some 70 years ago the flared fitting offered manufacturers and users a cost effective easy to assemble small package size comprehensive range of fittings that has become Globally accepted.

### COMMON ISSUES


Evolving higher pressure and more demanding duty cycle hydraulic systems exposed the metal to metal flare sealing face weakness of flared fittings making it very difficult to obtain a permanent leak free flared type fitting joint.

It has become the norm to expect a flared fitting to leak from misaligned flare fittings, during forging, flared surface damage and scratches or leakage caused by vibration in the field.



**THE SOLUTION**  
**FLARED FITTING + FLARETITE**  
**=**  
**100% LEAK FREE JOINT**

The Flaretite Seal is a stainless steel stamping, designed with multiple concentric rings. The entire seal is impregnated with a baked –on Loctite coating. When inserted into a flared fitting joint the concentric rings form multiple seals down the face of the flare and the Loctite coating fills minor imperfections. The sealing rings prevent environmental contamination and aggressive cleaning solvents from attacking the seal face and also protect the face from fretting, galling, over tightening and electrolysis. Unlike ORFS fittings Flaretite Seals will not em-brittle, harden & fail like o-rings do. Flaretite Seals will not fail in a fire like o-rings, this prevents atomized oil from fueling combustion.



Independently tested by Eaton's Aeroquip hose & fittings division to one million high pressure square wave pulse cycles on badly scored JIC flared fitting faces without failure, this design, which easily installs by simply clipping over the male flare section, makes Flaretite Seals the single best choice "compliant seal" flared type fitting permanent leak free fix.

- 304 Stainless steel steel with Loctite Vibra Seal coating for standard carbon steel fittings.
- Rated for -40 to 300 F temperature and all common gases & fluids.

| J&B # | 37 DEGREE<br>FLARE SIZE | DASH<br>SIZE | QTY |
|-------|-------------------------|--------------|-----|
| 59800 | 1/4                     | -4           | 5   |
| 59801 | 3/8                     | -6           | 5   |
| 59802 | 1/2                     | -8           | 5   |
| 59803 | 5/8                     | -10          | 5   |
| 59804 | 3/4                     | -12          | 5   |

# ADAPTERS


## 37° FLARE STEEL ADAPTERS

- Parker steel adapters are furnished cadmium plated and are made from close grained non-porous steel forgings or steel bar stock.
- These adapters conform to the Hydraulic Tube Fitting Standard as published in J514 of the Society of Automotive Engineers (SAE) Handbook and to specifications of the former Joint Industry Conference (JIC) on Hydraulic Standards for Industrial Equipment.

| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------------------|--------------|----------------|-----|
| 55944 | 0103-2-2               | 1/8          | 1/8            | 1   |
| 55945 | 0103-2-3               | 3/16         | 1/8            | 1   |
| 52769 | 0103-2-4               | 1/4          | 1/8            | 1   |
| 51370 | 0103-4-4               | 1/4          | 1/4            | 1   |
| 51371 | 0103-6-4               | 1/4          | 3/8            | 1   |
| 55946 | 0103-8-4               | 1/4          | 1/2            | 1   |
| 55947 | 0103-2-5               | 5/16         | 1/8            | 1   |
| 51373 | 0103-4-5               | 5/16         | 1/4            | 1   |
| 55948 | 0103-2-6               | 3/8          | 1/8            | 1   |
| 52770 | 0103-4-6               | 3/8          | 1/4            | 1   |
| 51372 | 0103-6-6               | 3/8          | 3/8            | 1   |
| 52771 | 0103-8-6               | 3/8          | 1/2            | 1   |
| 52773 | 0103-4-8               | 1/2          | 1/4            | 1   |
| 52772 | 0103-6-8               | 1/2          | 3/8            | 1   |
| 51374 | 0103-8-8               | 1/2          | 1/2            | 1   |
| 52774 | 0103-12-8              | 1/2          | 3/4            | 1   |
| 52776 | 0103-6-10              | 5/8          | 3/8            | 1   |
| 52775 | 0103-8-10              | 5/8          | 1/2            | 1   |
| 52777 | 0103-12-10             | 5/8          | 3/4            | 1   |
| 52778 | 0103-8-12              | 3/4          | 1/2            | 1   |
| 51376 | 0103-12-12             | 3/4          | 3/4            | 1   |
| 51377 | 0103-16-12             | 3/4          | 1              | 1   |
| 55949 | 0103-12-14             | 7/8          | 3/4            | 1   |
| 51379 | 0103-12-16             | 1            | 3/4            | 1   |
| 51378 | 0103-16-16             | 1            | 1              | 1   |
| 52779 | 0103-16-20             | 1-1/4        | 1              | 1   |
| 51385 | 0103-20-20             | 1-1/4        | 1-1/4          | 1   |
| 55950 | 0103-20-24             | 1-1/2        | 1-1/4          | 1   |
| 51388 | 0103-24-24             | 1-1/2        | 1-1/2          | 1   |

### MALE CONNECTOR

0103 (FTX)




# ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------------------|--------------|----------------|-----|
| 51369 | 2103-2-4               | 1/4          | 1/8            | 1   |
| 51380 | 2103-4-4               | 1/4          | 1/4            | 1   |
| 51387 | 2103-6-4               | 1/4          | 3/8            | 1   |
| 51375 | 2103-4-5               | 5/16         | 1/4            | 1   |
| 51381 | 2103-4-6               | 3/8          | 1/4            | 1   |
| 51382 | 2103-6-6               | 3/8          | 3/8            | 1   |
| 51389 | 2103-8-6               | 3/8          | 1/2            | 1   |
| 51368 | 2103-4-8               | 1/2          | 1/4            | 1   |
| 51383 | 2103-6-8               | 1/2          | 3/8            | 1   |
| 51384 | 2103-8-8               | 1/2          | 1/2            | 1   |
| 51391 | 2103-12-8              | 1/2          | 3/4            | 1   |
| 51390 | 2103-8-10              | 5/8          | 1/2            | 1   |
| 51392 | 2103-12-10             | 5/8          | 3/4            | 1   |
| 51393 | 2103-8-12              | 3/4          | 1/2            | 1   |
| 51386 | 2103-12-12             | 3/4          | 3/4            | 1   |
| 51397 | 2103-12-16             | 1            | 3/4            | 1   |
| 51395 | 2103-16-16             | 1            | 1              | 1   |
| 51399 | 2103-20-16             | 1            | 1-1/4          | 1   |
| 51398 | 2103-16-20             | 1-1/4        | 1              | 1   |
| 51400 | 2103-20-20             | 1-1/4        | 1-1/4          | 1   |

**MALE ELBOW  
2103 (CTX)**



**45° MALE ELBOW  
3103 (VTX)**

| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------------------|--------------|----------------|-----|
| 52494 | 3103-4-4               | 1/4          | 1/4            | 1   |
| 52496 | 3103-4-6               | 3/8          | 1/4            | 1   |
| 52501 | 3103-6-6               | 3/8          | 3/8            | 1   |
| 52502 | 3103-8-6               | 3/8          | 1/2            | 1   |
| 52498 | 3103-6-8               | 1/2          | 3/8            | 1   |
| 52500 | 3103-8-8               | 1/2          | 1/2            | 1   |
| 52780 | 3103-12-8              | 1/2          | 3/4            | 1   |
| 52503 | 3103-8-10              | 5/8          | 1/2            | 1   |
| 52505 | 3103-12-10             | 5/8          | 3/4            | 1   |
| 52499 | 3103-8-12              | 3/4          | 1/2            | 1   |
| 52504 | 3103-12-12             | 3/4          | 3/4            | 1   |
| 52510 | 3103-16-16             | 1            | 1              | 1   |




# ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | STRAIGHT<br>THREAD | QTY |
|-------|------------------------|--------------|--------------------|-----|
| 54324 | 06B-4                  | 1/4          | 7/16-20            | 1   |
| 54326 | 06B-6                  | 3/8          | 9/16-18            | 1   |
| 54328 | 06B-8                  | 1/2          | 3/4-16             | 1   |
| 54329 | 06B-10                 | 5/8          | 7/8-14             | 1   |
| 54330 | 06B-12                 | 3/4          | 1-1/16-12          | 1   |
| 54332 | 06B-16                 | 1            | 1-5/16-12          | 1   |
| 54333 | 06B-20                 | 1-1/4        | 1-5/8-12           | 1   |
| 54331 | 06B-24                 | 1-1/2        | 1-7/8-12           | 1   |

**NUT**  
**06B (BTX)**




| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|-----|
| 54334 | 06S-4                  | 1/4          | 1   |
| 54336 | 06S-6                  | 3/8          | 1   |
| 54338 | 06S-8                  | 1/2          | 1   |
| 54339 | 06S-10                 | 5/8          | 1   |
| 54340 | 06S-12                 | 3/4          | 1   |
| 54342 | 06S-16                 | 1            | 1   |

**INCH SLEEVE**  
**06S (TX)**



| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|-----|
| 55980 | 2353-4-4               | 1/4          | 1   |
| 55982 | 2353-6-6               | 3/8          | 1   |
| 55983 | 2353-8-8               | 1/2          | 1   |
| 55984 | 2353-10-10             | 5/8          | 1   |
| 55985 | 2353-12-12             | 3/4          | 1   |

**BULKHEAD UNION  
ELBOW**  
**2353 (WETX-WLN-S)**




# ADAPTERS

## 37° FLARE STEEL ADAPTERS

| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | SWIVEL<br>THREAD | QTY |
|-------|------------------------|--------------|------------------|-----|
| 54284 | 3903-4-4               | 1/4          | 7/16-20          | 1   |
| 54285 | 3903-5-5               | 5/16         | 1/2-20           | 1   |
| 54286 | 3903-6-6               | 3/8          | 9/16-18          | 1   |
| 54288 | 3903-8-8               | 1/2          | 3/4-16           | 1   |
| 54289 | 3903-10-10             | 5/8          | 7/8-14           | 1   |
| 54290 | 3903-12-12             | 3/4          | 1-1/16-12        | 1   |
| 54291 | 3903-16-16             | 1            | 1-5/16-12        | 1   |
| 54293 | 3903-20-20             | 1-1/4        | 1-5/8-12         | 1   |

### SWIVEL NUT ELBOW


3903 (C6X)



| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------------------|--------------|----------------|-----|
| 52364 | 2203-4-4               | 1/4          | 1/4            | 1   |
| 52366 | 2203-6-6               | 3/8          | 3/8            | 1   |
| 52368 | 2203-8-8               | 1/2          | 1/2            | 1   |

### FEMALE ELBOW


2203 (DTX)



| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|-------|------------------------|--------------|----------------|-----|
| 52593 | 0203-4-4               | 1/4          | 1/4            | 1   |
| 52594 | 0203-6-6               | 3/8          | 3/8            | 1   |
| 52595 | 0203-8-8               | 1/2          | 1/2            | 1   |

### FEMALE CONNECTOR

0203 (GTX)




# ADAPTERS

## 37° FLARE STEEL ADAPTERS

| J&B #  | HOSE FITTING PART # | TUBE O.D. REDUCTION | TUBE END UN/UNF-2A | TUBE END UN/UNF-2B | QTY |
|--------|---------------------|---------------------|--------------------|--------------------|-----|
| 52961  | 0603-6-4            | 3/8 to 1/4          | 7/16-20            | 9/16-18            | 1   |
| 52958  | 0603-8-4            | 1/2 to 1/4          | 7/16-20            | 3/4-16             | 1   |
| 52962  | 0603-8-6            | 1/2 to 3/8          | 9/16-18            | 3/4-16             | 1   |
| *52964 | *0603-10-8          | 5/8 to 1/2          | 3/4-16             | 7/8-14             | 1   |
| 52960  | 0603-12-6           | 3/4 to 3/8          | 9/16-18            | 1-1/16-12          | 1   |
| 52965  | 0603-12-8           | 3/4 to 1/2          | 3/4-16             | 1-1/16-12          | 1   |
| *52966 | *0603-12-10         | 3/4 to 5/8          | 7/8-14             | 1-1/16-12          | 1   |
| *52963 | *0603-14-12         | 7/8 to 3/4          | 1-1/16-12          | 1-3/16-12          | 1   |
| 52968  | 0603-16-12          | 1 to 3/4            | 1-1/16-12          | 1-5/16-12          | 1   |
| 52972  | 0603-20-12          | 1-1/4 to 3/4        | 1-1/16-12          | 1-5/8-12           | 1   |
| 52967  | 0603-20-16          | 1-1/4 to 1          | 1-5/16-12          | 1-5/8-12           | 1   |
| 52969  | 0603-24-20          | 1-1/2 to 1-1/4      | 1-5/8-12           | 1-7/8-12           | 1   |


**TUBE END REDUCER**  
**0603 (TRTX-S)**



\* Comes with an O6B(BTX) nut attached. For all other sizes, order O6B(BTX) nut separately on page 770A.


| J&B # | HOSE FITTING PART # | TUBE SIZE | QTY |
|-------|---------------------|-----------|-----|
| 55450 | 0353-4-4            | 1/4       | 1   |
| 55452 | 0353-6-6            | 3/8       | 1   |
| 55454 | 0353-8-8            | 1/2       | 1   |
| 55480 | 0353-10-10          | 5/8       | 1   |
| 55456 | 0353-12-12          | 3/4       | 1   |

**BULKHEAD UNION**  
**0353 (WTX-WLN-S)**



| J&B # | HOSE FITTING PART # | TUBE SIZE | SWIVEL THREAD | QTY |
|-------|---------------------|-----------|---------------|-----|
| 55500 | 393T-4-4            | 1/4       | 7/16-20       | 1   |
| 55502 | 393T-6-6            | 3/8       | 9/16-18       | 1   |
| 55504 | 393T-8-8            | 1/2       | 3/4-16        | 1   |
| 55506 | 393T-10-10          | 5/8       | 7/8-14        | 1   |
| 55508 | .393T-12-12         | 3/4       | 1-1/16-12     | 1   |

**SWIVEL NUT BRANCH TEE**  
**393T (S6X-S)**




# ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|-----|
| 54103 | 03CP-3                 | 3/16         | 1   |
| 54104 | 03CP-4                 | 1/4          | 1   |
| 54105 | 03CP-5                 | 5/16         | 1   |
| 54106 | 03CP-6                 | 3/8          | 1   |
| 54108 | 03CP-8                 | 1/2          | 1   |
| 54110 | 03CP-10                | 5/8          | 1   |
| 54112 | 03CP-12                | 3/4          | 1   |
| 54114 | 03CP-14                | 7/8          | 1   |
| 54116 | 03CP-16                | 1            | 1   |
| 54118 | 03CP-20                | 1-1/4        | 1   |
| 54119 | 03CP-24                | 1-1/2        | 1   |

**PLUG**  
**03CP (PNTX)**




| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|-----|
| 54123 | 06CP-3                 | 3/16         | 1   |
| 54124 | 06CP-4                 | 1/4          | 1   |
| 54125 | 06CP-5                 | 5/16         | 1   |
| 54126 | 06CP-6                 | 3/8          | 1   |
| 54128 | 06CP-8                 | 1/2          | 1   |
| 54130 | 06CP-10                | 5/8          | 1   |
| 54132 | 06CP-12                | 3/4          | 1   |
| 54131 | 06CP-14                | 7/8          | 1   |
| 54133 | 06CP-16                | 1            | 1   |
| 54135 | 06CP-20                | 1-1/4        | 1   |
| 54137 | 06CP-24                | 1-1/2        | 1   |

**CAP**  
**06CP (FNTX)**



| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|--------------|-----|
| 56530 | 0606-4-4               | 1/4          | 1/4          | 1   |
| 56531 | 0606-6-6               | 3/8          | 3/8          | 1   |
| 56532 | 0606-8-8               | 1/2          | 1/2          | 1   |
| 56533 | 0606-10-10             | 5/8          | 5/8          | 1   |
| 56534 | 0606-12-12             | 3/4          | 3/4          | 1   |
| 56535 | 0606-16-16             | 1            | 1            | 1   |

**SWIVEL NUT  
UNION**  
**0606 (HX6)**





# ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | MALE<br>PIPE | QTY |
|-------|------------------------|--------------|--------------|-----|
| 56360 | 0106-4-4               | 1/4          | 1/4          | 1   |
| 56362 | 0106-4-5               | 5/16         | 1/4          | 1   |
| 56364 | 0106-4-6               | 3/8          | 1/4          | 1   |
| 56366 | 0106-6-6               | 3/8          | 3/8          | 1   |
| 56368 | 0106-6-8               | 1/2          | 3/8          | 1   |
| 56369 | 0106-8-8               | 1/2          | 1/2          | 1   |
| 56370 | 0106-8-10              | 5/8          | 1/2          | 1   |
| 56372 | 0106-12-12             | 3/4          | 3/4          | 1   |
| 56373 | 0106-12-16             | 1"           | 3/4          | 1   |
| 56374 | 0106-16-16             | 1"           | 1"           | 1   |

**SWIVEL  
CONNECTOR  
0106 (F6X)**




| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | SWIVEL<br>NUT END | QTY |
|-------|------------------------|--------------|-------------------|-----|
| 56340 | 3703-4-4               | 1/4          | 7/16-20           | 1   |
| 56342 | 3703-5-5               | 5/16         | 1/2-20            | 1   |
| 56344 | 3703-6-6               | 3/8          | 9/16-18           | 1   |
| 56346 | 3703-8-8               | 1/2          | 3/4-16            | 1   |
| 56348 | 3703-10-10             | 5/8          | 7/8-14            | 1   |
| 56350 | 3703-12-12             | 3/4          | 1-1/16-12         | 1   |
| 56352 | 3703-16-16             | 1            | 1-5/16-12         | 1   |

**45° SWIVEL NUT  
ELBOW  
3703 (V6X)**



| J&B # | HOSE FITTING<br>PART # | TUBE<br>O.D. | FEMALE<br>PIPE | SWIVEL<br>NUT END | QTY |
|-------|------------------------|--------------|----------------|-------------------|-----|
| 56320 | 6-6 G6X-S              | 3/8          | 3/8            | 9/16-18           | 1   |
| 56322 | 8 G6X-S                | 1/2          | 3/8            | 3/4-16            | 1   |
| 56324 | 8-8 G6X-S              | 1/2          | 1/2            | 3/4-16            | 1   |
| 56326 | 10 G6X-S               | 5/8          | 1/2            | 7/8-14            | 1   |
| 56328 | 12 G6X-S               | 3/4          | 3/4            | 1-1/16-12         | 1   |

**SWIVEL  
CONNECTOR  
G6X-S**




# ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|--------------|-----|
| 51402 | 0303-4-4               | 1/4          | 1/4          | 1   |
| 51401 | 0303-4-6               | 1/4          | 3/8          | 1   |
| 51403 | 0303-5-5               | 5/16         | 5/16         | 1   |
| 51404 | 0303-6-6               | 3/8          | 3/8          | 1   |
| 51405 | 0303-6-8               | 3/8          | 1/2          | 1   |
| 51406 | 0303-8-8               | 1/2          | 1/2          | 1   |
| 51407 | 0303-10-10             | 5/8          | 5/8          | 1   |
| 51411 | 0303-10-12             | 5/8          | 3/4          | 1   |
| 51408 | 0303-12-12             | 3/4          | 3/4          | 1   |
| 51413 | 2403-14-12             | 3/4          | 7/8          | 1   |
| 51409 | 0303-12-16             | 3/4          | 1            | 1   |
| 51410 | 0303-16-16             | 1            | 1            | 1   |
| 51412 | 0303-20-20             | 1-1/4        | 1-1/4        | 1   |

**UNION**  
**0303 (HTX)**




| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|-------|------------------------|--------------|-----|
| 51420 | 033T-4-4               | 1/4          | 1   |
| 51422 | 033T-6-6               | 3/8          | 1   |
| 51424 | 033T-8-8               | 1/2          | 1   |
| 51426 | 033T-10-10             | 5/8          | 1   |

**UNION TEE**  
**033T (JTX-S)**



| J&B # | HOSE FITTING<br>PART # | TUBE<br>SIZE | SWIVEL<br>END | QTY |
|-------|------------------------|--------------|---------------|-----|
| 51428 | 063T-4-4               | 1/4          | 7/16-20       | 1   |
| 51430 | 063T-6-6               | 3/8          | 9/16-18       | 1   |
| 51432 | 063T-8-8               | 1/2          | 3/4-16        | 1   |
| 51434 | 063T-10-10             | 5/8          | 7/8-14        | 1   |
| 51436 | 063T-12-12             | 3/4          | 1-1/16-12     | 1   |
| 51438 | 063T-16-16             | 1            | 1-5/16-12     | 1   |

**SWIVEL NUT RUN TEE**  
**063T (R6X-S)**



# ADAPTERS


## \*\*\*STAINLESS STEEL\*\*\*

### 37° FLARE STEEL ADAPTERS

| J&B #  | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|--------|------------------------|--------------|----------------|-----|
| V53090 | 0103-4-4C              | 1/4          | 1/4            | 1   |
| V53091 | 0103-6-6C              | 3/8          | 3/8            | 1   |
| V53092 | 0103-8-8C              | 1/2          | 1/2            | 1   |
| V53094 | 0103-12-12C            | 3/4          | 3/4            | 1   |
| V53095 | 0103-16-16C            | 1            | 1              | 1   |
| V53096 | 0103-20-20C            | 1-1/4        | 1-1/4          | 1   |

#### MALE CONNECTOR


0103 (FTX)



| J&B #  | HOSE FITTING<br>PART # | TUBE<br>SIZE | PIPE<br>THREAD | QTY |
|--------|------------------------|--------------|----------------|-----|
| V53098 | 2103-4-4C              | 1/4          | 1/4            | 1   |
| V53099 | 2103-6-6C              | 3/8          | 3/8            | 1   |
| V53100 | 2103-8-8C              | 1/2          | 1/2            | 1   |
| V53102 | 2103-12-12C            | 3/4          | 3/4            | 1   |
| V53104 | 2103-16-16C            | 1            | 1              | 1   |
| V53105 | 2103-20-20C            | 1-1/4        | 1-1/4          | 1   |

#### MALE ELBOW

2103 (CTX)



# ADAPTERS


## 37° FLARE STEEL ADAPTERS "WITH O-RING"

- Parker steel adapters are furnished cadmium plated and are made from close grained non-porous steel forgings or steel bar stock.

| J&B # | PARKER #   | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|------------|------------------|-----------------------|-----|
| 52385 | 0503-2-2   | 1/8              | 5/16-24               | 1   |
| 55956 | 0503-3-3   | 3/16             | 3/8-24                | 1   |
| 55954 | 0503-2-4   | 1/4              | 5/16-24               | 1   |
| 55955 | 0503-3-4   | 1/4              | 3/8-24                | 1   |
| 52388 | 0503-4-4   | 1/4              | 7/16-20               | 1   |
| 55957 | 0503-5-4   | 1/4              | 1/2-20                | 1   |
| 52389 | 0503-6-4   | 1/4              | 9/16-18               | 1   |
| 55958 | 0503-8-4   | 1/4              | 3/4-16                | 1   |
| 52395 | 0503-5-5   | 5/16             | 1/2-20                | 1   |
| 55959 | 0503-6-5   | 5/16             | 9/16-18               | 1   |
| 52396 | 0503-4-6   | 3/8              | 7/16-20               | 1   |
| 55960 | 0503-5-6   | 3/8              | 1/2-20                | 1   |
| 52390 | 0503-6-6   | 3/8              | 9/16-18               | 1   |
| 52397 | 0503-8-6   | 3/8              | 3/4-16                | 1   |
| 52399 | 0503-10-6  | 3/8              | 7/8-14                | 1   |
| 52401 | 0503-6-8   | 1/2              | 9/16-18               | 1   |
| 52392 | 0503-8-8   | 1/2              | 3/4-16                | 1   |
| 52403 | 0503-10-8  | 1/2              | 7/8-14                | 1   |
| 54218 | 0503-12-8  | 1/2              | 1-1/16-12             | 1   |
| 52422 | 0503-8-10  | 5/8              | 3/4-16                | 1   |
| 52393 | 0503-10-10 | 5/8              | 7/8-14                | 1   |
| 55961 | 0503-12-10 | 5/8              | 1-1/16-12             | 1   |
| 52405 | 0503-8-12  | 3/4              | 3/4-16                | 1   |
| 52398 | 0503-10-12 | 3/4              | 7/8-14                | 1   |
| 52394 | 0503-12-12 | 3/4              | 1-1/16-12             | 1   |
| 55962 | 0503-14-12 | 3/4              | 1-3/16-12             | 1   |
| 54217 | 0503-16-12 | 3/4              | 1-5/16-12             | 1   |
| 52407 | 0503-14-14 | 7/8              | 1-3/16-12             | 1   |
| 55963 | 0503-16-14 | 7/8              | 1-5/16-12             | 1   |
| 55964 | 0503-10-16 | 1                | 7/8-14                | 1   |
| 55965 | 0503-12-16 | 1                | 1-1/16-12             | 1   |
| 55966 | 0503-14-16 | 1                | 1-3/16-12             | 1   |
| 52409 | 0503-16-16 | 1                | 1-5/16-12             | 1   |
| 54220 | 0503-20-16 | 1                | 1-5/8-12              | 1   |
| 55967 | 0503-16-20 | 1-1/4            | 1-5/16-12             | 1   |
| 54221 | 0503-20-20 | 1-1/4            | 1-5/8-12              | 1   |

### STRAIGHT THREAD CONNECTOR

0503 (F5OX)




# ADAPTERS

## 37° FLARE STEEL ADAPTERS "WITH O-RING"


| J&B # | PARKER #   | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|------------|------------------|-----------------------|-----|
| 51440 | 0506-4-4   | 1/4              | 7/16-20               | 1   |
| 51442 | 0506-5-5   | 5/16             | 1/2-20                | 1   |
| 51443 | 0506-6-6   | 3/8              | 9/16-18               | 1   |
| 51446 | 0506-8-8   | 1/2              | 3/4-16                | 1   |
| 51449 | 0506-10-10 | 5/8              | 7/8-14                | 1   |
| 51452 | 0506-12-12 | 3/4              | 1-1/16-14             | 1   |
| 51455 | 0506-16-16 | 1                | 1-5/16-12             | 1   |
| 51457 | 0506-20-20 | 1-1/4            | 1-5/8-12              | 1   |

**SWIVEL STRAIGHT  
THREAD  
CONNECTOR  
JIC SWIVEL /  
ORB  
0506 (F650X)**



| J&B # | PARKER # | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|----------|------------------|-----------------------|-----|
| 52540 | 253T-6-6 | 3/8              | 9/16-18               | 1   |

**STRAIGHT  
THREAD BRANCH  
TEE  
253T (S50X)**




# ADAPTERS

## 37° FLARE STEEL ADAPTERS "WITH O-RING"

| J&B # | PARKER #   | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|------------|------------------|-----------------------|-----|
| 52512 | 3503-4-4   | 1/4              | 7/16-20               | 1   |
| 52514 | 3503-5-5   | 5/16             | 1/2-20                | 1   |
| 52516 | 3503-6-6   | 3/8              | 9/16-18               | 1   |
| 52520 | 3503-8-8   | 1/2              | 3/4-16                | 1   |
| 52522 | 3503-10-10 | 5/8              | 7/8-14                | 1   |
| 52524 | 3503-12-12 | 3/4              | 1-1/16-14             | 1   |
| 52525 | 3503-16-16 | 1                | 1-5/16-12             | 1   |

## 45° STRAIGHT THREAD ELBOW


3503 (V50X)



| J&B # | PARKER #   | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|------------|------------------|-----------------------|-----|
| 52370 | 2503-4-4   | 1/4              | 7/16-20               | 1   |
| 52371 | 2503-6-4   | 1/4              | 9/16-18               | 1   |
| 52372 | 2503-5-5   | 5/16             | 1/2-20                | 1   |
| 52383 | 2503-4-6   | 3/8              | 7/16-20               | 1   |
| 52380 | 2503-6-6   | 3/8              | 9/16-18               | 1   |
| 52377 | 2503-8-6   | 3/8              | 3/4-16                | 1   |
| 52384 | 2503-8-8   | 1/2              | 3/4-16                | 1   |
| 52378 | 2503-6-8   | 1/2              | 9/16-18               | 1   |
| 52414 | 2503-10-8  | 1/2              | 7/8-14                | 1   |
| 52379 | 2503-12-8  | 1/2              | 1-1/16-12             | 1   |
| 52381 | 2503-10-10 | 5/8              | 7/8-14                | 1   |
| 52382 | 2503-8-10  | 5/8              | 3/4-16                | 1   |
| 52363 | 2503-10-12 | 3/4              | 7/8-14                | 1   |
| 52386 | 2503-12-12 | 3/4              | 1-1/16-12             | 1   |
| 52415 | 2503-16-12 | 3/4              | 1-5/16-12             | 1   |
| 52387 | 2503-16-16 | 1                | 1-5/16-12             | 1   |
| 52417 | 2503-20-20 | 1-1/4            | 1-5/8-12              | 1   |

## STRAIGHT THREAD ELBOW


2503 (C50X)



| J&B # | PARKER #   | JIC TUBE<br>SIZE | O-RING PORT<br>THREAD | QTY |
|-------|------------|------------------|-----------------------|-----|
| 54605 | 5503-4-4   | 1/4              | 7/16-20               | 1   |
| 54606 | 5503-6-6   | 3/8              | 9/16-8                | 1   |
| 54607 | 5503-8-8   | 1/2              | 3/4-16                | 1   |
| 54608 | 5503-12-12 | 3/4              | 1-1/16-12             | 1   |

## LONG STRAIGHT THREAD ELBOW


5503 (CC50X-S)



# ADAPTERS

## SAE STRAIGHT THREAD PORT O-RING 90 Durometer Nitrile


| J&B # | PARKER #    | DASH SIZE | END SIZE | WIDTH | I.D. | QTY |
|-------|-------------|-----------|----------|-------|------|-----|
| 56260 | 3-904 N0552 | -4        | 1/4      | 0.07  | 0.35 | 1   |
| 56262 | 3-905 N0552 | -5        | 5/16     | 0.07  | 0.41 | 1   |
| 56264 | 3-906 N0552 | -6        | 3/8      | 0.08  | 0.47 | 1   |
| 56266 | 3-908 N0552 | -8        | 1/2      | 0.09  | 0.64 | 1   |
| 56268 | 3-910 N0552 | -10       | 5/8      | 0.10  | 0.76 | 1   |
| 56270 | 3-912 N0552 | -12       | 3/4      | 0.12  | 0.92 | 1   |
| 56272 | 3-916 N0552 | -16       | 1        | 0.12  | 1.17 | 1   |
| 56274 | 3-920 N0552 | -20       | 1-1/4    | 0.12  | 1.48 | 1   |



**O-RING**


| J&B # | PARKER #   | FEMALE PIPE THREAD | MALE STRAIGHT THREAD | QTY |
|-------|------------|--------------------|----------------------|-----|
| 54627 | 0502-4-4   | 1/4-18             | 7/16-20              | 1   |
| 54628 | 0502-5-4   | 1/4-18             | 1/2-20               | 1   |
| 54630 | 0502-6-4   | 1/4-18             | 9/16-18              | 1   |
| 55937 | 0502-8-4   | 1/4-18             | 3/4-16               | 1   |
| 54631 | 0502-6-6   | 3/8-16             | 9/16-18              | 1   |
| 54632 | 0502-8-6   | 3/8-18             | 3/4-16               | 1   |
| 54633 | 0502-10-6  | 3/8-16             | 7/8-14               | 1   |
| 55938 | 0502-6-8   | 1/2-14             | 9/16-18              | 1   |
| 54635 | 0502-8-8   | 1/2-14             | 3/4-16               | 1   |
| 54634 | 0502-10-8  | 1/2-14             | 7/8-14               | 1   |
| 54636 | 0502-12-8  | 1/2-14             | 1-1/16-12            | 1   |
| 55939 | 0502-10-12 | 3/4-14             | 7/8-14               | 1   |
| 54639 | 0502-12-12 | 3/4-14             | 1-1/16-12            | 1   |
| 54637 | 0502-14-12 | 3/4-14             | 1-3/16-12            | 1   |
| 54638 | 0502-16-12 | 3/4-14             | 1-5/16-12            | 1   |

**FEMALE PIPE  
ADAPTER  
0502 (F50G-S)**



| J&B # | PARKER # | MALE STRAIGHT THREAD | QTY |
|-------|----------|----------------------|-----|
| 54640 | 05CP-2   | 5/16-24              | 1   |
| 54641 | 05CP-3   | 3/8-24               | 1   |
| 54642 | 05CP-4   | 7/16-20              | 1   |
| 54643 | 05CP-5   | 1/2-20               | 1   |
| 54644 | 05CP-6   | 9/16-18              | 1   |
| 54645 | 05CP-8   | 3/4-16               | 1   |
| 54646 | 05CP-10  | 7/8-14               | 1   |
| 54647 | 05CP-12  | 1-1/16-12            | 1   |
| 54650 | 05CP-14  | 1-3/16-12            | 1   |
| 54648 | 05CP-16  | 1-5/16-12            | 1   |
| 54649 | 05CP-20  | 1-5/8-12             | 1   |

**HEX HEAD PLUG  
05CP (P50N-S)**




# METRIC ADAPTERS

## 37° FLARE STEEL ADAPTERS


| J&B #  | PARKER #   | INCH<br>SIZE<br>JIC 37°(1) | MALE METRIC<br>STRAIGHT<br>THREAD (2) | QTY |
|--------|------------|----------------------------|---------------------------------------|-----|
| ^53020 | 4M10C8OMXS | 1/4                        | M10 x 1                               | 1   |
| ^53022 | 6M14C8OMXS | 3/8                        | M14 x 1.5                             | 1   |
| ^53023 | 8M16C8OMXS | 1/2                        | M16 x 1.5                             | 1   |

**Male Elbow  
Metric Straight  
Thread (C8OMXS)**




| J&B #  | PARKER #   | INCH<br>SIZE<br>JIC 37°(1) | MALE METRIC<br>STRAIGHT<br>THREAD (2) | QTY |
|--------|------------|----------------------------|---------------------------------------|-----|
| ^53010 | 4M10F8OMXS | 1/4                        | M10 x 1                               | 1   |
| ^53012 | 6M14F8OMXS | 3/8                        | M14 x 1.5                             | 1   |
| ^53013 | 8M16F8OMXS | 1/2                        | M16 x 1.5                             | 1   |

**Male Connector  
Metric Straight  
Thread (F8OMXS)**




| J&B #  | PARKER #  | INCH<br>SIZE<br>JIC 37°(1) | BSPP MALE<br>PIPE<br>THREAD (2) | QTY |
|--------|-----------|----------------------------|---------------------------------|-----|
| ^52985 | 4-4C4OMXS | 1/4                        | 1/4                             | 1   |
| ^52987 | 6C4OMXS   | 3/8                        | 1/4                             | 1   |
| ^52988 | 6-6C4OMXS | 3/8                        | 3/8                             | 1   |
| ^52991 | 8-8C4OMXS | 1/2                        | 1/2                             | 1   |

**Male Elbow  
BSPP (C4OMXS)**



| J&B #  | PARKER #  | INCH<br>SIZE<br>JIC 37°(1) | BSPP MALE<br>PIPE<br>THREAD (2) | QTY |
|--------|-----------|----------------------------|---------------------------------|-----|
| ^52970 | 4F4OMXS   | 1/4                        | 1/8                             | 1   |
| ^52971 | 4-4F4OMXS | 1/4                        | 1/4                             | 1   |
| ^52976 | 6F4OMXS   | 3/8                        | 1/4                             | 1   |
| ^52977 | 6-6F4OMXS | 3/8                        | 3/8                             | 1   |
| ^52980 | 8-8F4OMXS | 1/2                        | 1/2                             | 1   |

**Male Connector  
BSPP (F4OMXS)**



\* Numbers with a "^" are not necessarily stocked in large quantities




# METRIC ADAPTERS

## 37° FLARE STEEL ADAPTERS

| J&B #  | PARKER # | INCH<br>SIZE<br>JIC 37°(1) | BSPT MALE<br>PIPE THREAD<br>(2) | QTY |
|--------|----------|----------------------------|---------------------------------|-----|
| ^53060 | 4-4C3MXS | 1/4                        | 1/4                             | 1   |
| ^53063 | 6C3MXS   | 3/8                        | 1/4                             | 1   |
| ^53064 | 6-6C3MXS | 3/8                        | 3/8                             | 1   |
| ^53068 | 8-8C3MXS | 1/2                        | 1/2                             | 1   |


Male Elbow  
BSPT (C3MXS)



2

| J&B #  | PARKER # | INCH<br>SIZE<br>JIC 37°(1) | BSPT MALE<br>PIPE THREAD<br>(2) | QTY |
|--------|----------|----------------------------|---------------------------------|-----|
| ^53040 | 4F3MXS   | 1/4                        | 1/8                             | 1   |
| ^53041 | 4-4F3MXS | 1/4                        | 1/4                             | 1   |
| ^53044 | 6F3MXS   | 3/8                        | 1/4                             | 1   |
| ^53045 | 6-6F3MXS | 3/8                        | 3/8                             | 1   |
| ^53049 | 8-8F3MXS | 1/2                        | 1/2                             | 1   |

Male  
Connector  
BSPT (F3MXS)




2

1


| J&B #  | PARKER #      | BSPT<br>MALE | NPT<br>FEMALE | QTY |
|--------|---------------|--------------|---------------|-----|
| ^55481 | 3/8X3/8F3HG-S | 3/8          | 3/8           | 1   |
| ^55484 | 3/4X3/4F3HG-S | 3/4          | 3/4           | 1   |

Conversion  
Adapter  
BSPT (F3HG)



| J&B #  | PARKER #       | BSPP<br>MALE | NPT<br>FEMALE | QTY |
|--------|----------------|--------------|---------------|-----|
| ^55490 | 3/8X3/8F4OHG-S | 3/8          | 3/8           | 1   |
| ^55494 | 3/4X3/4F4OHG-S | 3/4          | 3/4           | 1   |

Conversion  
Adapter  
BSPP (F4OHG)




\* Numbers with a "^" are not necessarily stocked in large quantities

# METRIC ADAPTERS

---

## METRIC STRAIGHT THREAD PLUG 7408

| J&B # | MFG #   | MALE METRIC<br>STRAIGHT<br>THREAD | QTY |
|-------|---------|-----------------------------------|-----|
| 55496 | 7408-14 | M14 x 1.50                        | 1   |
| 55497 | 7408-16 | M16 x 1.50                        | 1   |
| 55498 | 7408-20 | M20 x 1.50                        | 1   |



# ADAPTERS


## STEEL PIPE (HYDRAULIC)

- Parker steel adapters are furnished cadmium plated and are made from close grained non-porous steel forgings or steel bar stock.
- These adapters have Dryseal American (National Standard) taper (N.P.T.F.) pipe threads and unified class 2A male and 2B female straight threads.

| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 54152 | 01CP-2                 | 1/8            | 1   |
| 54154 | 01CP-4                 | 1/4            | 1   |
| 54156 | 01CP-6                 | 3/8            | 1   |
| 54158 | 01CP-8                 | 1/2            | 1   |
| 54160 | 01CP-12                | 3/4            | 1   |
| 54161 | 01CP-16                | 1              | 1   |
| 54162 | 01CP-20                | 1-1/4          | 1   |

### HEX HEAD PLUG


01CP (HP)



| J&B #   | HOSE FITTING<br>PART # | FEMALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|----------------|----------------|-----|
| 54083   | 0202-2-2               | 1/8            | 1/8            | 1   |
| 54084   | 0202-4-4               | 1/4            | 1/4            | 1   |
| ^ 54185 | 0202-4-6               | 3/8            | 1/4            | 1   |
| 54086   | 0202-6-6               | 3/8            | 3/8            | 1   |
| ^ 54189 | 0202-6-8               | 1/2            | 3/8            | 1   |
| 54088   | 0202-8-8               | 1/2            | 1/2            | 1   |
| ^ 54191 | 0202-8-12              | 3/4            | 1/2            | 1   |
| 54092   | 0202-12-12             | 3/4            | 3/4            | 1   |
| 54093   | 0202-16-16             | 1              | 1              | 1   |
| ^ 54193 | 0202-20-20             | 1-1/4          | 1-1/4          | 1   |

### PIPE COUPLING


0202 (GG)



| J&B # | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|-------|------------------------|--------------|----------------|-----|
| 52781 | 2102-2-2               | 1/8          | 1/8            | 1   |
| 52782 | 2102-4-4               | 1/4          | 1/4            | 1   |
| 52783 | 2102-6-6               | 3/8          | 3/8            | 1   |
| 52784 | 2102-8-8               | 1/2          | 1/2            | 1   |
| 54260 | 2102-12-12             | 3/4          | 3/4            | 1   |
| 54262 | 2102-16-16             | 1            | 1              | 1   |

### STREET ELBOW

2102 (CD)



\* Numbers with a "A" are not necessarily stocked in large quantities


# ADAPTERS

## STEEL PIPE (HYDRAULIC)

| J&B # | HOSE FITTING<br>PART # | MALE<br>PIPE | MALE<br>PIPE | QTY |
|-------|------------------------|--------------|--------------|-----|
| 52577 | 0101-2-2               | 1/8          | 1/8          | 1   |
| 52579 | 0101-2-4               | 1/4          | 1/8          | 1   |
| 52581 | 0101-4-4               | 1/4          | 1/4          | 1   |
| 52583 | 0101-4-6               | 3/8          | 1/4          | 1   |
| 52582 | 0101-6-6               | 3/8          | 3/8          | 1   |
| 52589 | 0101-6-8               | 1/2          | 3/8          | 1   |
| 52584 | 0101-8-8               | 1/2          | 1/2          | 1   |
| 52591 | 0101-8-12              | 3/4          | 1/2          | 1   |
| 52586 | 0101-12-12             | 3/4          | 3/4          | 1   |
| 52587 | 0101-16-16             | 1            | 1            | 1   |
| 55972 | 0101-20-20             | 1-1/4        | 1-1/4        | 1   |

### PIPE NIPPLE


0101 (FF)



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55900 | 2202-2-2               | 1/8            | 1   |
| 54184 | 2202-4-4               | 1/4            | 1   |
| 54186 | 2202-6-6               | 3/8            | 1   |
| 54188 | 2202-8-8               | 1/2            | 1   |
| 54190 | 2202-12-12             | 3/4            | 1   |
| 54192 | 2202-16-16             | 1              | 1   |
| 54195 | 2202-20-20             | 1-1/4          | 1   |

### FEMALE PIPE ELBOW


2202 (DD)



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55902 | 022T-2-2               | 1/8            | 1   |
| 54194 | 022T-4-4               | 1/4            | 1   |
| 54196 | 022T-6-6               | 3/8            | 1   |
| 54198 | 022T-8-8               | 1/2            | 1   |
| 54200 | 022T-12-12             | 3/4            | 1   |
| 54201 | 022T-16-16             | 1              | 1   |
| 55974 | 022T-20-20             | 1-1/4          | 1   |

### FEMALE PIPE TEE

022T (MMO)




# ADAPTERS

## STEEL PIPE (HYDRAULIC)

| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55904 | 212T-4-4               | 1/4            | 1   |
| 55905 | 212T-6-6               | 3/8            | 1   |
| 55906 | 212T-8-8               | 1/2            | 1   |
| 55907 | 212T-12-12             | 3/4            | 1   |

### MALE BRANCH TEE


212T (MMS)



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55910 | 012T-4-4               | 1/4            | 1   |
| 55911 | 012T-6-6               | 3/8            | 1   |
| 55912 | 012T-8-8               | 1/2            | 1   |
| 55913 | 012T-12-12             | 3/4            | 1   |

### MALE RUN TEE


012T (MRO)



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55916 | 4202-4-4               | 1/4            | 1   |
| 55917 | 4202-6-6               | 3/8            | 1   |
| 55918 | 4202-8-8               | 1/2            | 1   |
| 55919 | 4202-12-12             | 3/4            | 1   |

### FEMALE PIPE ELBOW


4202 (DD45)



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 55922 | 2101-4-4               | 1/4            | 1   |
| 55923 | 2101-6-6               | 3/8            | 1   |
| 55924 | 2101-8-8               | 1/2            | 1   |
| 55925 | 2101-12-12             | 3/4            | 1   |

### MALE PIPE ELBOW

2101 (CR)




# ADAPTERS

## STEEL PIPE (HYDRAULIC)

| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| 52900   | 0102-4-2               | 1/4          | 1/8            | 1   |
| 52901   | 0102-6-4               | 3/8          | 1/4            | 1   |
| ^ 52902 | 0102-8-4               | 1/2          | 1/4            | 1   |
| 52903   | 0102-8-6               | 1/2          | 3/8            | 1   |
| 52909   | 0102-12-6              | 3/4          | 3/8            | 1   |
| 52906   | 0102-12-8              | 3/4          | 1/2            | 1   |
| 52911   | 0102-16-8              | 1            | 1/2            | 1   |
| 52912   | 0102-16-12             | 1            | 3/4            | 1   |
| 52915   | 0102-20-16             | 1-1/4        | 1              | 1   |
| ^ 52916 | 0102-24-20             | 1-1/2        | 1-1/4          | 1   |

### PIPE THREAD REDUCER


0102 (PTR)



| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| ^ 56220 | 3102-4-4               | 1/4          | 1/4            | 1   |
| ^ 56222 | 3102-6-6               | 3/8          | 3/8            | 1   |
| 53070   | 3102-8-8               | 1/2          | 1/2            | 1   |
| 53071   | 3102-12-12             | 3/4          | 3/4            | 1   |

### 45° STREET ELBOW


3102 (CD45)



| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| 53703   | 0201-4-2               | 1/8          | 1/4            | 1   |
| ^ 56244 | 0201-6-4               | 1/4          | 3/8            | 1   |
| ^ 56246 | 0201-8-6               | 3/8          | 1/2            | 1   |
| ^ 56248 | 0201-12-8              | 1/2          | 3/4            | 1   |
| ^ 56250 | 0201-16-12             | 3/4          | 1              | 1   |
| 53705   | 0201-20-16             | 1            | 1-1/4          | 1   |

### Expander/ Adapter

0201 (FG)



\* Numbers with a "A" are not necessarily stocked in large quantities

# ADAPTERS


## FEMALE PIPE SWIVEL

- Parker steel adapters are furnished cadmium plated and are made from close grained non-porous steel forgings or steel bar stock.
- The female swivel end of these adapters is a straight pipe thread (NPSM) with a 30 degree seat. All male pipe fittings that are used with these female pipe swivel adapters must have a 30 degree seat in order to effect a proper seal. Parker male pipe hose fittings and male by female pipe swivel adapters contain this 30 degree seat.

| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| 52918   | 0107-2-2               | 1/8          | 1/8            | 1   |
| ^ 52919 | 0107-2-4               | 1/8          | 1/4            | 1   |
| 52920   | 0107-4-4               | 1/4          | 1/4            | 1   |
| 52921   | 0107-4-6               | 1/4          | 3/8            | 1   |
| 52923   | 0107-6-4               | 3/8          | 1/4            | 1   |
| 52922   | 0107-6-6               | 3/8          | 3/8            | 1   |
| 52924   | 0107-6-8               | 3/8          | 1/2            | 1   |
| 52925   | 0107-8-6               | 1/2          | 3/8            | 1   |
| 52926   | 0107-8-8               | 1/2          | 1/2            | 1   |
| 52927   | 0107-8-12              | 1/2          | 3/4            | 1   |
| 52929   | 0107-12-8              | 3/4          | 1/2            | 1   |
| 52928   | 0107-12-12             | 3/4          | 3/4            | 1   |
| ^ 52931 | 0107-12-16             | 3/4          | 1              | 1   |
| 52930   | 0107-16-16             | 1            | 1              | 1   |
| ^ 52933 | 0107-16-20             | 1            | 1-1/4          | 1   |
| ^ 52935 | 0107-20-20             | 1-1/4        | 1-1/4          | 1   |

### MALE PIPE ADAPTER


0107



| J&B # | HOSE FITTING<br>PART # | PIPE<br>THREAD | QTY |
|-------|------------------------|----------------|-----|
| 52932 | 0207-4-4               | 1/4            | 1   |
| 52934 | 0207-6-6               | 3/8            | 1   |
| 52936 | 0207-8-8               | 1/2            | 1   |
| 52938 | 0207-12-12             | 3/4            | 1   |
| 52940 | 0207-16-16             | 1              | 1   |

### FEMALE PIPE ADAPTER

0207



\* Numbers with a "^" are not necessarily stocked in large quantities


# ADAPTERS

## FEMALE PIPE SWIVEL

| J&B #   | PARKER #   | T1<br>PORT<br>THREAD | T2<br>FEMALE PIPE<br>THREAD | QTY |
|---------|------------|----------------------|-----------------------------|-----|
| ^ 52365 | 0507-4-4   | 7/16                 | 1/4                         | 1   |
| ^ 52367 | 0507-6-4   | 9/16                 | 1/4                         | 1   |
| 52374   | 0507-6-6   | 9/16                 | 3/8                         | 1   |
| ^ 52369 | 0507-8-6   | 3/4                  | 3/8                         | 1   |
| ^ 52373 | 0507-6-8   | 9/16                 | 1/2                         | 1   |
| 52376   | 0507-8-8   | 3/4                  | 1/2                         | 1   |
| ^ 52375 | 0507-10-8  | 7/8                  | 1/2                         | 1   |
| ^ 52391 | 0507-12-12 | 1-1/16               | 3/4                         | 1   |

## STRAIGHT THREAD ADAPTER


0507



| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| 52942   | 2107-4-4               | 1/4          | 1/4            | 1   |
| 52943   | 2107-6-4               | 3/8          | 1/4            | 1   |
| ^ 52945 | 2107-4-6               | 1/4          | 3/8            | 1   |
| 52944   | 2107-6-6               | 3/8          | 3/8            | 1   |
| ^ 52947 | 2107-8-6               | 1/2          | 3/8            | 1   |
| ^ 52949 | 2107-6-8               | 3/8          | 1/2            | 1   |
| 52946   | 2107-8-8               | 1/2          | 1/2            | 1   |
| ^ 52951 | 2107-8-12              | 1/2          | 3/4            | 1   |
| 52948   | 2107-12-12             | 3/4          | 3/4            | 1   |
| 52950   | 2107-16-16             | 1            | 1              | 1   |

## MALE PIPE 90° ELBOW


2107



| J&B #   | HOSE FITTING<br>PART # | FEMALE<br>PIPE | QTY |
|---------|------------------------|----------------|-----|
| ^ 56180 | 2207-4-4               | 1/4            | 1   |
| ^ 56182 | 2207-6-6               | 3/8            | 1   |
| ^ 56184 | 2207-8-8               | 1/2            | 1   |
| ^ 56186 | 2207-12-12             | 3/4            | 1   |

## FEMALE PIPE 90° ELBOW

2207



\* Numbers with a "^" are not necessarily stocked in large quantities




# ADAPTERS

## FEMALE PIPE SWIVEL

| J&B #   | HOSE FITTING<br>PART # | MALE<br>PIPE | FEMALE<br>PIPE | QTY |
|---------|------------------------|--------------|----------------|-----|
| 52952   | 3107-4-4               | 1/4          | 1/4            | 1   |
| 52954   | 3107-6-6               | 3/8          | 3/8            | 1   |
| 52955   | 3107-8-8               | 1/2          | 1/2            | 1   |
| 52957   | 3107-12-12             | 3/4          | 3/4            | 1   |
| ^ 52959 | 3107-16-16             | 1            | 1              | 1   |

**MALE PIPE  
45° ELBOW**

**3107**



| J&B #   | HOSE FITTING<br>PART # | SAE<br>STRAIGHT<br>THREAD<br>WITH O-RING | FEMALE<br>PIPE | QTY |
|---------|------------------------|------------------------------------------|----------------|-----|
| ^ 56160 | 2507-4-4               | 7/16                                     | 1/4            | 1   |
| ^ 56162 | 2507-6-6               | 9/16                                     | 3/8            | 1   |
| ^ 56164 | 2507-8-6               | 3/4                                      | 3/8            | 1   |
| ^ 56166 | 2507-8-8               | 3/4                                      | 1/2            | 1   |
| ^ 56168 | 2507-10-8              | 7/8                                      | 1/2            | 1   |
| ^ 56170 | 2507-12-8              | 1-1/16                                   | 1/2            | 1   |
| ^ 56172 | 2507-12-12             | 1-1/16                                   | 3/4            | 1   |

**STRAIGHT THREAD  
90° ELBOW**

**2507**




\* Numbers with a "^" are not necessarily stocked in large quantities

# ADAPTERS


## SEAL LOK FITTINGS

| J&B # | HOSE FITTING<br>PART # | END<br>SIZE<br>(1) & (2) | TUBE<br>END<br>(1) | TUBE<br>END<br>(2) | QTY |
|-------|------------------------|--------------------------|--------------------|--------------------|-----|
| 55460 | 4 XHLO-S               | 1/4                      | 7/16-20            | 9/16-18            | 1   |
| 55462 | 6 XHLO-S               | 3/8                      | 9/16-18            | 11/16-16           | 1   |
| 55467 | 8 XHLO-S               | 1/2                      | 3/4-16             | 13/16-16           | 1   |
| 55465 | 10 XHLO-S              | 5/8                      | 7/8-14             | 1-14               | 1   |
| 55466 | 12 XHLO-S              | 3/4                      | 1-1/16-12          | 1-3/16-12          | 1   |
| 55468 | 16 XHLO-S              | 1                        | 1-5/16-12          | 1-7/16-12          | 1   |

**ORFS MALE END  
ADAPTER  
(XHLO-S)**



**ORFS TUBE END  
REDUCER  
(TRLON-S)**



| J&B #  | HOSE FITTING<br>PART # | END<br>SIZE<br>(1) | FEMALE<br>END<br>(1) | END<br>SIZE<br>(2) | MALE<br>END<br>(2) |          | QTY |
|--------|------------------------|--------------------|----------------------|--------------------|--------------------|----------|-----|
| *55464 | 6-4 TRLON-S            | 3/8                | 11/16-16             | 1/4                | 9/16-18            |          | 1   |
| 55470  | 10-8 TRLON-S           | 5/8                | 1-14                 | 1/2                | 13/16-16           | 2 pieces | 1   |
| 55472  | 12-8 TRLON-S           | 3/4                | 1-3/16-12            | 1/2                | 13/16-16           | 2 pieces | 1   |
| *55474 | 12-10 TRLON-S          | 3/4                | 1-3/16-12            | 5/8                | 1-14               |          | 1   |
| *55476 | 20-16 TRLON-S          | 1-1/4              | 1-11/16-12           | 1"                 | 1-7/16-12          |          | 1   |

\* These sizes come manufactured with a crimp style nut on the large end.


# ADAPTERS

## SEAL LOK FITTINGS

| J&B # | PARKER #   | END<br>SIZE<br>(1) & (2) | JIC TUBE<br>END<br>(1) | ORFS<br>END<br>(2) | QTY |
|-------|------------|--------------------------|------------------------|--------------------|-----|
| 52542 | 4 LOHX6-S  | 1/4                      | 7/16-20                | 9/16-18            | 1   |
| 52543 | 6 LOHX6-S  | 3/8                      | 9/16-18                | 11/16-16           | 1   |
| 52544 | 8 LOHX6-S  | 1/2                      | 3/4-16                 | 13/16-16           | 1   |
| 52545 | 10 LOHX6-S | 5/8                      | 7/8-14                 | 1-14               | 1   |
| 52546 | 12 LOHX6-S | 3/4                      | 1-1/16-12              | 1-3/16-12          | 1   |
| 52547 | 16 LOHX6-S | 1                        | 1-5/16-12              | 1-7/16-12          | 1   |

**SWIVEL ADAPTER  
JIC TUBE SWIVEL /  
ORFS**


**(LOHX6-S)**



| J&B # | PARKER #  | END<br>SIZE<br>(1) & (2) | JIC TUBE<br>END<br>(1) | ORFS<br>END<br>(2) | QTY |
|-------|-----------|--------------------------|------------------------|--------------------|-----|
| 52554 | 4 XHL6-S  | 1/4                      | 7/16-20                | 9/16-18            | 1   |
| 52555 | 6 XHL6-S  | 3/8                      | 9/16-18                | 11/16-16           | 1   |
| 52556 | 8 XHL6-S  | 1/2                      | 3/4-16                 | 13/16-16           | 1   |
| 52557 | 10 XHL6-S | 5/8                      | 7/8-14                 | 1-14               | 1   |
| 52558 | 12 XHL6-S | 3/4                      | 1-1/16-12              | 1-3/16-12          | 1   |
| 52559 | 16 XHL6-S | 1                        | 1-5/16-12              | 1-7/16-12          | 1   |

**MALE SWIVEL  
ADAPTER  
JIC TUBE /  
ORFS SWIVEL**

**(XHL6-S)**



# ADAPTERS


## CAPS & PLUGS FOR SEAL LOK FITTINGS

### Plugs for Seal Loks

| J&B #   | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|---------|------------------------|--------------|-----|
| ^ 54275 | 4 PNLO-S               | 1/4          | 1   |
| ^ 54276 | 6 PNLO-S               | 3/8          | 1   |
| ^ 54277 | 8 PNLO-S               | 1/2          | 1   |
| ^ 54278 | 10 PNLO-S              | 5/8          | 1   |
| ^ 54279 | 12 PNLO-S              | 3/4          | 1   |
| ^ 54280 | 16 PNLO-S              | 1            | 1   |
| 54281   | 20 PNLO-S              | 1-1/4        | 1   |

### ORFS TUBE END PLUG

PNLO-S




### Caps for Seal Loks

| J&B #   | HOSE FITTING<br>PART # | TUBE<br>SIZE | QTY |
|---------|------------------------|--------------|-----|
| ^ 54265 | 4 FNL-S                | 1/4          | 1   |
| ^ 54266 | 6 FNL-S                | 3/8          | 1   |
| ^ 54267 | 8 FNL-S                | 1/2          | 1   |
| ^ 54268 | 10 FNL-S               | 5/8          | 1   |
| ^ 54269 | 12 FNL-S               | 3/4          | 1   |
| ^ 54270 | 16 FNL-S               | 1            | 1   |
| ^ 54271 | 20 FNL-S               | 1-1/4        | 1   |

### ORFS TUBE END CAP

FNL-S




\* Numbers with a “^” are not necessarily stocked in large quantities

## ORFS O-RING

90 Durometer Nitrile

| J&B # | PARKER #    | DASH<br>SIZE | END<br>SIZE | WIDTH | I.D. | QTY |
|-------|-------------|--------------|-------------|-------|------|-----|
| 56230 | 2-011 N0552 | -4           | 1/4         | 0.07  | 0.30 | 1   |
| 56231 | 2-012 N0552 | -6           | 3/8         | 0.07  | 0.36 | 1   |
| 56232 | 2-014 N0552 | -8           | 1/2         | 0.07  | 0.49 | 1   |
| 56233 | 2-016 N0552 | -10          | 5/8         | 0.07  | 0.61 | 1   |
| 56234 | 2-018 N0552 | -12          | 3/4         | 0.07  | 0.74 | 1   |
| 56235 | 2-020 N0552 | -14          | 7/8         | 0.07  | 0.86 | 1   |
| 56236 | 2-021 N0552 | -16          | 1           | 0.07  | 0.93 | 1   |
| 56237 | 2-025 N0552 | -20          | 1-1/4       | 0.07  | 1.18 | 1   |
| 56238 | 2-029 N0552 | -24          | 1-1/2       | 0.07  | 1.49 | 1   |



# FERULOK FITTINGS

---

| J&B # | PARKER # | TUBE O.D. | THREAD  | QTY |
|-------|----------|-----------|---------|-----|
| 55770 | 3 BU-S   | 3/16      | 3/8-24  | 1   |
| 55771 | 4 BU-S   | 1/4       | 7/16-20 | 1   |
| 55773 | 6 BU-S   | 3/8       | 9/16-18 | 1   |
| 55774 | 8 BU-S   | 1/2       | 3/4-16  | 1   |

**NUT  
(BU)**



| J&B # | PARKER # | TUBE O.D. | QTY |
|-------|----------|-----------|-----|
| 55780 | 3 TU-S   | 3/16      | 1   |
| 55781 | 4 TU-S   | 1/4       | 1   |
| 55783 | 6 TU-S   | 3/8       | 1   |
| 55784 | 8 TU-S   | 1/2       | 1   |

**FERRULE  
(TU)**



| J&B # | PARKER # | TUBE O.D. | TUBE ENDS | QTY |
|-------|----------|-----------|-----------|-----|
| 55790 | 3 HBU-S  | 3/16      | 3/8-24    | 1   |
| 55792 | 4 HBU-S  | 1/4       | 7/16-20   | 1   |
| 55794 | 6 HBU-S  | 3/8       | 9/16-18   | 1   |
| 55796 | 8 HBU-S  | 1/2       | 3/4-16    | 1   |

**UNION  
(HBU)**



| J&B # | PARKER # | JIC TUBE SIZE | TUBE END | QTY |
|-------|----------|---------------|----------|-----|
| 56516 | 4 XHU-S  | 1/4           | 7/16-20  | 1   |
| 56517 | 6 XHU-S  | 3/8           | 9/16-18  | 1   |
| 56518 | 8 XHU-S  | 1/2           | 3/4-16   | 1   |
| 56519 | 10 XHU-S | 5/8           | 7/8-14   | 1   |

**UNION ADAPTER  
SAE FLARELESS /  
37° FLARE**




# Hydraulic Quick Couplers

## 6100 Series

- Connect and disconnect under pressure.
- Use a threaded union connection.
- Have a connection indicator that shows when fully connected.
- Handles pressures up to 3000 psi.


| J&B #   | BODY SIZE | THREAD SIZE  | PARKER # | QTY |
|---------|-----------|--------------|----------|-----|
| ^56095  | 3/4       | 3/4-14       | 6125-12  | 1   |
| ^ 56090 | 1"        | 1-11 1/2     | 6125-16  | 1   |
| ^ 56091 | 1-1/4     | 1-1/4-11 1/2 | 6125-20  | 1   |

**WING NUT  
COUPLER**



| J&B #   | BODY SIZE | PIPE THREAD  | PARKER # | QTY |
|---------|-----------|--------------|----------|-----|
| ^56094  | 3/4       | 3/4-14       | 6105-12  | 1   |
| ^ 56092 | 1"        | 1-11 1/2     | 6105-16  | 1   |
| ^ 56093 | 1-1/4     | 1-1/4-11 1/2 | 6105-20  | 1   |

**FEMALE THREAD  
NIPPLE**



\* Numbers with a "^" are not necessarily stocked in large quantities.


# Hydraulic Quick Couplers

## 20 Series (Steel)

- Rated pressure 300 psi.
- Sleeve type couplers will interchange push-type couplers and other manufacturers' couplers which accept Industrial Interchange & nipples that conform to MIL-C4109.
- Temperature range is -40 F. to +250 F.
- Vacuum data 27.4Hg connected. Disconnected not recommended.


| J&B #   | BODY SIZE | PIPE THREAD | STEEL PARKER # | QTY |
|---------|-----------|-------------|----------------|-----|
| ^ 55551 | 1/4       | 1/4-18      | B23            | 1   |
| ^ 55555 | 3/8       | 3/8-18      | B25            | 1   |
| ^ 55556 | 1/2       | 1/2-14      | B17            | 1   |

**FEMALE THREAD COUPLER**




| J&B #   | BODY SIZE | PIPE THREAD | STEEL PARKER # | QTY |
|---------|-----------|-------------|----------------|-----|
| ^ 55540 | 1/4       | 1/4-18      | H3C            | 1   |
| ^ 55544 | 3/8       | 3/8-18      | H3E            | 1   |

**FEMALE THREAD NIPPLE**



| J&B #   | BODY SIZE | PIPE THREAD | STEEL PARKER # | QTY |
|---------|-----------|-------------|----------------|-----|
| ^ 55547 | 1/2       | 1/2-14      | 2F             | 1   |

**MALE THREAD NIPPLE**



\* Numbers withh a "^" are not necessarily stocked in large quantities.


# Hydraulic Quick Couplers

## 60 Series (Steel)

- Recommended where high cycle rates and pressure surges are encountered.
- "Industrial Interchange" design meets the dimensional requirements of Series B in ISO 7241-1.
- Temperature range is -40 F. to +250 F.
- Vacuum data 27.4Hg, both disconnected and connected


| J&B #   | BODY SIZE | PIPE THREAD | STEEL PARKER # | QTY |
|---------|-----------|-------------|----------------|-----|
| ^ 55510 | 1/4       | 1/4-18      | H2-62          | 1   |
| ^ 54618 | 3/8       | 3/8-18      | H3-62          | 1   |
| ^ 55520 | 1/2       | 1/2-14      | H4-62          | 1   |
| ^ 55530 | 3/4       | 3/4-14      | H6-62          | 1   |
| ^ 55531 | 1"        | 1-11-1/2    | H8-62          | 1   |

**FEMALE THREAD  
COUPLER**



| J&B #   | BODY SIZE | PIPE THREAD | STEEL PARKER # | QTY |
|---------|-----------|-------------|----------------|-----|
| ^ 55512 | 1/4       | 1/4-18      | H2-63          | 1   |
| ^ 54620 | 3/8       | 3/8-18      | H3-63          | 1   |
| ^ 55522 | 1/2       | 1/2-14      | H4-63          | 1   |
| ^ 55533 | 3/4       | 3/4-14      | H6-63          | 1   |
| ^55532  | 1"        | 1-11-1/2    | H8-63          | 1   |

**FEMALE THREAD  
NIPPLE**



\* Numbers with a "^" are not necessarily stocked in large quantities.



# Hydraulic Quick Couplers

---


## ADAPTERS

### 4000 Series (Steel)

- Plated to resist severe work and weather conditions.
  - Metal to metal seal provides **positive shut-off**.
  - Swivel action saves on hose twist wear.
  - Interchangeable with most "Economy" type couplers.
  - Temperature range -40 F. to +250 F.
  - Rated pressure 3000 psi.
- 

| J&B # | BODY SIZE | THREAD SIZE | STEEL PARKER # | QTY |
|-------|-----------|-------------|----------------|-----|
| 52691 | 1/4       | 1/4         | 4010-2         | 1   |
| 52687 | 3/8       | 3/8         | 4010-3         | 1   |
| 52689 | 1/2       | 1/2         | 8010-4         | 1   |


#### FEMALE THREAD NIPPLE



---

| J&B # | BODY SIZE | THREAD SIZE | STEEL PARKER # | QTY |
|-------|-----------|-------------|----------------|-----|
| 52690 | 1/4       | 1/4         | 4050-2         | 1   |
| 52686 | 3/8       | 3/8         | 4050-3         | 1   |
| 52688 | 1/2       | 1/2         | 4050-4         | 1   |

#### FEMALE THREAD COUPLER




# Hydraulic Quick Couplers

## FF Series (Steel)

- Operating pressure is 3000 psi.
- The 3/8" size conforms to HTMA (Hydraulic Tool Manufacturers Association) standards.
- All sizes incorporate **flush face** mating surfaces.

| J&B # | BODY SIZE | THREAD SIZE | PARKER PART # | QTY |
|-------|-----------|-------------|---------------|-----|
| 54610 | 3/8       | 3/8         | FF371-6FP     | 1   |
| 54614 | 3/8       | 1/2         | FF371-8FP     | 1   |
| 54611 | 1/2       | 1/2         | FF-501-8FP    | 1   |
| 54615 | 3/4       | 3/4         | FF751-12FP    | 1   |


FF SERIES  
COUPLER



**\* CAUTION:** These products are not to be used as swivels.  
Rotation under pressure will result in excessive and premature wear.

| J&B #   | BODY SIZE | THREAD SIZE | PARKER PART # | QTY |
|---------|-----------|-------------|---------------|-----|
| 54612   | 3/8       | 3/8         | FF372-6FP     | 1   |
| 54616   | 3/8       | 1/2         | FF372-8FP     | 1   |
| ^ 54613 | 1/2       | 1/2         | FC-502-8FP    | 1   |
| 54617   | 3/4       | 3/4         | FF752-12FP    | 1   |

FF SERIES  
NIPPLE



^ 54613 is a longer series.

**\* CAUTION:** These products are not to be used as swivels.  
Rotation under pressure will result in excessive and premature wear.

# HOSE ACCESSORIES

## PARTEK SLEEVE

- Parker's Partek Nylon Protective Sleeving gives you Tough hose abrasion protection.
- The weave gives an exceptionally smooth interior wall, allowing rubber hose to move freely inside the sleeve, providing easy installation and prevents any internal abrasion problems.
- Per the ISO 6945 specification, Partek has a unique tubular weave nylon construction strong enough to withstand greater than 200,000 abrasion cycles without wearing the fabric at any location.
- Temperature Range: -67 deg F to + 248 deg F (-53 deg C to +120 deg C).
- Color is **BLACK**.



| J&B # | INSIDE DIA. FLAT | INSIDE DIA. ROUND | SS25UL 201 | 285    | 302    | 426<br>351TC<br>451TC<br>471TC | 772TC | 782TC | 811<br>881 | PARKER # | QTY   |
|-------|------------------|-------------------|------------|--------|--------|--------------------------------|-------|-------|------------|----------|-------|
| 50100 | 1.07"            | 0.69"             | -4         | -4     |        | -3/-4                          |       |       |            | AS-B-11  | 50/FT |
| 50101 | 1.34"            | 0.86"             | -5/-6      | -5/-6  | -4/-5  | -5/-6                          |       |       |            | AS-B-13  | 50/FT |
| 50102 | 1.66"            | 1.06"             | -8         | -8/-10 | -6     | -8                             | -6    |       |            | AS-B-15  | 50/FT |
| 50103 | 1.92"            | 1.22"             | -10        | -12    | -8/-10 | -10                            | -8    |       |            | AS-B-17  | 50/FT |
| 50104 | 2.12"            | 1.35"             | -12        |        | -12    | -12                            | -10   | -8    |            | AS-B-19  | 50/FT |
| 50105 | 2.24"            | 1.42"             | -16        | -16    |        |                                | -12   | -10   | -12        | AS-B-22  | 50/FT |
| 50107 | 2.55"            | 1.63"             |            |        |        | -16                            |       | -12   |            | AS-B-27  | 50/FT |

**\*\*\* All sizes sold by the roll. Can break a roll and can be sold by the foot (must be in multiples of feet and cannot be broken down to inches).**

# HOSE ACCESSORIES

---

## STRAIN RELIEVERS

- Resistant to chemicals, weather and abrasion
- Excellent for pressure washer hoses.
- Reduces cracking at hose/fitting connection.

**\*Strain relief fits over hose & fitting**

| J&B # | SIZE | QTY |
|-------|------|-----|
| 38901 | 3/8  | 1   |
| 38902 | 1/2  | 1   |





**Strain relief**

# CAPPLUGS

## SERIES T TAPERED CAPPLUGS

- Tapered capplugs can be used as either **caps** or **plugs**.
- Because they are tapered in design and made from highly flexible Polyethylene, they cannot only be applied to fit **snugly** but are readily **removable**...whether used for capping or plugging.
- Especially recommended for use on MIL Std. and SAE-type tube and hydraulic fittings and for threaded external and internal N.P.T. fittings.



| J&B # | CAPPLUG # | QTY |
|-------|-----------|-----|
| 41800 | 1         | 25  |
| 41801 | 2         | 25  |
| 41802 | 2-x       | 25  |
| 41803 | 3         | 25  |
| 41804 | 3-x       | 25  |
| 41805 | 4         | 25  |
| 41806 | 4-x       | 25  |
| 41807 | 5         | 25  |
| 41808 | 6         | 25  |
| 41809 | 6-x       | 25  |
| 41810 | 7         | 25  |
| 41811 | 8         | 25  |
| 41812 | 8-x       | 25  |
| 41813 | 9         | 25  |
| 41814 | 9-x       | 25  |
| 41815 | 10        | 25  |

| J&B # | CAPPLUG # | QTY |
|-------|-----------|-----|
| 41816 | 11        | 25  |
| 41817 | 11-x      | 25  |
| 41818 | 12-x      | 10  |
| 41819 | 13        | 10  |
| 41820 | 13-x      | 10  |
| 41821 | 14        | 10  |
| 41822 | 14-x      | 10  |
| 41823 | 15-x      | 5   |
| 41824 | 16        | 5   |
| 41825 | 17        | 5   |
| 41826 | 17-s      | 5   |
| 41827 | 18        | 5   |
| 41828 | 19        | 5   |
| 41829 | 20        | 5   |
| 41830 | 20-s      | 5   |



Series T Tapered Capplugs


**\*Selection Charts are on page 797**

# CAPPLUGS

## SERIES T TAPERED CAPPLUGS


### Selection Charts

Recommended closures for tube and hydraulic fittings




| DASH # | TUBING O.D # | THREAD    | CAPLUG # AS PLUGS | CAPLUG # AS CAPS |
|--------|--------------|-----------|-------------------|------------------|
| -2     | 1/8          | 5/16-24   | 1                 | 2                |
| -3     | 3/16         | 3/8-24    | 2                 | 3-x              |
| -4     | 1/4          | 7/16-20   | 3                 | 4-x              |
| -5     | 5/16         | 1/2-20    | 4                 | 5                |
| -6     | 3/8          | 9/16      | 5                 | 6-x              |
| -6     | 3/8          | 5/8-18    | 6                 | 7                |
| -8     | 1/2          | 3/4-16    | 8                 | 9-x              |
| -10    | 5/8          | 7/8-14    | 10                | 11-x             |
| -12    | 3/4          | 1-1/16-12 | 12-x              | 13-x             |
| -16    | 1            | 1-5/16-12 | 14-x              | 15-x             |
| -20    | 1-1/4        | 1-5/8-12  | 17-s              | 18               |
| -24    | 1-1/2        | 1-7/8-12  | 19                | 20               |

Recommended closures for threaded external and internal N.P.T. fittings



| SIZE  | CAPLUG # AS PLUGS | CAPLUG # AS CAPS |
|-------|-------------------|------------------|
| 1/8   | 2-x               | 4                |
| 1/4   | 4                 | 6                |
| 3/8   | 6-x               | 8-x              |
| 1/2   | 9                 | 11               |
| 3/4   | 12-x              | 13-x             |
| 1     | 14                | 15-x             |
| 1-1/4 | 17-s              | 18               |
| 1-1/2 | 20-s              | 20               |

Recommended closures for unthreaded standard weight pipe




| SIZE  | CAPLUG # AS PLUGS | CAPLUG # AS CAPS |
|-------|-------------------|------------------|
| 1/8   | 1                 | 4                |
| 1/4   | 2-x               | 6-x              |
| 3/8   | 5                 | 8-x              |
| 1/2   | 7                 | 11               |
| 3/4   | 10                | 13-x             |
| 1     | 13                | 16               |
| 1-1/4 | 16                | 18-x             |
| 1-1/2 | 18                |                  |

# HOSE

## PRESSURE WASHER HOSE

- **Each hose is pre-assembled** with 50 feet of hose, a strain relief on each end, and a male pipe fitting on each end.
- Also available in custom lengths.



| J&B # | HOSE I.D. | PIPE THREAD | MAXIMUM WORKING PRESSURE (PSI) | MINIMUM BURST PRESSURE (PSI) | QTY  |
|-------|-----------|-------------|--------------------------------|------------------------------|------|
| 38905 | 3/8       | 3/8         | 2,250                          | 9,000                        | 1 EA |
| 38906 | 1/2       | 1/2         | 2,000                          | 8,000                        | 1 EA |



## J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

[www.jbfleet.com](http://www.jbfleet.com)



PART # 2114

## ADAPTERS SAE (JIC) 1/4 – 1/2



|                                                                                                                       |                                                                                                                                           |                                                                                                                                             |                                                                                                                                                   |                                                                                                                                                     |                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>54104</b><br>1/4 PLUG<br>3    | <br><b>54106</b><br>3/8 PLUG<br>3                        | <br><b>54108</b><br>1/2 PLUG<br>2                          | <br><b>54124</b><br>1/4 CAP<br>3                               | <br><b>54126</b><br>3/8 CAP<br>3                                 | <br><b>54128</b><br>1/2 CAP<br>2                               |
| <br><b>51406</b><br>1/2 UNION<br>1   | <br><b>51404</b><br>3/8 UNION<br>2                       | <br><b>52772</b><br>1/2 T X 3/8 P<br>MALE CONNECTOR<br>2   | <br><b>51374</b><br>1/2 T X 1/2 P<br>MALE CONNECTOR<br>2       | <br><b>51383</b><br>1/2 T X 3/8 P<br>90 MALE<br>CONNECTOR<br>1   | <br><b>51384</b><br>1/2 T X 1/2 P<br>90 MALE<br>CONNECTOR<br>1 |
| <br><b>51404</b><br>3/8 UNION<br>2   | <br><b>52770</b><br>3/8 T X 1/4 P<br>MALE CONNECTOR<br>2 | <br><b>51372</b><br>3/8 T X 3/8 P<br>MALE CONNECTOR<br>2 | <br><b>51381</b><br>3/8 T X 1/4 P<br>90 MALE<br>CONNECTOR<br>2 | <br><b>51382</b><br>3/8 T X 3/8 P<br>90 MALE<br>CONNECTOR<br>2   |                                                                                                                                                   |
| <br><b>51402</b><br>1/4 UNION<br>2 |                                                                                                                                           | <br><b>52769</b><br>1/4 T X 1/8 P<br>MALE CONNECTOR<br>2 | <br><b>51370</b><br>1/4 T X 1/4 P<br>MALE CONNECTOR<br>2     | <br><b>51380</b><br>1/4 T X 1/4 P<br>90 MALE<br>CONNECTOR<br>2 |                                                                                                                                                   |






PART # 2110



**J&B Fleet - Industrial Supply**  
22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

## ADAPTERS SAE (JIC) 5/8 – 1"

|                                                                                                                                                 |                                                                                                                                                 |                                                                                                                                                   |                                                                                                                                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>52775</b><br>5/8 TUBE X 1/2 PIPE<br>MALE CONNECTOR<br>2 | <br><b>52778</b><br>3/4 TUBE X 1/2 PIPE<br>MALE CONNECTOR<br>2 | <br><b>51376</b><br>3/4 TUBE X 3/4 PIPE<br>MALE CONNECTOR<br>1 | <br><b>51378</b><br>1" TUBE X 1" PIPE<br>MALE CONNECTOR<br>1      |
| <br><b>51407</b><br>5/8 UNION<br>2                             | <br><b>51408</b><br>3/4 UNION<br>2                             | <br><b>51410</b><br>1" UNION<br>1                              | <br><b>51395</b><br>1" TUBE X 1 PIPE<br>90 MALE CONNECTOR<br>1    |
| <br><b>54110</b><br>5/8 PLUG<br>2                              | <br><b>54112</b><br>3/4 PLUG<br>2                              | <br><b>54116</b><br>1" PLUG<br>2                               | <br><b>51386</b><br>3/4 TUBE X 3/4 PIPE<br>90 MALE CONNECTOR<br>1 |
| <br><b>54130</b><br>5/8 CAP<br>2                             | <br><b>54132</b><br>3/4 CAP<br>2                             | <br><b>54133</b><br>1" CAP<br>2                              | <br>16                                                                                                                                               |





## J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

[www.jbfleet.com](http://www.jbfleet.com)

**PART#2816**

### JIC PLUG & CAP

**54105 & 54125**



**#5  
5/16"  
37° FLARE  
PLUG & CAP**

2

2

**54110 & 54130**



**#10  
5/8"  
37° FLARE  
PLUG & CAP**

2

2

**54114 & 54131**



**#14  
7/8"  
37° FLARE  
PLUG & CAP**

2

2

**54118 & 54135**



**#20  
1-1/4"  
37° FLARE  
PLUG & CAP**

2

2

**54104 & 54124**



**#4  
1/4"  
37° FLARE  
PLUG & CAP**

2

2

**54108 & 54128**



**#8  
1/2"  
37° FLARE  
PLUG & CAP**

2

2

**54112 & 54132**



**#12  
3/4"  
37° FLARE  
PLUG & CAP**

2

2

**54116 & 54133**



**#16  
1"  
37° FLARE  
PLUG & CAP**

2

2

**54103 & 54123**



**#3  
3/16"  
37° FLARE  
PLUG & CAP**

2

2

**54106 & 54126**



**#6  
3/8"  
37° FLARE  
PLUG & CAP**

2




2

2

2

2

2



PART# 2815

# J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

















## HEX O-RING PLUG








|                                                                                         |                                                                                         |                                                                                            |                                                                                            |
|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <div>54642</div> <div></div> <div>#4<br/>7/16-20<br/>HEX O-RING PLUG</div> <div>4</div> | <div>54645</div> <div></div> <div>#8<br/>3/4-16<br/>HEX O-RING PLUG</div> <div>4</div>  | <div>54647</div> <div></div> <div>#12<br/>1-1/16-12<br/>HEX O-RING PLUG</div> <div>4</div> |                                                                                            |
| <div>54641</div> <div></div> <div>#3<br/>3/8-24<br/>HEX O-RING PLUG</div> <div>4</div>  | <div>54644</div> <div></div> <div>#6<br/>9/16-18<br/>HEX O-RING PLUG</div> <div>4</div> | <div>54646</div> <div></div> <div>#10<br/>7/8-14<br/>HEX O-RING PLUG</div> <div>4</div>    | <div>54648</div> <div></div> <div>#16<br/>1-5/16-12<br/>HEX O-RING PLUG</div> <div>2</div> |
| <div>54640</div> <div></div> <div>#2<br/>5/16-24<br/>HEX O-RING PLUG</div> <div>4</div> | <div>54643</div> <div></div> <div>#5<br/>1/2-20<br/>HEX O-RING PLUG</div> <div>4</div>  |                                                                                            |                                                                                            |







|                                                                                                                                                                                       |                                                                                                                                                                                         |                                                                                                                                                                                         |                                                                                                                                                                                         |                                                                                                                                                                                           |                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>53010</b> <sup>1</sup></p>  <p><b>1/4 TUBE OD<br/>M10 X 1 STRAIGHT</b></p> <p><sup>1</sup></p> | <p><b>53012</b> <sup>2</sup></p>  <p><b>3/8 TUBE OD<br/>M14 X 1.5 STRAIGHT</b></p> <p><sup>1</sup></p> | <p><b>53013</b> <sup>3</sup></p>  <p><b>1/2 TUBE OD<br/>M16 X 1.5 STRAIGHT</b></p> <p><sup>1</sup></p> | <p><b>53020</b> <sup>4</sup></p>  <p><b>1/4 TUBE OD<br/>M10 X 1 STRAIGHT</b></p> <p><sup>1</sup></p> | <p><b>53022</b> <sup>5</sup></p>  <p><b>3/8 TUBE OD<br/>M14 X 1.5 STRAIGHT</b></p> <p><sup>1</sup></p> | <p><b>53023</b></p>  <p><b>1/2 TUBE OD<br/>M16 X 1.5 STRAIGHT</b></p> <p><sup>1</sup></p>            |
| <p><b>53040</b> <sup>7</sup></p>  <p><b>1/4 TUBE OD<br/>1/8 BSPT PIPE</b></p> <p><sup>1</sup></p>    | <p><b>53041</b> <sup>8</sup></p>  <p><b>1/4 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p><sup>1</sup></p>      | <p><b>53044</b> <sup>9</sup></p>  <p><b>3/8 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p><sup>1</sup></p>      | <p><b>53045</b> <sup>10</sup></p>  <p><b>3/8 TUBE OD<br/>3/8 BSPT PIPE</b></p> <p><sup>1</sup></p>   | <p><b>53049</b> <sup>11</sup></p>  <p><b>1/2 TUBE OD<br/>1/2 BSPT PIPE</b></p> <p><sup>1</sup></p>     | <p><b>53060</b> <sup>12</sup></p>  <p><b>1/4 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p><sup>1</sup></p>   |
| <p><b>53063</b> <sup>13</sup></p>  <p><b>3/8 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p><sup>1</sup></p>   | <p><b>53064</b> <sup>14</sup></p>  <p><b>3/8 TUBE OD<br/>3/8 BSPT PIPE</b></p> <p><sup>1</sup></p>     | <p><b>53068</b> <sup>15</sup></p>  <p><b>1/2 TUBE OD<br/>1/2 BSPT PIPE</b></p> <p><sup>1</sup></p>     | <p><b>52970</b> <sup>16</sup></p>  <p><b>1/4 TUBE OD<br/>1/8 BSPP PIPE</b></p> <p><sup>1</sup></p>   | <p><b>52971</b> <sup>17</sup></p>  <p><b>1/4 TUBE OD<br/>1/4 BSPP PIPE</b></p> <p><sup>1</sup></p>     | <p><b>52976</b> <sup>18</sup></p>  <p><b>3/8 TUBE OD<br/>1/4 BSPP PIPE</b></p> <p><sup>1</sup></p>   |
| <p><b>52977</b> <sup>19</sup></p>  <p><b>3/8 TUBE OD<br/>3/8 BSPP PIPE</b></p> <p><sup>1</sup></p> | <p><b>52980</b> <sup>20</sup></p>  <p><b>1/2 TUBE OD 1/2<br/>BSPP PIPE</b></p> <p><sup>1</sup></p>   | <p><b>52985</b> <sup>21</sup></p>  <p><b>1/4 TUBE OD<br/>1/4 BSPP PIPE</b></p> <p><sup>1</sup></p>   | <p><b>52987</b> <sup>22</sup></p>  <p><b>3/8 TUBE OD<br/>1/4 BSPP PIPE</b></p> <p><sup>1</sup></p> | <p><b>52988</b> <sup>23</sup></p>  <p><b>3/8 TUBE OD<br/>3/8 BSPP PIPE</b></p> <p><sup>1</sup></p>   | <p><b>52991</b> <sup>24</sup></p>  <p><b>1/2 TUBE OD<br/>1/2 BSPP PIPE</b></p> <p><sup>1</sup></p> |



## J&B Fleet - Industrial Supply


22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

[www.jbfleet.com](http://www.jbfleet.com)

PART # 2117

## METRIC HYDRAULIC ADAPTERS

|                                                                               |                                                                                 |    |                                                                             |                                                                             |                                                                             |
|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------|----|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <p><b>53010</b> 1</p> <p><b>1/4 TUBE OD<br/>M10 X 1 STRAIGHT</b></p> <p>1</p> | <p><b>53012</b> 2</p> <p><b>3/8 TUBE OD<br/>M14 X 1.5 STRAIGHT</b></p> <p>1</p> | 3  | 4                                                                           | 5                                                                           | 6                                                                           |
| 7                                                                             | <p><b>53041</b> 8</p> <p><b>1/4 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p>1</p>      | 9  | <p><b>53045</b> 10</p> <p><b>3/8 TUBE OD<br/>3/8 BSPT PIPE</b></p> <p>1</p> | 11                                                                          | <p><b>53060</b> 12</p> <p><b>1/4 TUBE OD<br/>1/4 BSPT PIPE</b></p> <p>1</p> |
| 13                                                                            | <p><b>53064</b> 14</p> <p><b>3/8 TUBE OD<br/>3/8 BSPT PIPE</b></p> <p>1</p>     | 15 | 16                                                                          | <p><b>52971</b> 17</p> <p><b>1/4 TUBE OD<br/>1/4 BSP9 PIPE</b></p> <p>1</p> | 18                                                                          |
| <p><b>52977</b> 19</p> <p><b>3/8 TUBE OD<br/>3/8 BSPP PIPE</b></p> <p>1</p>   | 20                                                                              | 21 | 22                                                                          | 23                                                                          | 24                                                                          |






## J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

[www.jbfleet.com](http://www.jbfleet.com)

PART # 2121

### CAP PLUGS



|                                                                                                                                      |                                                                                                                                       |                                                                                                                                        |                                                                                                                                       |                                                                                                                                        |                                                                                                                                        |                                                                                                                                          |                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>41800</b> <sup>1</sup><br><br><b>#1</b><br>10    | <b>41801</b> <sup>2</sup><br><br><b>#2</b><br>10     | <b>41802</b> <sup>3</sup><br><br><b>#2-X</b><br>10    | <b>41803</b> <sup>4</sup><br><br><b>#3</b><br>10    | <b>41804</b> <sup>5</sup><br><br><b>#3-X</b><br>10  | <b>41805</b> <sup>6</sup><br><br><b>#4</b><br>10    | <b>41806</b> <sup>7</sup><br><br><b>#4-X</b><br>10    | <b>41807</b> <sup>8</sup><br><br><b>#5</b><br>10    |
| <b>41808</b> <sup>9</sup><br><br><b>#6</b><br>10    | <b>41809</b> <sup>10</sup><br><br><b>#6-X</b><br>10  | <b>41810</b> <sup>11</sup><br><br><b>#7</b><br>10     | <b>41811</b> <sup>12</sup><br><br><b>#8</b><br>10   | <b>41812</b> <sup>13</sup><br><br><b>#8-X</b><br>10 | <b>41813</b> <sup>14</sup><br><br><b>#9</b><br>10   | <b>41814</b> <sup>15</sup><br><br><b>#9-X</b><br>10   | <b>41815</b> <sup>16</sup><br><br><b>#10</b><br>10  |
| <b>41816</b> <sup>17</sup><br><br><b>#11</b><br>10  | <b>41817</b> <sup>18</sup><br><br><b>#11-X</b><br>10 | <b>41818</b> <sup>19</sup><br><br><b>#12-X</b><br>5   | <b>41819</b> <sup>20</sup><br><br><b>#13</b><br>5   | <b>41820</b> <sup>21</sup><br><br><b>#13-X</b><br>5 | <b>41821</b> <sup>22</sup><br><br><b>#14</b><br>5   | <b>41822</b> <sup>23</sup><br><br><b>#14-X</b><br>5   | <b>41823</b> <sup>24</sup><br><br><b>#15-X</b><br>2 |
| <b>41824</b> <sup>25</sup><br><br><b>#16</b><br>2 | <b>41825</b> <sup>26</sup><br><br><b>#17</b><br>2  | <b>41826</b> <sup>27</sup><br><br><b>#17-S</b><br>2 | <b>41827</b> <sup>28</sup><br><br><b>#18</b><br>2 | <b>41828</b> <sup>29</sup><br><br><b>#19</b><br>2 | <b>41829</b> <sup>30</sup><br><br><b>#20</b><br>2 | <b>41830</b> <sup>31</sup><br><br><b>#20-S</b><br>2 | <b>41831</b> <sup>32</sup><br><br><b>#21</b><br>2 |