

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Steelwalk

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Floor Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Distressed Steel	Number of Faces/Screens:	24x24 (14), 12x24 (28)
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.1	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	0.52
Scratch Hardness (MOHS)	8	Breaking Strength:	40+55 N/nm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	ISO-10545-13		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.28	Pieces per Carton:	4
SqFt per Pallet:	458.40	Pounds per Carton:	67.69
Boxes per Pallet:	30	SqFt per Container:	15.28
Pallets per Container:	28		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".