

7 mph Farm Class Rules

- 2 WD Rubber tires only – No cut tires – Radials allowed
- 6500 to 8500 lbs classes are 18.4 X 38 tire size max
- 9500 lbs and up are any tire size
- Wheelie bars recommended
- Hitch is 20" (6500-9500 lbs) and 22" (10500 lbs & up) high max and no shorter than 18" from the center of the rear axle to the hooking point. Hitch hole is to be stationary in all directions.
- No excessive stripping – Judges decision is final
- Stock appearing engine blocks with stock appearing injection pump in stock location
- No frame modification to make engine fit in the tractor
- No down draft carburetors. Single barrel carburetors only
- Pusher fuel pumps allowed electric or gear driven
- Fuel limited to gas, LP, or diesel only. (Subject to random check) No extra injected fuels (LP added to Diesel engines – No nitrous oxide added to gasoline engines)
- No water injection
- OEM intercoolers allowed
- Exhaust pipes need to be straight – or curved exhaust pipes after muffler
- Weld on hubs optional
- Working brakes
- No homemade wide front ends. OEM or Swartz only! Factory OEM narrow front allowed
- Front weights no further forward than 13 foot from the center of the rear axle
- Rear weights to be mounted so the hitch is not blocked and easily accessible