



#	Item	Pilot Door Systems Inc.	
1	Brackets	Flat Bracket, assembled to door at plant. 12 ga Steel with galvanized finish. Spring tension safety latch attached to spring side only.	
2	Track/Guide	At top there is a lead in plastic clip. Lock hole only on the left hand track. 18 ga. Galvanized steel.	

3	Panel Profile	Radial Profile panel. 19" wide. 28 ga. Steel. Panel is attached to axel drums with 3 tek screws.
---	---------------	--



--	--	--

4	Axel Drums	Circular Drum. 18 ga. Galvanized steel with continuous circular weld. 3 Drums on doors 8' or larger
---	------------	---



--	--	--

5	Head Stops	Attached to the track with 1/4"-20 Carriage bolt. 12 ga. Galvanized steel.
---	------------	--



--	--	--

6	Tension System	Slick tension star with safety latch on spring side bracket only. Comes with click tension wrench and thum screw for securing after tensioning.
---	----------------	---



--	--	--

7	Bottom Edge	Made from an aluminum extrusion and 1/8" x 1 1/2" x 1 1/2" structural angle. Seamed to the bottom panel of door.
---	-------------	--



8	Weather Stripping	Round tubing. Doesn't twist or get mangled when door is closed.
---	-------------------	---




9	Locks	12 ga. Zinc plated punched steel with capacity for two pad locks
---	-------	--



10	Handle	Galvanized steel handle with Carriage bolts. Located center of the door's bottom edge.
----	--------	--



11	Warning Sticker	Located on the bottom left side of the inside of the door. Orange sticker which is basic and easy to understand.	
12	Instructions	Installation instruction sheets come with door but are not attached.	

13	Felt Tape	Short and thick felt tape. Runs down the inside of the door on the two outside drums. Also covers lock bolts and nuts, screws attaching panel to axel, and the bottom edge angle.
----	-----------	---



--	--	--

14	Bearings	Polyester Moulded bearings, self lubricating, with over 13" of contact surface. 12 ga. Galvanized steel star plate attached. Attached to spring on axel.
----	----------	--



--	--	--

15	Springs	2 Springs if door is over 8' wide. Spring is Coated
----	---------	--



16	Ropes	Black Nylon Rope 3'-5' long.
----	-------	------------------------------

