



2813 Belair Road • Suite 307 • Fallston, MD 21047
 Phone: 410-877-0033 • Fax: 410-877-3177
 www.xpressflooring.com

Quarry-Tek vs. the Competition

	Quarry-Tek	Quarry-Quartz	Standard Epoxy Floors
Installation Time <i>(Based on 1000 sq ft)</i>	1 day completion is possible	3 day minimum	2-3 day minimum
Description	Seamless, 3/16" thick, can include continuous cove base	Seamless, 1/8" thick, can include continuous cove base	Seamless, 1/2" - 3/16" thick, can include continuous cove base
Durability	Most durable due to composition & thickness	Good for foot traffic	Most durable due to composition & thickness
Preparation	Just need a clean, 60 degree dry floor	Just need a clean, 60 degree dry floor	Same & additionally the surface must be prepped using "shot blasting" causing enormous dust
Appearance	Thick enough to hide some imperfections in substrate Additional steps in preparation can assist in disguising some defects & imperfections Easily include a Company Logo	Too thin to hide imperfections in substrate Additional steps in preparation can assist in disguising some defects & imperfections Easily include a Company Logo	Thick enough to hide some imperfections in substrate Additional steps in preparation can assist in disguising some defects & imperfections Easily include a Company Logo
Pricing	Starts @ approx. \$9.50/sf	Starts @ approx. \$9.50/sf	Starts @ approx. \$9.50/sf

(QTCOMPARE-021114)