

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

NAME	SERIES	ROCK
------	--------	------

TECHNICAL CHARACTERISTICS			
Available Formats:	3X15 Ledger Field Tile		
Style Description:	Stone Quartz Look	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:		Number of Faces/Screens:	54
Thickness in mm:	120	Number of Punches/Molds:	3
Modular Suitability:		Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	2MM

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	0.2	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	N/A
Scratch Hardness (MOHS)	8	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

PACKING INFORMATION <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:		Pieces per Carton:	26
SqFt per Pallet:		Pounds per Carton:	
Boxes per Pallet:	70	SqFt per Container:	
Pallets per Container:	N/A		

**Note:**

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".