

# TSA72

- 50GHz SOLUTIONS
- SUPER LOW LOSS
- DOUBLE SHIELDED
- KINK RESISTANT
- EASY TIGHT COUPLING



## TESTeLINK RF Cables



Professional High Frequency RF Test Cables.

2.4mm, 2.92mm(K), and 3.5mm Interfaces.

Key Features;

- Easy Tight Finger Coupling
- Kink Resistant Cable Construction
- Super Low Loss <1.04db/ft @ 50GHz
- Low VSWR < 1.35:1 (Typical < 1.20:1)
- RF Leakage >-100dB to 18GHz
- High Power 55W @ 50GHz

### Configuration Chart

TSA72-D1D1-S18

TSA72-YYZZ-YYY

**YYZZ = Connector Options**  
2.4mm Male (50GHz) = C1  
2.4mm Female (50GHz) = CF  
2.92mm Male (40GHz) = D1  
2.92mm Female (40GHz) = DF  
3.5mm Male (32GHz) = E1  
3.5mm Female (32GHz) = EF

**YYY = Length Options**  
FYY = Length in Feet(F06 = 6ft)  
SYY = Length in Inches(S18 = 18")  
YMY = Length in Meters(2M5 = 2.5m)  
CYY = Length in Centimeters(C30 = 30cm)

## TESTeLINK RF Cables