

## AC OR DC V.T. CONTROL



## Standard Features

- Available in Single & Three Phase Inputs (110VAC-690VAC 50/60HZ)
- Available in & Three Phase Outputs (110VAC-690VAC 50/60HZ)
- Up to 500kW!!
- ≤ 5% Ripple on all DC Output Models (optional filter resulting in <5% available)
- Over Current Protection
- Circuit Breakers are standard on most models
- Linear and step-less control throughout the output range
- Air or Water Cooled
- Manual or Motorized
- Self-Contained or Remote Controlled (remote on motorized only)
- All of our power supplies are designed for continuous duty at 40° C (high temp packages available)
- Custom and Modular Designs available

## Options

- Constant Current and Constant Voltage Control/Regulation
- Amp Hour/Minute/Second Meter (pump control optional)
- Digital Meters (IP65 Rating. Accuracy is 1% or better)
- Set-point Meter
- Motorized Control
- Cut-Off Timer
- Alarm
- PLC Interface (0-5VDC, 0-10VDC, 4-20mA)
- PLC Start/Stop
- Custom Dry Contacts
- Periodic Reversing (Manual or Automatic)
- Filter Choke (reduce AC ripple)
- Data Logging
- Protection Grade up to NEMA 4X
- We welcome all custom controls!



Phone: (708) 547-5663 Fax: (708) 547-5738 Email: sales@aldonex.com Factory Location: 2917 St. Charles Rd. Bellwood, IL 60104

Mailing Address: P.O. Box 148 Bellwood, IL 60104

