

# NEO XL-Series Family

Automated tape libraries deliver the ultimate in flexible, cost-effective backup, archive and disaster recovery



Keeping pace with today's incredible data growth rates is a significant challenge for IT professionals, especially when it comes to protecting that data seamlessly and affordably. The NEO XL-Series addresses the need for midrange and enterprise businesses to do more with less by providing effortless automated backup that combines flexibility, density, high-performance and affordability to ensure that data is protected faster, smarter, easier and more cost effectively.

## Features

### NEOxl 60 Highlights

- Capacity ranging from 90TB to 375TB
- Data transfer rates ranging from 504 GB/hr. to 4.3TB/hr.
- 6u form factor
- Scales up to 560 slots and 42 tape drives
- Removable cartridge magazines
- Support for Overland Storage LTFs solutions

### NEOxl 80 Highlights

- Capacity ranging from 120TB to 500TB
- Data transfer rates ranging from 504 GB/hr. to 8.6TB/hr.
- 6u form factor
- Scales up to 560 slots and 42 tape drives
- Removable cartridge magazines
- Support for Overland Storage LTFs solutions



#### **Flexibility – Grow into, not out of, your storage**

The scalable design of the NEO XL-Series allows customers to customize their backup and archive solution by starting out as a 6u, 60-slot, single-drive library and scaling to as many as 560 slots and 42 tape drives. The seamless design of NEOxl libraries allows you to add both data cartridges and tape drives as you scale, instead of requiring you to choose between capacity or performance.

Effortless expansion of your NEO XL-Series library occurs by simply connecting additional 6u modules, with a maximum of 7 modules in a standard 42" rack. Installation and configuration of additional modules is simplified with the use of either the web-based remote management interface or the touch-screen operator control panel.

The scalable design of NEOxl libraries not only allows users to easily scale the library into a larger configuration, but it also enables simplified redeployment of individual modules into smaller applications. This flexibility makes NEO XL-Series the most ideal, most cost-effective solution for any midrange or enterprise environment.



#### **Simplicity – Minimize administrative overhead**

NEO XL-Series libraries provide convenient, simplified installation, setup and operation with a touch-screen operator control panel or web-based remote management. Removable cartridge magazines facilitate the loading, unloading and off-line storage of data cartridges, reducing media handling costs. Meanwhile, mail slots provide easy, secure access to individual tape cartridges without interrupting library operations, while NEOxl tape drives are easily added, removed or replaced to ensure effortless upgradeability and serviceability.



#### **Affordability – Get the best return on your investment**

NEO XL-Series libraries are designed to not only provide an affordable purchase price, but to deliver superior long-term cost of ownership. NEO XL-Series ease-of-use features and enterprise-class reliability ensure administrative, support and downtime costs are virtually eliminated, while the native partitioning functionality provides the ability to utilize a single library in a variety of applications.



#### **Dependability – Backup and archive you can count on**

NEO XL-Series libraries provide the reliability required by today's demanding IT environments to ensure that your data is readily accessible and always available. Features such as redundant power provide access to your data in the event of a power disruption, while easily replaceable tape drives and tape library modules ensure seamless reconfiguration should a support event occur and require replacement.

All NEO XL-Series libraries are covered by a standard one-year, next business day onsite warranty. For customers requiring a higher level of onsite support, customers may upgrade to enhanced next-business day support or 24x7x4 hr response times for the most mission critical operations.

NEO XL-Series tape libraries provide the ultimate in automated data backup, archiving and disaster recovery by delivering the flexibility, affordability and dependability required for midrange and enterprise-class operations.

# NEO XL-Series Family

## Specifications

CONFIGURATION	NEOxl 60		NEOxl 80		NEOxl Expansion	
# of cartridge slots	60		80		80	
# of mail slots	Up to 10		Up to 10		Up to 10	
# of tape drives	Up to 3 HH		Up to 6 HH		Up to 6 HH	
Tape drive types supported	LTO5 SAS/FC, LTO6 SAS/FC		LTO5 SAS/FC, LTO6 SAS/FC		LTO5 SAS/FC, LTO6 SAS/FC	
max. # of modules supported	1 base + 6 expansions		1 base + 6 expansions		1 base + 6 expansions	
max. # of cartridge slots*	560		560		n/a	
max. # of tape drives*	Up to 42 HH		Up to 42 HH		n/a	
<b>CAPACITY (native/compressed)</b>	<b>LTO6</b>	<b>LTO5</b>	<b>LTO6</b>	<b>LTO5</b>	<b>LTO6</b>	<b>LTO5</b>
max. native capacity per module	150 TB	90 TB	200 TB	120 TB	200 TB	120 TB
max. compressed capacity per module	375 TB	180 TB	500 TB	240 TB	500 TB	240 TB
max. native capacity - fully scaled	1.1 PB	630 TB	1.4 PB	840 TB	n/a	n/a
max. compressed capacity - fully scaled	2.6 PB	1.3 PB	3.5 PB	1.7 PB	n/a	n/a
<b>PERFORMANCE (native/compressed)</b>						
max. native data transfer rate per module	1.7 TB/hr.	1.5 TB/hr.	3.5 TB/hr.	3.0 TB/hr.	3.5 TB/hr.	3.0 TB/hr.
max. compressed data transfer rate per module	4.3 TB/hr.	3.0 TB/hr.	8.6 TB/hr.	6.0 TB/hr.	8.6 TB/hr.	6.0 TB/hr.
max. native data transfer rate - fully scaled	12.1 TB/hr.	10.6 TB/hr.	24.2 TB/hr.	21.2 TB/hr.	n/a	n/a
max. compressed data transfer rate - fully scaled	30.2 TB/hr.	21.2 TB/hr.	60.5 TB/hr.	42.3 TB/hr.	n/a	n/a
	<b>LTO6</b>	<b>LTO5</b>	<b>LTO6</b>	<b>LTO5</b>	<b>LTO6</b>	<b>LTO5</b>
<b>INTERFACES</b>	6 Gb SAS 8 Gb FC		6 Gb SAS 8 Gb FC		6 Gb SAS 8 Gb FC	
<b>DIMENSIONS</b>						
H x W x D	10.6" x 18.7" x 35.1" 268mm x 475mm x 892mm		10.6" x 18.7" x 35.1" 268mm x 475mm x 892mm		10.6" x 18.7" x 35.1" 268mm x 475mm x 892mm	
Rack height	6u per module; 42u max.		6u per module; 42u max.		6u per module; 42u max.	
Weight (packaged)	121 lbs. / 54.5 Kg		121 lbs. / 54.5 Kg		100 lbs. / 50.0 Kg	
<b>RELIABILITY</b>						
MCBF (mean cycles between failures)	>2,000,000		>2,000,000		>2,000,000	
MTTR (mean time to repair)	<10 minutes		<10 minutes		<10 minutes	
<b>ENVIRONMENTAL</b>						
Operating temperature	5° to 40°C		5° to 40°C		5° to 40°C	
Operating humidity	10% to 80% RH non-condensing		10% to 80% RH non-condensing		10% to 80% RH non-condensing	
Voltage/Frequency	100 - 240 V; 50/60 Hz		100 - 240 V; 50/60 Hz		100 - 240 V; 50/60 Hz	
Power	350 watts		350 watts		350 watts	

## Sales Offices

**North America**  
125 S. Market Street  
San Jose, CA 95113  
USA  
Tel: (858) 571-5555

**Asia Pacific**  
16 New Industrial Road #04-04  
Hudson TechnoCentre  
Singapore, 536204  
Tel: +65 62811 778

**France**  
18 Rue Jean Rostand  
Orsay  
91400, France  
Tel: +33 1 81 91 73 40

**Germany**  
Wilhelm Wagenfeld Straße 28  
80807 München  
Germany  
Tel: +49 89 329 890 800

**United Kingdom**  
Ashville Way  
Wokingham, Berkshire  
RG41 2PL England  
Tel: +44 1 189 898 000



©2014 Overland Storage. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Overland Storage shall not be liable for technical or editorial errors or omissions contained herein.

DS-NEOXL-1014-01