



International Wholesale Tile, LLC

EcoLux Plus - Technical Specifications

Description: Luxury Engineered Vinyl Plank, Floating Floor with Attached IXPE Pad

Warranty: Limited Lifetime Residential Wear Warranty
Limited Lifetime Waterproof Warranty
Limited Lifetime Structural Warranty
5 Year Limited Light Commercial Warranty for EcoLux Plus

Installation: Unilin Angle/Angle Click - Float or Glue Down

Construction: Stone Core Composite (70% Limestone, 30% virgin PVC)
EcoLux Plus - 12 mil wear layer – 3.5mm core + 1mm attached pad
Painted-V Bevel Edge

Size/Packing: EcoLux Plus - 7.25” x 48” x 4.5mm Plank
28.97 sf/box, 12 planks/box, 1593.35 sf/pallet, 55 boxes/pallet

Wear Finish: 2 layered Ceramic Bead, Aluminum Oxide Finish with Antimicrobial surface

TEST DATA

ASTM – E492-09 Impact Insulation Class :	call PM Bill Behr for info
ASTM – E90-09 Airbourne Sound Conduction:	call PM Bill Behr for info
ANSI A137.1 Dynamic Coefficient of Friction Test	0.52 DCOF
ASTM F-970-07 Static Load Limit:	0.00 inches (250psi)
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Delta E Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Delta E Requirement
ASTM F 1914 Residual Indentation	.002 inches (140psi)