

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MOLTEN

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Wood Plank	Number of Faces/Screens:	18-20
Thickness in mm:	8.5	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Flat
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	<
Chemical Resistance:	Yes		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.13	Pieces per Carton:	9
SqFt per Pallet:	630.24	Pounds per Carton:	55.00
Boxes per Pallet:	48	SqFt per Container:	1166.34 (Based on 24.5 tons)
Pallets per Container:	20		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".