

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	COVER
------	--------	-------

TECHNICAL CHARACTERISTICS			
Available Formats:	8X48		
Style Description:	Wood Plank	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	11.5mm	Number of Punches/Molds:	3
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	Pre consumer >31%	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	≥3mm

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	0.002	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	0.48
Scratch Hardness (MOHS)	5	Breaking Strength:	R>40 N/mm ² S>1500 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Pass
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	GLA-GHA		

PACKING INFORMATION - <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:		Pieces per Carton:	
SqFt per Pallet:		Pounds per Carton:	
Boxes per Pallet:		SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".