



CLARITY | INNOVATION | VISION

STA-9604/STA-9608/STA-9616



4/8/16ch stand-alone Full HD display DVR
Mac & Windows 100% compatible CMS
iPhone, iPad, Android support
PTZ control
e-SATA Support (8/16ch only)
3TB HDD support

Item		STA-9604	STA-9608	STA-9616
Video input	No. of channel	4ch BNC	8ch BNC	16ch BNC
Video output	Monitor	1ch HDMI, Spot (multi screen), 1ch VGA		
Multitasking		Quadplex		
Recording	Resolution	960×480, 704×480, 704×240,352×240(NTSC) 960×576, 704×576,704×288,352×288(PAL)		
	Max. speed	120fps at WD1 (NTSC) 100fps at WD1 (PAL)	240fps at WD1 (NTSC) 200fps at WD1 (PAL)	480fps at WD1 (NTSC) 400fps at WD1 (PAL)
	Mode	Schedule, Event(Sensor, Motion Detection), Manual, Continuous, Continuous+Event		
Display	Resolution	1024*768, 1280*720, 1280*1024, 1600*900, 1920*1080		
Search	Mode	Quick, Calendar, Bookmark, Event (Sensor, Motion Detection), USB		
Playback	Speed	×1,×2,×4,×8,×16,×32,×64,×128,×256,field by field (forward, backward) ×1/4, ×1/2 Slow Motion (forward only), repeat A-B		
Sensor input		4 (NO/NC selectable)	8 (NO/NC selectable)	
Alarm output(Relay)		1 Relay output		
Network	Speed & Type	10/100M (Static, DHCP, E-mail), UPNP, DDNS server available		
	Codec	Dual codec. (H.264)		
	Bandwidth limit	Yes		
Storage	SATA	Internal HDD 2EA	Internal HDD 2EA or Internal HDD 1EA + e-SATA 1EA	
	e-SATA	N/A		
Backup		USB flash memory, network		
Password protection		1 admin + 100 users		
Interface	PTZ control	RS-485		
	Serial port	N/A	RS-232	
S/W upgrade		Network, USB flash memory		
Power source & consumption		+ 12VDC/4A adaptor (100 –240VAC, 50Hz/60Hz, 60W)		
Dimension (mm)		320(W) × 340(D) × 70(H)		