

ACRA FM-2V Turret Milling Machine

SPECIFICATION

- 3 Axis Digital Read Out
- Power Air Draw Bar
- Power Feeds X And Y
- Table – 230 X 1244mm
- Longitudinal Travel – 750mm
- Cross Travel – 305mm
- Vertical Travel (Knee) – 305mm
- Table T Slots (3) 16mm
- Max Work Piece Weight 340kg
- Vertical Spindle Motor 3HP
- Spindle Speeds 50-3750rpm
- Spindle Taper – R8
- Spindle Nose To Table – 42-469mm
- Quill Travel 127mm
- Automatic Vertical Feeds (Per Rev) – 0.04, 0.08, 0.14mm
- Head Swivel – (Left & Right) 90deg, (Front To Back) 45deg
- Sound Pressure Level – Below 80db
- Weight 900kgs
- Floor Space (LxWxH) 2197 X 2000 X 2600mm



STANDARD FEATURES

- 3 Axis Digital Read Out
- Powered Air Draw Bar
- Auto Lubrication System
- Interlocked Chuck Guard
- Powered Feeds X and Y
- Coolant
- Lo-Vo Lamp
- Tools, Toolbox and Operation Manual
- Precision Hardened And Ground Table With Turcite
- Quill Is Precision Hardened And Chrome Plated
- Tables Are Hardened And Ground
- T Slotted Table
- Ground Ram Slide Ways
- Ground And Hardened Column Slide Ways
- Built in Coolant Tank In Base Of Machine

TOOLING OPTIONS



K Type Precision Vice



Semi Universal Dividing Head



Rotary Table HV-6