

CONCRETECH

Nature Cure & Seal
VOC 350

PRODUCT DESCRIPTION

Concretech Nature Cure & Seal is VOC Compliant, quality, abrasion resistant, durable, solvent based cure and seal for concrete curing and sealing, protection and highlighting color. Nature Cure & Seal provides high colour darkening and high gloss. Nature Cure & Seal uses the most advanced VOC exempt solvents to slow drying time and provide the most user friendly products.

USES

For use on all interior and exterior concrete, stamped concrete, exposed aggregate, colored and flat work concrete for both curing and sealing of the concrete structure. Nature Cure & Seal leaves a high gloss finish.

PACKAGING

Nature Cure and Seal is ready to use and is available in 3.78 L /1 Gal, 18.9 L /5 Gal. and 207.9 L /55 Gal. containers.

LIMITATIONS

Do not apply when temperature is below 7 C (45 F) or above 25C (75 F). Precaution should be taken to condition materials in hot and windy conditions.

INSTALLATION INSTRUCTIONS

Protect all surfaces that are not intended to receive cure and seal. Protect vegetation and landscaping. Finish all touch up work, detailing, cleaning and surface coloration. Apply Concretech Nature Cure & Seal with pump up airless sprayer ensuring a continuous membrane immediately after the surface sheen has disappeared. Do not leave excess Cure and Seal in joints, grout lines or low spots. Contractors must use a sprayer designed for use with solvents. Other equipment may explode or fail, resulting in harm to persons or surrounding surfaces.

STORAGE

Store away from heat source, open flame or spark. Nature Cure & Seal is flammable. Store in cool dry area out of direct sunlight. Shelf life under normal conditions is two years. Store in sealed containers and ventilated areas only. Prevent contact with all sources of ignition, heat, spark and electric tools. Wear protective clothing, rubber gloves and eye protection. Prolonged exposure may result in respiratory illness, dizziness or damage to the nervous system. Contractor shall abide by all agency regulations for application, use, storage and disposal of solvent based materials. Keep away from children.

PROPERTIES

Color: Clear
Dry Time: 25-55 minutes
(depending on ambient temperature)

Coverage: Apply at 225 – 250 sqft/gal
VOC Concentration: < 350 grams per litre

SAFETY PRECAUTIONS

First Aid: Flush contaminated areas immediately and seek medical attention. Remove contaminated clothing. Wash hands with soap and water. Flush eyes with clean water or eye wash solution.

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1

www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel: 1.604.210.1147