

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	ALBA STONE
------	--------	------------

TECHNICAL CHARACTERISTICS			
Available Formats:	13x22	Glaze Application Method:	HDIT Inkjet
Style Description:	Marble Look	Number of Faces/Screens:	8
Visual Characteristics:	Basic Colors with White Veins	Number of Punches/Molds:	1
Thickness in mm:	7.4 mm	Body Type:	Ceramic
Modular Suitability:	No	Color Body Unglazed:	Red
Application:	Residential	Surface Type:	Matte/Flat
Recycled Content: Post or Pre Customer	40%	Recommended Grout Joint:	4 mm
Rectified:	Pressed		

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	6%- 8%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>700 N
Frost Resistant:	No	Thermal Shock Resistance:	No
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

PACKING INFORMATION			
SqFt per Carton:	21.85	Pieces per Carton:	11
SqFt per Pallet:	874.00	Pounds per SqFt:	3.02 lbs
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	21.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".