

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**MAXIWOOD**

## TECHNICAL CHARACTERISTICS

|   |                         |                           |                    |
|---|-------------------------|---------------------------|--------------------|
| Available Formats:                        | 9x36, 6x36, 24x24 Decos |                           |                    |
| Style Description:                        | Polished                | Glaze Application Method: | HDIT Inkjet        |
| Visual Characteristics:                   | Wood                    | Number of Faces/Screens:  | 6x36: 30; 9x36: 20 |
| Thickness in mm:                          | 10.85                   | Number of Punches/Molds:  | 1                  |
| Modular Suitability:                      | Yes                     | Body Type:                | Porcelain (<.5%)   |
| Application:                              | Residential/Commercial  | Color Body Unglazed:      | No                 |
| Recycled Content:<br>Post or Pre Customer | N/A                     | Surface Type:             | Polished/Glossy    |
| Rectified:                                | Yes                     | Recommended Grout Joint:  | No less than 1/8"  |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |       |  |                       |
|------------------------------|-------|--|-----------------------|
| Water Absorption:            | < .5% | Static COF:                              | Wet: ≥0.60 Dry: >0.60 |
| Shade Variation (1, 2, 3, 4) | V3    | Dynamic COF:                             | N/A                   |
| Scratch Hardness (MOHS)      | N/A   | Breaking Strength:                       | ≥ 1300N               |
| Frost Resistant:             | Yes   | Thermal Shock Resistance:                | Yes                   |
| PEI/Abrasion Resistance:     | IV    | Deep Abrasion Test <175mm <sup>2</sup> : | No                    |
| Chemical Resistance:         | GB    |  |                       |

## PACKING INFORMATION - 9x36 *Please inquire with Customer Service for additional sizes*

|                        |        |                     |          |
|------------------------|--------|---------------------|----------|
| SqFt per Carton:       | 8.75   | Pieces per Carton:  | 4        |
| SqFt per Pallet:       | 420.00 | Pounds per SqFt:    | 4.53 Lbs |
| Boxes per Pallet:      | 48     | SqFt per Container: | 10,080   |
| Pallets per Container: | 24     |                     |          |

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".