

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

CHALET

TECHNICAL CHARACTERISTICS

Available Formats:	6x36	Glaze Application Method:	HDIT Inkjet
Style Description:	Rustic/Reclaimed	Number of Faces/Screens:	27
Visual Characteristics:	Wood	Number of Punches/Molds:	9
Thickness in mm:	10 mm	Body Type:	Porcelain (<.5%)
Modular Suitability:	Yes	Color Body Unglazed:	Yes
Application:	Residential/Commercial	Surface Type:	Matte
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	Minimum 1/8"
Rectified:	Yes		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	Wet: 0.65 Dry: 0.9
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	N/A
Scratch Hardness (MOHS)	7	Breaking Strength:	N/A
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION

SqFt per Carton:	13.07	Pieces per Carton:	9
SqFt per Pallet:	627.36	Pounds per SqFt:	4.59
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".