With the G-STRETCH-System, you stretch your screen frames in a simple and professional way.



Grünig

Best results due to the revolutionary G-STRETCH technology.



G-STRETCH 201 DUPLEX clamp

- Grünig IP-system: preliminary requirement for excellent stretching results
- Extremely high retention force for all the commonly used meshes
- Automatic amplification of the closing force
- No parts which require any readjustment
- The clamps are equipped with their own V2A guideway system
- Ergonomic design and handling
- High-quality aluminium construction



G-STRETCH 202 Pneumatic clamp

- A cost-efficient first step into professional stretching
- Modular extension possible in 250 mm / 10 " increments p/side
- Pneumatic stretching with highest precision/reproducibility
- Pneumatic two-circuit control panel
- Automatic pre-bowing of the screen frames
- Simple adjustment of the frame profile height
- DUPLEX clamps offering max. retention force
- Automatic stretching system A2 up to 50 programs (optional)



G-STRETCH 210 Mechanical stretching machine

- Maximum frame format of 3000 x 3000 mm / 118" x 118"
- Instant adjustment of the machine size
- Optimum handling and highest precision
- Automatic pre-bowing of the screen frames
 Locking function for pre-bowing of screen frames
- No contact between frame and mesh during stretching process
- A supporting board allows to stretch many frames at the same time
- DUPLEX clamps sliding in V2A guideways



G-STRETCH 215A Pneumatic stretching machine

- Maximum frame format of 3000 x 3000 mm / 118" x 118"
- Instant adjustment of the machine size
- Automatic pre-bowing of the screen frames
 No contact between frame and mesh
- No contact between frame and mesh during stretching process
 Pneumatic stretching with highest
- precision / reproducibility
- A supporting board allows to stretch many frames at the same time
- DUPLEX clamps sliding in V2A guideways
 Automatic stretching system A2 up to 50 programs



G-STRETCH 270A Electro-mechanical stretching machine

- Maximum frame format of 1500 x 1500 mm / 59" x 59"
- Instant adjustment of the machine size
- Optimum handling and highest degree of precision
- Automatic pre-bowing of the screen frames
- No contact between frame and mesh during stretching process
 A supporting based allows to stratch
- A supporting board allows to stretch many frames at the same time
- DUPLEX clamps sliding in V2A guideways
- Automatic stretching A2 with touch screen control and 50 programs



G-STRETCH 281A Multiscreen stretching machine XL

- Maximum stretching surface of 4500 x 12000 mm / 177" x 472"
- High yield with a minimum of mesh consumption
- Simultaneous handling of several screen frames (Multiscreen)
- Adjustable stretching speeds for warp and weft directions
- No contact between frame and mesh during stretching process
- Easy setting of the desired stretching angle
- DUPLEX clamps sliding in V2A guideways
- Automatic stretching A2 with touch screen control and length measuring system

Grünig

Grünig-Interscreen AG Ringgenmatt 14 CH-3150 Schwarzenburg Switzerland Phone +41 31 734 2600 Fax +41 31 734 2601 www.grunig.ch mail@grunig.ch