



3-1/8" OD X 1.250" ID DRILL COLLAR, SLICK, AISI 4145, 2-7/8" HT PAC

## DRILL COLLAR BODY

Nominal OD (in)	3-1/8
Nominal ID (in)	1.250
Pipe Wall Thickness (in)	0.938
Surface Finish	SLICK
Grade	AISI 4145
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	6.443
Cross Sectional Area OD (in <sup>2</sup> )	7.670
Cross Sectional Area ID (in <sup>2</sup> )	1.227
Section Modulus (in <sup>3</sup> )	2.919
Polar Section Modulus (in <sup>3</sup> )	5.839
Momet of Inertia Drill Collar Body (in <sup>4</sup> )	4.56
Polar Moment of Inertia Drill Collar Body (in <sup>4</sup> )	9.12

## DRILL COLLAR CONNECTION

Connection	2-7/8" HT PAC
OD (in)	3.125
ID (in)	1.250
Torsional Strength (lbs/ft)	10,300
Tensile Yield Strength (lbs)	331,100
Minimum Make-up Torque (lbs/ft)	5,100
Maximum Make-up Torque (lbs/ft)	6,200

## DRILL COLLAR ASSEMBLY

Adjusted Weight (lbs/ft)	21.65
Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	0.34
Closed End Displacement (gal/ft)	0.40
Fluid Capacity (gal/ft)	0.06
Drift Size (in)	1.125

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.