

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

CHEROKEE

## TECHNICAL CHARACTERISTICS

Available Formats:	6X24		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	matt	Number of Faces/Screens:	24
Thickness in mm:	8.7	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Grey
Recycled Content: Post or Pre Customer		Surface Type:	Textured
Rectified:	No	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	.62
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GLA/GHA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.41	Pieces per Carton:	19
SqFt per Pallet:	1104.60 SF	Pounds per Carton:	
Boxes per Pallet:	60	SqFt per Container:	
Pallets per Container:	15		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".