



TITAN SYN SN SAE 5W-30

Ultra High Performance, extreme fuel-economy oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.

Description

TITAN SYN SN SAE 5W-30 is an ultra high performance gasoline engine oil based on innovative engine oil technology. The modern and reliable additive technology secures best performance at all running conditions.

This Ultra High Performance Engine Oil can be used all over the year. The good cold flow properties of TITAN SYN SN SAE 5W-30 are ensuring fastest lubrication at all parts of the engine. Friction and wear will be reduced and by that the fuel efficiency improved.

TITAN SYN SN SAE 5W-30 guaranties engine durability under city conditions as well as under top speed highway running conditions.

Application

TITAN SYN SN SAE 5W-30 shall be used for passenger cars and light duty vehicles with gasoline engines. As all season's motor oil, TITAN SYN SN SAE 5W-30 offers good cold start and fuel economy in the winter as well as high thermal stability in summer.

TITAN SYN SN SAE 5W-30 can be mixed with other similar type high quality hydrocarbon based engine oils. Preferably TITAN SYN SN SAE 5W-30 should not be mixed with other engine oil to keep its full performance.

Advantages/Benefits

- Multi-purpose use in many different cars
- Good cold start performance
- Very good engine cleanliness
- High thermal stability.
- Fuel savings at all running conditions
- Low evaporation loss
- Sustainable wear protection for all engines

Specifications

- API SN
- ILSAC GF-5

Product Code 173 - 15/08/2013 Page 1

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product

ALHAMRANI FUCHS PETROLEUM SAUDI ARABIA LIMITED

P. O. Box 7103, Jeddah 21462, Saudi Arabia

Telephone +966 2 6635 666 FAX +966 2 6634 094 www.fuchs.com.sa

ISO 9001:2008
ISO 14001:2004
OHSAS 18001:2007
CERTIFIED



CHARACTERISTICS

Density @ 35 °C	0.8382	g/ml	ASTM D 4052
Flash Point, CoC	228	°C	ASTM D 92
Pour Point	-36	°C	ASTM D 97
Dynamic Viscosity @ - 30 °C	4580	CP	ASTM D 5293
Kinematic Viscosity @ 40 °C	60.4	mm ² /s	ASTM D 445
Kinematic Viscosity @ 100 °C	10.29	mm ² /s	ASTM D 445
Viscosity Index	159	-	ASTM D 2270
TBN	6.8	mg KOH/g	ASTM D 2896

Product Code 173 - 15/08/2013 Page 2

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product

ALHAMRANI FUCHS PETROLEUM SAUDI ARABIA LIMITED

P. O. Box 7103, Jeddah 21462, Saudi Arabia

Telephone +966 2 6635 666 FAX +966 2 6634 094 www.fuchs.com.sa

ISO 9001:2008
ISO 14001:2004
OHSAS 18001:2007
CERTIFIED

