



## **LED 8" COMMERCIAL DOWNLIGHT**

LED 8" LED COMMERCIAL DOWNLIGHT SERIES has been designed and engineered for commercial application, retrofitting existing recessed 8" can housing as well as new construction application. It has a CRI > 80 with high system efficiency. It is suitable for offices, retails, hospitals, hotels, schools, warehouses and factories.

## **FEATURES**


- Superior quality white LED light
- Driver efficiency > 85%
- Aluminum heat sink
- Comfortable diffused light
- High thermal comductivity
- Efficacy > 75 Lm/W
- Dimmable
- High Power Factor > 0.9
- Standard lifetime 50,000 hours
- High CRI > 80
- Working temperature: -4°F~+122°F
- Input Voltage 100-277VAC

## **OPTIONS**

- TRIM white or other color
- Reflector Specular or Matte diffuse
- Diffuser Frosted or Opal



5 Years Warranty







Manufactured by:



Model	Watts	СТТ	Lumens	CRI	Size	PF	Cover
GAI-04-RD-8-20W-X	20	2700K, 3000K, 3500K, 4000k	( 1500	>80	A)8.19"x(B)9.29"		
GAI-04-RD-8-29W-X	29	2700K, 3000K, 3500K, 4000k	ζ 2000	>80	(A)8.19"x(B)9.29"		Frosted
GAI-04-RD-8-34W-X	34	2700K, 3000K, 3500K, 4000k	ζ 2500	>80	(A)8.89"x(B)9.29"	>0.9	Opal
GAI-04-RD-8-40W-X	40	2700K, 3000K, 3500K, 4000k	3000	>80	(A)8.89"x(B)9.29"		opu.
GAI-04-RD-8-42W-X	42	2700K, 3000K, 3500K, 4000k	3500	>80	(A)8.89"x(B)9.29"		