

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Avorio**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	Bianco (42), De brescia (40), & Grigio (32)
Thickness in mm:	10mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	N/A
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte/Flat
Rectified:	No	Recommended Grout Joint:	ANSI Standards

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	250 lbs or greater
Frost Resistant:	Yes	Thermal Shock Resistance:	resistant
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	Resistant		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.71	Pieces per Carton:	8
SqFt per Pallet:	628.40	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	16		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".