

5-1/2" OD DRILL PIPE, 24.70 PPF, 6.625" OD X 4.000" ID, VM-105 DP SS, VX™ 54-L

## DRILL PIPE BODY

Nominal Weight (lbs/ft)	24.70
Grade	VM-105 DP SS
Type of Upset	IEU

	New	Premium
Nominal OD (in)	5-1/2	5.334
Nominal ID (in)	4.670	4.670
Pipe Wall Thickness (in)	0.415	0.332
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	6.630	5.217
Cross Sectional Area OD (in <sup>2</sup> )	23.758	22.346
Cross Sectional Area ID (in <sup>2</sup> )	17.129	17.129
Section Modulus (in <sup>3</sup> )	7.844	6.145
Polar Section Modulus (in <sup>3</sup> )	15.688	12.290
Torsional Strength (lbs/ft)	79,200	62,000
Tensile Strength (lbs)	696,000	548,000
Burst Pressure (psi)	13,860	12,700
Collapse Pressure (psi)	14,010	9,630

## DRILL PIPE CONNECTION

OD (in)	6.625
ID (in)	4.000
Pin Tong Length (in)	10.00
Box Tong Length (in)	15.00
Connection	VX™ 54-L
Torsional Strength (lbs/ft)	68,800
Tensile Yield Strength (lbs)	1,140,000
Tool Joint/Pipe Body Torsional Ratio (New)	0.87

## DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.43
Closed End Displacement (gal/ft)	1.23
Fluid Capacity (gal/ft)	0.84
Drift Size (in)	3.875
Adjusted Weight (lbs/ft)	28.02

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.