

4.000" OD, HWDP, WELDED, STANDARD, 4.875" OD x 2.563" ID, DPM-ST39

HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	4.000
Nominal ID (in)	2.563
Pipe Grade	AISI 1340
Heavy Weight Type	STANDARD
HWConstruction	WELDED
Pipe Wall Thickness (in)	0.719
Cross Sectional Area of Pipe Body (in ²)	7.407
Cross Sectional Area OD (in ²)	12.566
Cross Sectional Area ID (in ²)	5.159
Section Modulus (in ³)	5.224
Polar Section Modulus (in ³)	10.448
Torsional Strength (lbs/ft)	32,660
Tensile Strength (lbs)	481,593
Burst Pressure (psi)	23,776
Collapse Pressure (psi)	19,162

HEAVY WEIGHT DRILL PIPE CONNECTION

Tool Joint Grade	VM-65 HW MS
OD (in)	4.875
ID (in)	2.563
Pin Tong Length (in)	18.00
Box Tong Length (in)	18.00
Connection	DPM-ST39
Torsional Strength (lbs/ft)	33,052
Tensile Yield Strength (lbs)	724,069
Minimum Make-up Torque (lbs/ft)	16,500
Recommended Make-up Torque (lbs/ft)	19,800
Maximum Make-up Torque (lbs/ft)	23,100
Tool Joint/Drill Pipe Torsional Ratio (New)	1.01
Balanced OD	5.056

HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.45
Closed End Displacement (gal/ft)	0.72
Fluid Capacity (gal/ft)	0.27
Drift Size (in)	2.313
Adjusted Weight (lbs/ft)	29.44
Internal Plastic Coating	TK34P
Hardbanding	ARNCO 100 XT

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.