



SHEET METAL PRODUCTS

COMMERCIAL GRADE FLANGE & GASKET FITTINGS

STRAIGHT, CONICAL and HETO FITTINGS

The flange and gasketed fittings are of similar construction to our spin in style fittings with the addition of a 1" galvanized mounting flange and a 1/8" PE foam gasket coated with a pressure sensitive adhesive for easy mounting and reduced leakage. This results in a reduction in labor installation and less leakage than with traditional spin in fittings. The flange and gasket feature is available in straight, conical and rectangular to round fitting styles. All fittings are fabricated with a beaded collar for non slip positioning of draw bands or gear clamps. Our damper blades are fabricated with quality hardware including stamped handles, spring loaded & solid bearings and stand offs with locking wing nuts.

STRAIGHT



CONICAL



HETO



TECHNICAL INFORMATION

FLSOC

- Straight Fitting
- 1" Galvanized Flange
- 1/8" PE Foam Gasket
- Pressure sensitive Adhesive
- Beaded sleeve
- Galvanized steel 26/24ga
- Stainless steel 304/316
- Aluminum 3003
- 4" to 20" diameters

FLCSOC

- Conical Fitting
- 1" Galvanized Flange
- 1/8" PE Foam Gasket
- Pressure sensitive Adhesive
- 1" radius opening
- Beaded sleeve
- Galvanized steel 26/24ga
- Stainless steel 304/316
- Aluminum 3003
- 4" to 20" diameters

HETO

- Rectangular to Round
- 1" Galvanized Flange
- 1/8" PE Foam Gasket
- Pressure sensitive adhesive
- Closed corners
- Beaded Sleeve
- Galvanized steel 26/24ga
- Stainless steel 304/316
- Aluminum 3003
- 5" to 20" diameters

We offer regular Spin-on Collars, Bellmouth Take-offs, Bellmouth collars with Direct-Drive Heavy Duty Regulators, Air-Tite Connectors and High Velocity Angle Boots. These products simplify installation and enhance design efficiencies. Shop drawings are available upon request.