



23010 Ryen Dr NW, Ste C. • Poulsbo, WA 98370-6406  
(360) 598-3090 • FAX (206) 494-7787  
email: info@tarpinnovators.com

## **PRODUCT SPECIFICATIONS**

### **61" 22oz VINYL PVC Coated Polyester TI P/N: VI-22-061-100-IP**

#### **BASE FABRIC**

<b>Denier</b>	Woven Polyester Scrim
<b>Base Fabric</b>	1300D x 1300D / 16 x 16
<b>Fabric Count</b>	18 Warp / 18 Weft
<b>Base Weight</b>	6 oz / yard <sup>2</sup>

#### **COATED FABRIC**

<b>Overall Weight</b>	22 oz / yard <sup>2</sup>
<b>Type of Coating</b>	PVC
<b>Width</b>	61"
<b>Color</b>	Black, Red, Green, Blue, Orange, White, Yellow

#### **MECHANICAL PROPERTIES**

<b>Tensile Strength (Grab)</b>	674 lbf x 532 lbf	(FS-191A-5100)
<b>Tensile Strength (Strip)</b>	429 lbf x 351 lbf / 2.5 cm	(FS-191A-5102)
<b>Tear Strength (Tongue)</b>	161 lbf x 139 lbf	(FS-191A-5134)
<b>Adhesion Strength</b>	22 lbf / 5 cm	(FS-191A-5970)
<b>Cold Crack Resistance</b>	-40° C	(FS-191A-5874)

**U.V. Resistant**  
**Mildew and Rot Resistant**

This information is offered for your general guidance only. Above values represent typical data and are subject to slight variations. It is accurate to the best of our knowledge at the time of printing but is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to safe handling of this material. No warranty is expressed or implied regarding the accuracy of these data.