JUMBO SERIES





- Capacity pump o16 m3/h
- Machine cycle 15-30 sec.
- Dimensions (l x w x h) 525 x 450 x 385 mm
- Weight 48 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,55 kW

For Sales and Service Contact



Dussen Pty Ltd 3/70 Andrew St Wynnum. Brisbane, QLD 4178

PH: 07 3393 6552 FAX: 07 3393 6352 sales@dussen.com.au www.dussen.com.au

FAST AND ROBUST VACUUMPACKAGING MACHINES WITH WORLD WIDE REPUTATION

- · Compact system with "Jumbo" results
- Clear added value for company and product
- Modern table models with proven packaging achievements
- Professional vacuumpackaging for a attractive price
- Digital command and maintenance functions
- User friendly and low maintenance
- Easy to clean

FOOD PRODUCTS

Retail Trade - Restaurants - Catering - Supermarkets (meat, poultry, fish, cheese, vegetables etc.)

- Longer shelf life (no contamination or bacteria's multiplication)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Cost savings due to longer shelf life (larger purchasing orders, efficient cooking time spreading)
- Increased turnover due to longer shelf life (more variation and spread in product range)
- Professional product presentation
- · Optimal packaging contributes to food safety and HACCP standards
- Ideal for cuisine-sous-vide applications

INDUSTRIAL PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products -Textiles - Laboratories - Automotive - etc.

- Moisture free packaging
- · Scrapes and scratches free solution
- Air and dust free packaging
 Fraud resistant packaging
- Volume reducing packaging
 Sterile and contamination
- free packaging

SPECIFICATIONS

GENERAL

- Table model
- Suitable for a large range of product and dimensions
- Full stainless steel conception
- Deep-drawn vacuum chamber with round corners for optimal hygiene
- Transparent lid
- · Easily removable wireless sealing bars
- · Insert plates for fast vacuum cycle and product
- Gentle air flow return for better product protection
- Compact budget

PACKAGING FUNCTIONS

Vacuum

Optimal final vacuum 99,80% (2 mbar)

SEALING FUNCTIONS

- Double seal
- 2 x 3.5 mm convex sealing wire for product remains elimination and strong hermetic seals
- Cut-off seal
 - 1 x 3.5 mm convex sealing wire and
 - 1 x 1.1 mm round cut-off wire for hygienic and attractive product presentation.

OPERATIONAL CONTROL FUNCTIONS

Time control

Command in seconds for vacuum and seal.

SUPPORT CONTROL FUNCTIONS

- STOP button for partial/full cycle interruption
- Digital maintenance program for pump
- · Automatic reminder for oil replacement
- · Service detection device

OPTIONAL FUNCTIONS / ACCESSORIES

- Inclined plate for efficient packing of liquid products
- Connection for external vacuuming food containers
- Service kit for standard maintenance
- · Trolley with shelves and castors

















