



SUBMITTAL DATA
SHEET METAL FITTINGS

CONICALS

Conical Spin Fittings

(Tolerance on all sizes +/- 1/8")

Nom. Dia.	Sleeve O.D.	Cone O.D	Length No Damper	Length With Damper	Cut Hole Size
4"	3.875	5.875	7.5	10"	5.75
6"	5.875	7.875	7.5	10"	6.75
8"	7.875	9.875	7.5	10"	7.75
10"	9.875	11.875	7.5	10"	11.75
12"	11.875	13.875	7.5	10"	13.75
14"	13.875	15.875	7.5	10"	15.75
16"	15.875	17.875	7.5	10"	17.75
18"	17.875	19.875	7.5	10"	19.75
20"	19.875	21.875	7.5	10"	21.75

Fitting Model

- CSOC No Damper
- CSOCD Standard Damper – Spring End Bearing with Handle and Wingnut
- CSOCD1 2" Damper Handle Extension
- CSOCD3 2" Buildout – 3/8" square shaft, Nylon End Bearings and Locking Handle

Standard Construction

- Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above

Gauge Options

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other _____

Material Options

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other _____