

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

GUATEMALA

TECHNICAL CHARACTERISTICS

Available Formats:	9x47	Glaze Application Method:	H.D.I.T. Inkjet
Style Description:		Number of Faces/Screens:	10
Visual Characteristics:	Wood	Number of Punches/Molds:	
Thickness in mm:	8.7mm	Body Type:	Porcelain
Modular Suitability:	No	Color Body Unglazed:	Porcelain (White Body)
Application:	Residential/Commercial	Surface Type:	Matte, Textured
Recycled Content: Post or Pre Customer		Recommended Grout Joint:	>5
Rectified:	No		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.49
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300n
Frost Resistant:	Yes	Thermal Shock Resistance:	APPLY
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GLA/GHA		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.08	Pieces per Carton:	6
SqFt per Pallet:	759.36	Pounds per Carton:	
Boxes per Pallet:	42	SqFt per Container:	
Pallets per Container:	18		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".