



## Standard Series CCTV Monitor

<b>Specification</b>	
Model	ADE-110W1
<b>Display</b>	
Panel Type	LED Panel
Screen Size	10.1" diagonal
Aspect Ratio	16:10
Resolution	1280 x 800
Viewable Size (mm)	216.96 (H) x 135.6 (V)
Pixel Pitch (mm)	0.1695
Viewing Angle (L/R/B/T)	80° / 80° / 80° / 80°
Contrast Ratio	800:1
Luminance (Typ.)	250 cd/m <sup>2</sup>
Display Color	262K
Response Time	30ms
<b>Input Connector</b>	
D-SUB	1
HDMI	1
BNC (Analog)	1
Audio Stereo Phone jack	1
<b>Output Connector</b>	
BNC (Analog)	1
<b>Input Signal</b>	
Analog	CVBS
D-SUB	VESA Modes
HDMI	480i/480p/576i/576p/720p/1080i/1080p
<b>Analog Input spec.</b>	
CVBS	1.0Vp-p (With Sync) NTSC. PAL
D-SUB	D-sub 15pin, FH: 31.5K~80 kHz, FV: 50~75 Hz
<b>Digital Input spec.</b>	
HDMI	Panel Link T.M.D.S HDMI-1.4
<b>Others</b>	
Power input	Power adapter: AC 100 ~ 240V / Monitor: DC12V
Power Management	VESA DPMS compatible
Power Consumption	13W (max.)
Speaker power	2W x 2
Accessory	Users Manual, VGA Cable, Stereo Audio cable, 12V Power Adapter, Power cord
Physical Dimension WxHxD	9.67"x8.3"x3.58"
Packing Dimension WxHxD	11.2"x10.1"x4.2"
Weight N.W./G.W.	1.8 lb/3.3 lb
VESA Mount Pattern	75x75 mm <sup>2</sup>
Operating temperature/Humidity	0°C ~ 40°C (32°F ~ 104°F) / 10%~85%*
Storage temperature/Humidity	-20°C ~ 60°C (-4°F ~ 140°F) / 10%~95%*
Regulation	CE, FCC, WEEE, RoHS

\* No-condensing

Note: Specifications are subject to change without notice.